

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI) | COMPLAINT/DISCOVERY (CI) |
|---|--|
| AIRS ID#: 0310408 DATE: <u>2/9/06</u> | ARRIVE: DEPART: |
| FACILITY NAME: SAWH'S INC | |
| FACILITY LOCATION: 5808-1 Normandy Blvd | |
| JACKSONVILLE 322 | 05 |
| RESPONSIBLE OFFICIAL: PAUL SAWH | PHONE: (904)781-9484 |
| CONTACT NAME: Zenna Shaw | PHONE: same |
| REMITTANCE YEAR: 2005 ENTITL | EMENT PERIOD: 10/8/2001 / 10/8/2006 (effective date) (end date) |
| | |
| PART I: INSPECTION COMPLIANCE STATUS (ch | leck ☑ only one box) |
| IN COMPLIANCE MINOR Non-COMI | PLIANCE SIGNIFICANT Non-COMPLIANCE |
| | |
| PART II: FACILITY CLASSIFICATION - Rule 62-2 (check ☑ only one box in A) | 213.300 FAC |
| A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source | 2. <u>New small area source</u> dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source by the large area source description of the large area source by the large area source description of the large area source by the large area source description of the large |
| dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits | dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91) |
| B. The total quantity of perchloroethylene (perc) pu cleaning facility was 105 gallons. | rchased within the preceding 12 months by this dry |

| PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC | (check 🗹 only one box |
|--|--|
| Does the responsible official of the dry cleaning facility: | for each question) |
| 1. Store perc, and wastes containing perc, in tightly sealed & impervious containers? | \bigvee Yes \square No \square N/A |
| 2. Examine the containers for leakage? | \bigvee Yes \square No \square N/A |
| 3. Close and secure machine doors except during loading/unloading? | Yes No |
| 4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal? | Yes No N/A |
| 5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications? | Yes No N/A |

| PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form) | | | | | | |
|---|---|------|---------------------|-----------------------|--|--|
| 1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V. | | | | | | |
| | 2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below. | | | | | |
| 3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i> | | | | | | |
| | 4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below. | | | | | |
| А. | Has the responsible official of all <u>existing large area & new sources</u> : | | ☑ only each ques | one box for stion) | | |
| 1. | Equipped all machines with the appropriate vent controls? | Yes | No | | | |
| 2. | Equipped dry-to-dry machines with a closed-loop vapor venting system? | ⊠Yes | No | N/A | | |
| 3. | Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? | ⊠Yes | No | □N/A | | |
| 4. | Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? | ⊠Yes | No | | | |
| 5. | Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? | Yes | No | □N/A | | |
| 6. | Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? | ⊠Yes | No | | | |

| PA | RT IV: <u>PROCESS</u> <u>VENT</u> <u>CONTROLS</u> – Rule 62-213.300 FAC (continued) | |
|----|--|---|
| B. | Does the responsible official of an existing large or new large area source also: | (check ☑ only one box for each question) |
| 1. | Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? | □Yes □No |
| | Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? a) Is the temperature differential equal to, or greater than 20° F? | - □Yes □No □N/A □Yes □No □N/A |
| 3. | Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? | □Yes □No □N/A |
| | a) Is the perc concentration equal to, or less than 100 ppm? | Yes No N/A |
| | Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | □Yes □ No □ N/A |
| | Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils? | - Yes No N/A |
| 6. | Route airflow to the carbon adsorber (if used) at all times? | Yes No N/A |
| | | |

| PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC | | | | |
|--|---|--|--|--|
| Does the responsible official: | (check ☑ only one box for each question) | | | |
| 1. Maintain receipts for perc purchased? | 🛛 Yes 🗌 No | | | |
| 2. Maintain rolling monthly total of yearly perc consumption? | - 🛛 Yes 🗌 No | | | |
| 3. Maintain leak detection inspection and repair reports for the following: | | | | |
| a) documentation of leaks repaired w/in 24 hrs? or; | Xes No N/A | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | Yes No N/A | | | |
| 4. Maintain calibration data? (for applicable direct reading instruments) | Yes No N/A | | | |
| 5. Maintain exhaust duct monitoring data on perc concentrations? | - 🗌 Yes 🗌 No 🖾 N/A | | | |
| 6. Maintain a startup/shutdown/malfunction plan? | - 🛛 Yes 🗌 No | | | |
| 7. Maintain deviation reports? | 🗌 Yes 🗌 No 🖾 N/A | | | |
| a) Problem corrected? | 🗌 Yes 🗌 No 🖾 N/A | | | |
| 8. Maintain a compliance plan, if applicable? | Yes No X/A | | | |
| | | | | |

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

| detection and repair inspection? |
|--|
| 2. Does the facility maintain a leak log? |
| 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves XYes No N/A g) Muck cookers Yes No N/A b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A c) Filter gaskets and seating Yes No N/A i) Exhaust dampers Yes No N/A d) Pumps Yes No N/A j) Diverter valves Yes No N/A e) Solvent tanks and containers Yes No N/A f) Water separators Yes No N/A |
| 4. Which method(s) of detection (is/are) used by the responsible official? |
| a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) |
| Brenda Johnson 2/9/06 |
| Inspector's Name (Please Print)Date of Inspection |
| 2/9/07 |

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: