STATION NOTECION
FLORIDA

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)		
AIRS ID#: 0090154 DATE: <u>2/13/08</u>	ARRIVE: <u>1:08 pm</u> DEPART: <u>1:28 pm</u>		
FACILITY NAME: JOSHUA CLEANERS			
FACILITY LOCATION: 1450 N Courtenay Pkwy	#27		
MERRITT ISLAND 32	2953		
OWNER/AUTHORIZED REPRESENTATIVE: FRAM	NCO OWUSU PHONE: (407)452-0462		
CONTACT NAME:	PHONE:		
ENTITLEMENT PERIOD: 10/10/2002 / 10/10/200 (effective date) (end date))7 Facility may be operating without Entitlement!		
	· 🗖 · · · 、		
PART I: INSPECTION COMPLIANCE STATUS (cho			
IN COMPLIANCE MINOR Non-COMP	LIANCE SIGNIFICANT Non-COMPLIANCE		
PART II: <u>FACILITY</u> <u>CLASSIFICATION</u> - Rule 62-213.300 FAC (check ☑ only one box in A) A. 1. <u>Existing small area source</u> 2. <u>New small area source</u>			
dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)		
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)		
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits			
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was gallons.			

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No □N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)				
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.			
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>			
	4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.			
А.	Has the responsible official of all <u>existing large area & new sources</u> : (check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls? [Yes No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system? Yes No			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? Yes No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? [Yes]No]N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? [Yes]No			

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)		
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A	
	a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A	
PA	PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		
Does the responsible official: (check I only one box for each question)			
1.	Maintain receipts for perc purchased?	Yes No	
2.	Maintain rolling monthly total of yearly perc consumption?	Yes No	

PART V: <u>RECORDREEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(check \blacksquare only one box for
Does the responsible official:		each question)
1.	Maintain receipts for perc purchased?	Yes No
2.	Maintain rolling monthly total of yearly perc consumption?	Yes No
3.	Maintain leak detection inspection and repair reports for the following:	
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A
4.	Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A
5.	Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A
6.	Maintain a startup/shutdown/malfunction plan?	Yes No
7.	Maintain deviation reports?	Yes No N/A
	a) Problem corrected?	Yes No N/A
8.	Maintain a compliance plan, if applicable?	Yes No N/A
1		

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Yes No			
2. Does the facility maintain a leak log? Yes No				
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves Yes No N/A g) Mu b) Door gaskets and seating Yes No N/A h) Still c) Filter gaskets and seating Yes No N/A i) Exh d) Pumps Yes No N/A j) Div e) Solvent tanks and containers Yes No N/A k) Can f) Water separators Yes No N/A 	Ils Yes No N/A aust dampers Yes No N/A erter valves Yes No N/A			
4. Which method(s) of detection (is/are) used by the responsible official?				
 a) Visual examination (condensed solvent on exterior surfaces)				
Rodell Rice 2/13/08				
Inspector's Name (Please Print)	Date of Inspection			
	N/A			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: The owner purchased a petroleum use machine.