

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

AIRS ID#: 0090156 DATE: March 22, 2007 ARRIVE: 10:45 DEPART: 11:15 FACILITY NAME: PLAZA CLEANERS FACILITY LOCATION: 754 Apollo Blvd MELBOURNE 32935-5068					
FACILITY LOCATION: 754 Apollo Blvd					
MELBOURNE 32935-5068					
RESPONSIBLE OFFICIAL: RANDAL KILLEBREW PHONE: (321)242-8811					
CONTACT NAME: PHONE:					
REMITTANCE YEAR: 2006 ENTITLEMENT PERIOD: 7/7/2005 / 7/7/2010 (effective date) (end date)					
PART I: INSPECTION COMPLIANCE STATUS (check I only one box) IN COMPLIANCE MINOR Non-COMPLIANCE SIGNIFICANT Non-COMPLIANCE					
PART II: FACILITY CLASSIFICATION (check I only one box in A) Rule 62-213.300 FAC A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91) 2. New small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91) 2. New small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr (constructed before 12/9/91) 4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit dry for General Permit dry exceeds above limits					

PART III: <u>GENERAL</u> <u>CONTROL</u> <u>REQUIREMENTS</u> – Rule 62	$(check \square only one box)$
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervi	ious containers? Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Xes No
4. Drain cartridge filters in their housing or in sealed containers for at prior to disposal?	
5. Maintain solvent-to-carbon ratios and steam pressure for carbon ad according to the manufacturer's specifications?	

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (Refer to Part II-A.1.-4. Classification: page 1 of 4, this form) 1. If the facility classification is a Existing small area source, no controls are required. Proceed to Part V. 2. If the facility classification is a **New small area source**, the machine should be equipped with a refrigerated condenser. Complete section A. below. 3. If the facility classification is a **Existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 4. If the facility classification is a <u>New large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below. (check \blacksquare only one box for Has the responsible official of all existing large area & new sources: А. each question) Equipped all machines with the appropriate vent controls? ------ XYes No 1. 2. Equipped dry-to-dry machines with a closed-loop vapor venting system? ------ XYes N/A Equipped the condenser with a diverter valve so airflow will be directed away 3. from the condenser upon opening the door? ------ Xyes No N/A Measured and recorded the temperature of the outlet exhaust stream of a 4. refrigerated condenser on a weekly basis? ------ XYes No Repaired or adjusted the equipment within 24 hours if the exhaust temperature of 5. the condenser exceeded 45° F? ------ Yes No N/A Conducted all temperature monitoring after an appropriate cool-down period and 6. after verifying that the coolant had been completely charged? ------ XYes No

PA	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No		
	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A		
	a) Is the temperature differential equal to, or greater than 20° F?	Yes No N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A		
l	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A		
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A		
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for		
Does the responsible official: each question)				
1.	Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No		
2.	Maintain rolling monthly total of yearly perc consumption?	Yes INO		
3.	Maintain leak detection inspection and repair reports for the following:			

PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check \blacksquare only one box for	
D	oes the responsible official:	each question)	
1.	Maintain receipts for perc purchased?	Yes No	
2.	Maintain rolling monthly total of yearly perc consumption?	Yes 🗌 No	
3.	Maintain leak detection inspection and repair reports for the following:		
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A	
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A	
4.	Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A	
5.	Maintain exhaust duct monitoring data on perc concentrations?	Yes No X/A	
6.	Maintain a startup/shutdown/malfunction plan?	Yes 🗌 No	
7.	Maintain deviation reports?	Yes No N/A	
	a) Problem corrected?	- Yes No N/A	
8.	Maintain a compliance plan, if applicable?	Yes No N/A	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection? Image: Yes No 2. Does the facility maintain a leak log? Image: Yes No
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves b) Door gaskets and seating c) Filter gaskets and seating d) Pumps e) Solvent tanks and containers f) Water separators f) Water separators
4. Which method(s) of detection (is/are) used by the responsible official?
 a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) c) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) **(see below) e) Halogen leak detector e)
**If using direct-reading instrumentation, is the equipment: **
 Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) Yes Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) Yes Inspected for leaks and obvious signs of wear on a weekly basis? 3) Yes Kept in a clean and secure area when not in use? 4) Yes Verified for accuracy by use of duplicate samples (calorimetric only)? 5) Yes

Michael Young

Inspector's Name (Please Print)

March 22, 2007

Date of Inspection

March 22, 2008

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: There was a minor leak on a steem line that ran near the Dry cleaning unit, He had purchased the part already and is calling around for pricing on the repair work.