

## CHROMIUM ELECTROPLATING/ANODIZING



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS RE-INSPECTION		
AIRS ID#: 1030353 DATE: <u>2/9/09</u>	ARRIVE: <u>10:30 a.m.</u> DEPART: <u>11:00 a.m.</u>	
FACILITY NAME: ADTEC II		
<b>FACILITY LOCATION:</b> 5440 70th Ave North		
PINELLAS PARK 33781-4228		
OWNER/AUTHORIZED REPRESENTATIVE: DAVID SIDERI PHONE: (727)522-4653		
CONTACT NAME:	PHONE:	
ENTITLEMENT PERIOD: 6/26/2006 / 6/26/2011 (effective date) (end date)		
PART I: INSPECTION COMPLIANCE STATUS (check ✓ only one box)  ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE		
PART II: CLASSIFICATION – Rule 62-213.300 FAC Facility type(s)/applicable standard as indicated on notification form:  1. Hard Chromium Plating  a. Existing Large (0.015 mg/dscm)		
2. Decorative Chromium Plating/Anodizing		
a. <u>Chromic Acid Bath</u>	<ol> <li>Emissions of ≤ 0.01/mg/dscm (4.4x10<sup>-6</sup> gr/dscf)</li> <li>Surface tension of ≤ 45 dynes/cm (3.1x10<sup>-3</sup> lb-f/ft)</li> <li>(May only be selected if a wetting agent is used.)</li> </ol>	
b. <u>Trivalent</u> <u>Chromium</u> <u>Bath</u>	<ol> <li>With wetting agent</li></ol>	
c. <u>Chromium Anodizing</u>	<ol> <li>Emissions of ≤ 0.01 mg/dscm (4.4x10<sup>-6</sup> gr/dscf)</li> <li>Surface tension of 45 dynes/cm (3.1x10<sup>-3</sup> lb-f/ft)</li> <li>(May only be selected if a wetting agent is used.)</li> </ol>	

PART III: CONTROL TECHNOLOGY - Rule 62-213.300 FAC	
(Select control	
	DEVICE IN USE?
1. Composite Mesh Pad	☐Yes ☐No
2. Fiber Bed Mist Eliminator	
3. Packed Bed Scrubber	
4. Packed Bed Scrubber/Composite Mesh Pad  5. Foam Blanket Fume Suppressant	
6. Fume Suppressant w/ Wetting Agent	Yes □No
o. Maine suppressant with wetting rigent	
Has the facility conducted an initial performance test to establish monitoring parameters? (Not required for sources using a wetting agent or 1-inch foam blanket thickness)	⊠Yes □No □N/A
DARTHY DECORDATED INCORPORTING DECLUDENTING D. L. CA. 412. 200	(2)
PART IV: <u>RECORDKEEPING/REPORTING REQUIREMENTS</u> – Rule 62-213.300	(3)
Has the responsible official maintained the following records?	
1. Quarterly inspection records for add-on air pollution control devices and	
monitoring equipment. (applicable only to a facility using a packed bed scrubber	r, fiber-bed
mist eliminator, or composite mesh pad)	
2. Operations and Maintenance Plan (OMP). (applicable only to a facility using a	
scrubber, fiber-bed mist eliminator, or composite mesh pad)	- ∐Yes ∐No ⊠N/A
3. Maintenance records for the source, add-on pollution control devices, and	
monitoring equipment (equipment identified, date performed, description).	- ⊠Yes ∐No
4. Records of date of occurrence, duration, cause, and corrective action of each	A Maria Maria
malfunction of process, add-on pollution control device, and monitoring equipmer 5. Results of all performance tests	
6. Records of monitoring data. (not applicable to trivalent chromium baths using	
agent)	
ugenij	
Composite Mesh Pad	
Measure the pressure drop across the CMP daily	- Yes No
Packed Bed Scrubber	
Measure the pressure drop across the PBS and the inlet velocity daily	Yes No
Fiber-Bed Mist Eliminator	
Measure the pressure drop across the FBME and the upstream device daily	☐Yes ☐No
Packed Bed Scrubber/Composite Mesh Pad  Massayra the pressure due program the CMP deily	
Measure the pressure drop across the CMP dailyFoam Blanket Fume Suppressant	Yes No
Measure the foam blanket thickness at the appropriate interval	□Yes □No
Fume Suppressant w/ Wetting Agent	
Measure the surface tension at the appropriate interval	Yes No
7. Purchase records of wetting agent components.	
8. Records of the date and time that fume suppressants are added to the bath	
9. Records of rectifier capacity, if used to determine facility size	
10. Records of the total process operating time	- ⊠Yes □No
11. Records identifying specific periods of excess emissions	
12. Startup, Shutdown & Malfunction Plan	- ⊠Yes □No

Jeff Morris	2/9/09
Inspector's Name (Please Print)	Date of Inspection
	2/9/10
Inspector's Signature	Approximate Date of Next Inspection

**COMMENTS:** Chrome #2 tank: On June 10, 2008, the Chrome #2 Black tank was over 45 dynes/cm surface tension and 500 milliters of Brightguard was put into the tank. On November 20, 2008 the facility recorded 47 dynes/cm surface tension and another 500 ml was added. A record of the past compliance year is attached to the compliance file.

Decorative tank: On October 31, 2008, the Decorative tank was over 45 dynes/cm surface tension and 500 milliters of Brightguard was put into the tank. A record of the past compliance year is attached to the compliance file.[jm]