

CHROMIUM ELECTROPLATING/ANODIZING



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS		· / —	
AIRS ID#: 1030353 DATE: <u>10/8/09</u>	ARRIVE: <u>9:45</u>	DEPART: <u>10:30</u>	
FACILITY NAME: ADTEC II			
FACILITY LOCATION: 5440 70th Ave North			
PINELLA	AS PARK 33781-4228		
OWNER/AUTHORIZED REPRESENTATIVE: DAVID SIDERI PHONE: (727)522-4653			
CONTACT NAME: Halina Lesniak	PHO	NE: (
ENTITLEMENT PERIOD: 6/26/2006 / 6/26/2011 (effective date) (end date)			
PART I: <u>INSPECTION COMPLIANCE STATUS</u> (check ✓ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE			
PART II: CLASSIFICATION – Rule 62 Facility type(s)/applicable standard as in 1. Hard Chromium Plating a. Existing Large (0.015 mg/dscm) c. New (0.015 mg/dscm)	ndicated on notification form:	tisting facilities g average of	
2. <u>Decorative Chromium Plating/Anodizing</u>			
a. <u>Chromic</u> <u>Acid</u> <u>Bath</u>	 Emissions of ≤ 0.01/mg/dscm (4.4x10⁻¹ Surface tension of ≤ 45 dynes/cm (3.1 (May only be selected if a wetting age 	$\times 10^{-3}$ lb-f/ft)	
b. <u>Trivalent Chromium</u> <u>Bath</u>	 With wetting agent Without wetting agent ≤ 0.01mg/dscm 		
c. <u>Chromium Anodizing</u>	 Emissions of ≤ 0.01 mg/dscm (4.4x10⁻¹ Surface tension of 45 dynes/cm (3.1x10⁻¹) (May only be selected if a wetting age 	0^{-3} lb-f/ft)	

PART III: CONTROL TECHNOLOGY - Rule 62-213.300 FAC	
(Select control	
	DEVICE IN USE?
de rice)	<u>BEVICE</u> III COL.
1. Composite Mesh Pad	∏Yes ∏No
2. Fiber Bed Mist Eliminator	☐Yes ☐No
3. Packed Bed Scrubber	Yes No
4. Packed Bed Scrubber/Composite Mesh Pad	Yes No
5. Foam Blanket Fume Suppressant	□Yes □No
6. Fume Suppressant w/ Wetting Agent	⊠Yes □No
Has the facility conducted an initial performance test to establish monitoring parameters? (Not required for sources using a wetting agent or 1-inch foam blanket thickness)	⊠Yes ∐No ∐N/A
(1401 required for sources using a weiting agent of 1-inch fount blanket intekness)	
PART IV: <u>RECORDKEEPING/REPORTING REQUIREMENTS</u> – Rule 62-213.300	(3)
Has the responsible official maintained the following records?	
1. Quarterly inspection records for add-on air pollution control devices and	
monitoring equipment. (applicable only to a facility using a packed bed scrubbed	r fiher-hed
mist eliminator, or composite mesh pad)	
2. Operations and Maintenance Plan (OMP). (applicable only to a facility using a	
scrubber, fiber-bed mist eliminator, or composite mesh pad)	
3. Maintenance records for the source, add-on pollution control devices, and	
monitoring equipment (equipment identified, date performed, description)	- ⊠Yes □No
4. Records of date of occurrence, duration, cause, and corrective action of each	
malfunction of process, add-on pollution control device, and monitoring equipmen	nt. XYes No
5. Results of all performance tests	
6. Records of monitoring data. (not applicable to trivalent chromium baths using	
agent)	
Composite Mesh Pad	
Measure the pressure drop across the CMP daily	- Yes No
Packed Bed Scrubber	
Measure the pressure drop across the PBS and the inlet velocity daily	Yes No
Fiber-Bed Mist Eliminator	
Measure the pressure drop across the FBME and the upstream device daily	☐Yes ☐No
Packed Bed Scrubber/Composite Mesh Pad	
Measure the pressure drop across the CMP daily	Yes No
Foam Blanket Fume Suppressant	-
Measure the foam blanket thickness at the appropriate interval	⊠Yes □No
Fume Suppressant w/ Wetting Agent	
Measure the surface tension at the appropriate interval	
7. Purchase records of wetting agent components.	
8. Records of the date and time that fume suppressants are added to the bath	
9. Records of rectifier capacity, if used to determine facility size	
10. Records of the total process operating time	
11. Records identifying specific periods of excess emissions	
12. Startup, Shutdown & Martunchon Plan	- MIES MINO

Jeff Morris	10/8/09
Inspector's Name (Please Print)	Date of Inspection
	10/8/10
Inspector's Signature	Approximate Date of Next Inspection

COMMENTS: 10/8/09 - AQD performed the annual inspection of the Chrome #2 Black tank and the Decorative Chrome tank.

The facility continously monitors its use and total accumulated time of the plating tanks.

Chrome #2 tank: On April 16, 2009 the Chrome #2 Black tank was at 35.71 dynes/cm surface tension and 500 milliters of Brightguard was put into the tank on May 28, 2009. A record of the past compliance year is attached to the compliance file.

Decorative tank: On October 31, 2008, the Decorative tank was over 45 dynes/cm surface tension and 500 milliters of Brightguard was put into the tank. A record of the past compliance year is attached to the compliance file.[jm]