

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

RE-IN	JAL (INS1, INS2)	COMPLAINT/DISCOVERY (CI)	
	SPECTION (FUI)	ARMS COMPLAINT NO:	
AIRS ID#: 1150084 DATE: <u>06</u>	<u>/15/2007</u>	ARRIVE: ~ 12:45 pm DEPART:	
FACILITY NAME: 60 MINUT	E CLEANERS		
FACILITY LOCATION:	3115 Southgate Circle		
	SARASOTA 34239-		
RESPONSIBLE OFFICIAL: I	OONALD CARLSON	PHONE: (941)955-1311	
CONTACT NAME: JEFF ELL	IS	PHONE: (941)955-1311	
REMITTANCE YEAR: 2007	ENTITLE	MENT PERIOD: 12/7/2006 / 12/7/2011 (end date)	
PART I: INSPECTION COMI		·	
☑ IN COMPLIANCE	MINOR Non-COMPL	LIANCE SIGNIFICANT Non-COMPLIANCE	
PART II: FACILITY CLASSI (check only one b		3.300 FAC	
	ox in A) source	 3.300 FAC 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed on or after 12/9/91) 	

	RT III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC es the responsible official of the dry cleaning facility:	(check ☑ only one box for each question)
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No ⊠N/A
2.	Examine the containers for leakage?	□Yes □ No ⊠ N/A
	Close and secure machine doors except during loading/unloading?	Yes No
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	☐Yes ☐ No ☒ N/A
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A
	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)	
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.
	2. If the facility classification is a <u>New small area source</u> , the machine should be econdenser. Complete section A. below.	quipped with a refrigerated
	 If the facility classification is a <u>Existing large area source</u>, the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below must have been installed prior to September 22, 1993 If the facility classification is a <u>New large area source</u>, the machine should be excondenser. Complete both sections A and B below. 	ow. Carbon adsorber
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)
1.	Equipped all machines with the appropriate vent controls?	□Yes □No
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- ∐Yes ∐No ⊠N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- Yes No N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ∐Yes □No ⊠N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	□Yes □No

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- □Yes □ No □N/A
a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ☑ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	□Yes □ No □ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No ⊠ N/A
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- □Yes □ No ☑ N/A
6. Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for
Does the responsible official:	each question)
1. Maintain receipts for perc purchased?	☐ Yes ☐ No
2. Maintain rolling monthly total of yearly perc consumption?	☐ Yes ☐ No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	
•	Yes No N/A
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A Yes No N/A
and parts installed w/in 5 days of receipt?	Yes No N/A
and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments)	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No □ N/A
and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations?	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No □ N/A Yes □ No
and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	☐ Yes ☐ No ☒ N/A
and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Yes No
2. Does the facility maintain a leak log?	
b) Door gaskets and seating Yes No N/A h) c) Filter gaskets and seating Yes No N/A i) d) Pumps Yes No N/A j	Muck cookers Yes No N/A Stills Yes No N/A Exhaust dampers Yes No N/A Diverter valves Yes No N/A Cartridge filter housings Yes No N/A
4. Which method(s) of detection (is/are) used by the responsible of	official?
a) Visual examination (condensed solvent on exterior surfaces b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetri e) Halogen leak detector	b)
 Capable of detecting perc vapor concentrations in a range o Calibrated against a standard gas prior to and after each use Inspected for leaks and obvious signs of wear on a weekly l Kept in a clean and secure area when not in use?	e (PID/FID only)? 2) Yes No basis? 3) Yes No
5) Verified for accuracy by use of duplicate samples (calorime	
5) Verified for accuracy by use of duplicate samples (calorime	etric only)? 5) Yes No
5) Verified for accuracy by use of duplicate samples (calorime Susan Cameron, ESIII	etric only)? 5) Yes No 06/15/2007
5) Verified for accuracy by use of duplicate samples (calorime Susan Cameron, ESIII	06/15/2007 Date of Inspection
Susan Cameron, ESIII Inspector's Name (Please Print)	O6/15/2007 Date of Inspection ~ 2008 Approximate Date of Next Inspection