ALL ALLO ALL
1 Ser
FLORIDA

PERCHLOROETHYLENE DRY CLEANERS



## **COMPLIANCE INSPECTION CHECKLIST**

	L (INS1, INS2)	COMPLAINT/DISCOV ARMS COMPLAINT N		
AIRS ID#: 0950343 DATE: <u>1/7/20</u>	)08	ARRIVE: <u>08:50</u>	DEPART: <u>09:30</u>	
FACILITY NAME: CONTEMPOR	RARY CLEANERS			
FACILITY LOCATION: 488	32 Kirkman Road			
OR	LANDO 32811			
OWNER/AUTHORIZED REPRES	SENTATIVE: MAH	IENDRA KAPADIA <b>PHO</b> I	<b>NE:</b> (407)295-1414	
CONTACT NAME:		РНО	NE:	
	2007 / 1/4/2012 ive date) (end date)			
I <u> </u>				
PART I: INSPECTION COMPLI	ANCE STATUS (che	eck $\blacksquare$ only one box)		
IN COMPLIANCE	MINOR Non-COMPI	LIANCE SIGNIFIC.	ANT Non-COMPLIANCE	
L				
PART II: FACILITY CLASSIFIC (check ☑ only one box i		3.300 FAC		
<b>A. 1.</b> Existing small area sound dry-to-dry only, x < 140 transfer only, x < 200 gate both types, x < 140 gal/y (constructed before 12/9)	gal/yr l/yr r	2. <u>New small area sound</u> dry-to-dry only, x < transfer only, x < 200 both types, x < 140 g (constructed on or af	140 gal/yr 0 gal/yr çal/yr	
3. Existing large area sound ry-to-dry only, $140 \le x$ transfer only, $200 \le x \le 1$ , both types, $140 \le x \le 1.8$ (constructed before 12/9).	≤ 2,100 gal/yr 1,800 gal/yr 800 gal/yr /91)	4. New large area soundry-to-dry only, 140 transfer only, $200 \le x$ both types, $140 \le x \le ($ constructed on or af	≤ x ≤ 2,100 gal/yr x ≤ 1,800 gal/yr ≤ 1,800 gal/yr	
5. Ineligible for General P drop store/out of busines facility exceeds above lin	s/petroleum			
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 126 gallons.				

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box	
Does the responsible official of the dry cleaning facility:	for each question)	
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A	
2. Examine the containers for leakage?	Yes No N/A	
3. Close and secure machine doors except during loading/unloading?	Yes No	
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A	
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes □ No ⊠ N/A	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)					
	1. If the facility classification is a Existing small area source, no controls are required. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>				
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.				
А.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		☑ only each ques	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	No	□N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	No	N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	⊠N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	No		

B. Does the responsible official of an existing large or new large area source also:       (check ☑ only one box for each question)         1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?       □Yes □No         2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?       □Yes □No □N/A         a) Is the temperature differential equal to, or greater than 20° F?       □Yes □No □N/A         3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?       □Yes □No □N/A         a) Is the perc concentration equal to, or less than 100 ppm?       □Yes □No □N/A         4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 2 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?       □Yes □No □N/A         5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?       □Yes □No □N/A         6. Route airflow to the carbon adsorber (if used) at all times?       □Yes □No □N/A	PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)				
located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?       Yes       No         2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?       Yes       No       N/A         a) Is the temperature differential equal to, or greater than 20° F?       Yes       No       N/A         3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?       Yes       No       N/A         a) Is the perc concentration equal to, or less than 100 ppm?       Yes       No       N/A         4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?       Yes       No       N/A         5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?       Yes       No       N/A	B.					
inlet and outlet weekly?       □Yes       No       N/A         a) Is the temperature differential equal to, or greater than 20° F?       □Yes       No       N/A         3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?       □Yes       No       N/A         a) Is the perc concentration equal to, or less than 100 ppm?       □Yes       □No       N/A         4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?       □Yes       No       N/A         5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?       □Yes       No       N/A	1.	1	Yes No			
<ul> <li>3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?</li></ul>		inlet and outlet weekly?				
<ul> <li>a) Is the perc concentration equal to, or less than 100 ppm?  Yes No N/A</li> <li>4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? Yes No N/A</li> <li>5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils? Yes No N/A</li> </ul>		Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the				
<ul> <li>perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?  Yes No N/A</li> <li>5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?  Yes No N/A</li> </ul>						
condenser coils? Yes No N/A	4.	perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend,	Yes No N/A			
6. Route airflow to the carbon adsorber (if used) at all times? Yes No N/A	5.		- Yes No N/A			
	6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A			

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check $\mathbf{\nabla}$ only one box for
Does the responsible official:	each question)
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No
2. Maintain rolling monthly total of yearly perc consumption?	Yes No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	- Xes No N/A
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A
5. Maintain exhaust duct monitoring data on perc concentrations?	- Yes No N/A
6. Maintain a startup/shutdown/malfunction plan?	- 🛛 Yes 🗌 No
7. Maintain deviation reports?	- 🗌 Yes 🗌 No 🖾 N/A
a) Problem corrected?	🗌 Yes 🗌 No 🖾 N/A
8. Maintain a compliance plan, if applicable?	- 🗌 Yes 🗌 No 🖾 N/A

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No			
2. Does the facility maintain a leak log?	Xes No			
<ul> <li>3. Does the responsible official check the following areas for leaks?</li> <li>a) Hose connections, fittings, couplings, and valves</li> <li>b) Door gaskets and seating</li> <li>c) Filter gaskets and seating</li> <li>d) Pumps</li> <li>e) Solvent tanks and containers</li> <li>f) Water separators</li></ul>	ls XYes No N/A aust dampers Yes No N/A erter valves Yes No N/A			
4. Which method(s) of detection (is/are) used by the responsible official?				
<ul> <li>a) Visual examination (condensed solvent on exterior surfaces)</li></ul>				
Assefa Hailemariam 1/7/2008				
Inspector's Name (Please Print)	Date of Inspection			
	~1/7/2008			
Inspector's Signature	Approximate Date of Next Inspection			

**COMMENTS:**