

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: AN	NNUAL (INS1, INS2)	COMPLAINT/DISCO	VERY (CI)			
RE	E-INSPECTION (FUI)	ARMS COMPLAINT	NO:			
AIRS ID#: 0890431 DATE :	<u>9-4-08</u>	ARRIVE: <u>1245</u>	DEPART: <u>100</u>			
FACILITY NAME: A1A PLANT						
FACILITY LOCATION:	540425 US HWY 1					
	CALLAHAN 32011-78	368				
OWNER/AUTHORIZED REPRESENTATIVE: FRAN ISHAM PHONE: (904)879-2250						
CONTACT NAME:		РНО	NE:			
ENTITLEMENT PERIOD: 9/25/2006 / 9/25/2011 (effective date) (end date)						
PART I: INSPECTION CO		· —				
IN COMPLIANCE	☐ MINOR Non-COMPI	LIANCE SIGNIFIC	CANT Non-COMPLIANCE			
PART II: FACILITY CLA (check only on		3.300 FAC				
A. 1. Existing small ar dry-to-dry only, x transfer only, x < both types, x < 14 (constructed before	x < 140 gal/yr 200 gal/yr 40 gal/yr	dry-to-dry only, x < 20 both types, x < 140 (constructed on or a	140 gal/yr 00 gal/yr gal/yr			
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$) 4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$)						
(constructed befo	one 12/9/91)	(constructed on or a	fter 12/9/91)			
5. Ineligible for Ge	eneral Permit business/petroleum	(constructed on or a	fter 12/9/91)			

PA	RT III: GENERAL CONTROL REQUIREMENTS - Rule 62-213.300 FAC	(check ☑ only one box				
Do	es the responsible official of the dry cleaning facility:	for each question)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A				
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A				
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No				
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A				
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A				
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.					
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993					
	4. If the facility classification is a <u>New large area source</u> , the machine should be eccondenser. Complete both sections A and B below.	quipped with a refrigerated				
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)				
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A				
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A				
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes □No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes No N/A				
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No				

B. Does the responsible official of an existing large or new large area source also: (check ☑ only one box for each question)	
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? Yes No	
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? Yes No N/A	
a) Is the perc concentration equal to, or less than 100 ppm? Yes No N/A	
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	
6. Route airflow to the carbon adsorber (if used) at all times?	
	1
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: (check ✓ only one box for each question)	
1. Maintain receipts for perc purchased? Yes No	
2. Maintain rolling monthly total of yearly perc consumption? Yes No	
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or; Yes No N/A	
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	
4. Maintain calibration data? (for applicable direct reading instruments) Yes No N/A	
5. Maintain exhaust duct monitoring data on perc concentrations? Yes No N/A	
6. Maintain a startup/shutdown/malfunction plan? X Yes No	
6. Maintain a startup/shutdown/malfunction plan? ⊠ Yes □ No 7. Maintain deviation reports? □ Yes □ No ☑ N/A	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?	<u> </u>			
2. Does the facility maintain a leak log?				
b) Door gaskets and seating c) Filter gaskets and seating d) Pumps Yes No N/A i) E Yes No N/A j) I	Muck cookers			
4. Which method(s) of detection (is/are) used by the responsible of	ficial?			
a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric e) Halogen leak detector **If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 2) Calibrated against a standard gas prior to and after each use (3) Inspected for leaks and obvious signs of wear on a weekly ba 4) Kept in a clean and secure area when not in use? 5) Verified for accuracy by use of duplicate samples (calorimetr	b) tubes)			
Marc Lovallo	9-4-08			
Inspector's Name (Please Print)	Date of Inspection			
	September 2009			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS:				