

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE</b> :	ANNUAL (INS1, INS2)	COMPLAINT/DISCO	VERY (CI)			
	RE-INSPECTION (FUI)	ARMS COMPLAINT	NO:			
AIRS ID#: 0112331 DA	TE: <u>10/30/2009</u>	ARRIVE: <u>1030</u>	<b>DEPART:</b> <u>1100</u>			
FACILITY NAME: FRENCH CONNECTION DRY CLEANING & LAUNDRY						
FACILITY LOCATION	N: 1610 S Cypress Road					
	POMPANO BEACH	33060-9137				
OWNER/AUTHORIZE	OWNER/AUTHORIZED REPRESENTATIVE: PAMELA ROGERS PHONE: (954)943-7880					
CONTACT NAME:		РНО	NE:			
ENTITLEMENT PERIO		1				
	(effective date) (end date)					
PART I: INSPECTION	COMPLIANCE STATUS (C	check 🗹 only one box)				
☐ IN COMPLIANO	CE MINOR Non-COM	IPLIANCE SIGNIFIC	CANT Non-COMPLIANCE			
	CLASSIFICATION - Rule 62-	213.300 FAC				
(check <b>Y</b> on	ly one box in A)					
A. 1. Existing smal		2. New small area sou				
	$\frac{1}{2}$ lly, x < 140 gal/yr x < 200 gal/yr	dry-to-dry only, $x < transfer only, x < 20$				
both types, x	< 140 gal/yr	both types, $x < 140$	gal/yr			
(constructed b	before 12/9/91)	(constructed on or a	fter 12/9/91)			
3. Existing larg	e area source	4. New large area sou	arce			
dry-to-dry on	aly, $140 \le x \le 2{,}100 \text{ gal/yr}$	dry-to-dry only, 140	$0 \le x \le 2,100$ gal/yr			
	$200 \le x \le 1,800 \text{ gal/yr}$	transfer only, $200 \le$				
	$40 \le x \le 1,800 \text{ gal/yr}$ before 12/9/91)	both types, $140 \le x$ (constructed on or a				
5 Ingligible for	· General Permit					
	t of business/petroleum					
	eds above limits					
	y of perchloroethylene (perc) p	urchased within the preceding	g 12 months by this dry			
cleaning facility	was 100 gallons.					

_				
PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check 🗹	•	
Do	es the responsible official of the dry cleaning facility:	for eac	ch questi	on)
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A
3.	Close and secure machine doors except during loading/unloading?	X Yes	☐ No	
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes	□ No	□ N/A
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	⊠Yes	□ No	□ N/A
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)			
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	ired. Prod	ceed to 1	Part V.
	2. If the facility classification is a <u>New small area source</u> , the machine should be excondenser. <b>Complete section A. below.</b>	quipped w	vith a ref	rigerated
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B belo</b> <i>must have been installed prior to September 22, 1993</i>			
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped w	vith a ref	rigerated
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :		only ach ques	one box for
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	□N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	□No	□N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊻Yes	□No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes	□No	⊠N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	□Yes □ No □N/A
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☐ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes  No  N/A
6. Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No □ N/A
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check <b>☑</b> only one box for
Does the responsible official:	each question)
1. Maintain receipts for perc purchased?	
	- ⊠ Yes □ No
2. Maintain rolling monthly total of yearly perc consumption?	
<ul><li>2. Maintain rolling monthly total of yearly perc consumption?</li><li>3. Maintain leak detection inspection and repair reports for the following:</li></ul>	
	☐ Yes ☐ No
3. Maintain leak detection inspection and repair reports for the following:	☐ Yes ☐ No
3. Maintain leak detection inspection and repair reports for the following:  a) documentation of leaks repaired w/in 24 hrs? or;  b) documentation of parts ordered to repair leak and leak repaired w/in 2 days	Yes No
3. Maintain leak detection inspection and repair reports for the following:  a) documentation of leaks repaired w/in 24 hrs? or;  b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes       ☐ No         ☐ Yes       ☐ No       ☐ N/A         ☐ Yes       ☐ No       ☐ N/A         ☐ Yes       ☐ No       ☐ N/A
<ul> <li>3. Maintain leak detection inspection and repair reports for the following:</li> <li>a) documentation of leaks repaired w/in 24 hrs? or;</li></ul>	Yes         No           Yes         No         N/A
<ul> <li>3. Maintain leak detection inspection and repair reports for the following: <ul> <li>a) documentation of leaks repaired w/in 24 hrs? or;</li> <li>b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?</li> </ul> </li> <li>4. Maintain calibration data? (for applicable direct reading instruments)</li> <li>5. Maintain exhaust duct monitoring data on perc concentrations?</li> </ul>	☐ Yes         ☐ No           ☐ Yes         ☐ No         ☐ N/A           ☐ Yes         ☐ No         ☐ N/A
<ul> <li>3. Maintain leak detection inspection and repair reports for the following: <ul> <li>a) documentation of leaks repaired w/in 24 hrs? or;</li> <li>b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?</li> </ul> </li> <li>4. Maintain calibration data? (for applicable direct reading instruments)</li></ul>	Yes         No           Yes         No         N/A
<ol> <li>Maintain leak detection inspection and repair reports for the following:         <ul> <li>a) documentation of leaks repaired w/in 24 hrs? or;</li></ul></li></ol>	Yes       No         Yes       No       N/A         No       N/A

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?					
2. Does the facility maintain a leak log?					
3. Does the responsible official check the following areas for leaks?  a) Hose connections, fittings,     couplings, and valves	1s         Yes         No         N/A           aust dampers         Yes         No         N/A           erter valves         Yes         No         N/A				
4. Which method(s) of detection (is/are) used by the responsible official?					
<ul> <li>a) Visual examination (condensed solvent on exterior surfaces)</li> <li>b) Physical detection (airflow felt through gaskets)</li> <li>c) Odor (noticeable perc odor)</li> <li>d) Use of direct-reading instrumentation (FID/PID/calorimetric tube) Halogen leak detector</li> </ul>	b)				
**If using direct-reading instrumentation, is the equipment:  1) Capable of detecting perc vapor concentrations in a range of 0-5  2) Calibrated against a standard gas prior to and after each use (PII 3) Inspected for leaks and obvious signs of wear on a weekly basis'	00 ppm? 1) ⊠Yes □No D/FID only)? 2) ⊠Yes □No				
4) Kept in a clean and secure area when not in use?  5) Verified for accuracy by use of duplicate samples (calorimetric of the secure area).	4)				
4) Kept in a clean and secure area when not in use?	4)				
<ul><li>4) Kept in a clean and secure area when not in use?</li><li>5) Verified for accuracy by use of duplicate samples (calorimetric of the context of the context</li></ul>					
4) Kept in a clean and secure area when not in use? 5) Verified for accuracy by use of duplicate samples (calorimetric of Elizabeth F. Susky	10/30/2009				
4) Kept in a clean and secure area when not in use? 5) Verified for accuracy by use of duplicate samples (calorimetric of Elizabeth F. Susky					
4) Kept in a clean and secure area when not in use?  5) Verified for accuracy by use of duplicate samples (calorimetric of the samples) (calorimetric of the	Approximate Date of Next Inspection  QD staff observed operations at The French Connection dry ng water outside) that were possible haz-mat violations. Further investigate. The facility was utilizing the DEP				
4) Kept in a clean and secure area when not in use?  5) Verified for accuracy by use of duplicate samples (calorimetric of the complex of the calorimetric of the complex of the calorimetric of the calorimet	Approximate Date of Next Inspection  QD staff observed operations at The French Connection dry ng water outside) that were possible haz-mat violations. Further investigate. The facility was utilizing the DEP moted that the expoxy must be repainted around the machine nics.				
4) Kept in a clean and secure area when not in use?	Approximate Date of Next Inspection    OD Staff observed operations at The French Connection dry ng water outside) that were possible haz-mat violations. Further investigate. The facility was utilizing the DEP inoted that the expoxy must be repainted around the machine nics.    Some steam/water outside and no hits were observed.				
4) Kept in a clean and secure area when not in use?  5) Verified for accuracy by use of duplicate samples (calorimetric of the complex of the calorimetric of the complex of the calorimetric of the calorimet	Approximate Date of Next Inspection    OD Staff observed operations at The French Connection dry ng water outside) that were possible haz-mat violations. Further investigate. The facility was utilizing the DEP inoted that the expoxy must be repainted around the machine nics.    Some steam/water outside and no hits were observed.				