

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

<u>INSPECTION</u> <u>TYPE</u> : ANN	NUAL (INS1, INS2)	COMPLAINT/DISCOVERY	Y(CI)		
RE-I	NSPECTION (FUI)	ARMS COMPLAINT NO:			
AIRS ID#: 0250776 DATE: 1	1/12/2010	ARRIVE: <u>10:00 AM</u>	DEPART: <u>10:45 AM</u>		
FACILITY NAME: KIM'S VALET CLEANERS					
FACILITY LOCATION:	5126 Biscayne Blvd				
	MIAMI 33137-3220				
OWNER/AUTHORIZED REPRESENTATIVE: KYONG COE PHONE: (305)758-7405					
CONTACT NAME:		PHONE:			
ENTITLEMENT PERIOD: 11/3/2006 / 11/3/2011 (effective date) (end date)					
DADEL WODE CETON CO.	ADVIANCE CELEVIC / 1				
PART I: <u>INSPECTION COM</u>			UN COMPLIANCE		
☑ IN COMPLIANCE	MINOR Non-COMP	LIANCE SIGNIFICANT	`Non-COMPLIANCE		
PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC (check ☑ only one box in A)					
A. 1. Existing small area dry-to-dry only, x < transfer only, x < 2 both types, x < 140 (constructed before	< 140 gal/yr 00 gal/yr gal/yr	2. New small area source dry-to-dry only, x < 140 g transfer only, x < 200 gal both types, x < 140 gal/yı (constructed on or after 1	/yr r		
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$) 4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$)			,800 gal/yr 00 gal/yr		
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits					
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 97 gallons.					

PA	RT III: GENERAL CONTROL REQUIREMENTS - Rule 62-213.300 FAC	(check ☑ only one box
Do	es the responsible official of the dry cleaning facility:	for each question)
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No ⊠ N/A
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)	
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.
	2. If the facility classification is a <u>New small area source</u> , the machine should be excondenser. Complete section A. below.	quipped with a refrigerated
	 3. If the facility classification is a <u>Existing large area source</u>, the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below must have been installed prior to September 22, 1993 4. If the facility classification is a <u>New large area source</u>, the machine should be expected to the section of the secti	ow. Carbon adsorber
	condenser. Complete both sections A and B below.	
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A
a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A
6. Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A
PART V: <u>RECORDKEEPING</u> <u>REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for
Does the responsible official:	each question)
1. M.: 4.:	
1. Maintain receipts for perc purchased?	- 🛚 Yes 🔲 No
Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption?	
2. Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No
2. Maintain rolling monthly total of yearly perc consumption? 3. Maintain leak detection inspection and repair reports for the following:	⊠ Yes □ No
2. Maintain rolling monthly total of yearly perc consumption? 3. Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days	Yes No
2. Maintain rolling monthly total of yearly perc consumption? 3. Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	 Yes □ No Yes □ No □ N/A □ Yes □ No □ N/A □ Yes □ No □ N/A
 Maintain rolling monthly total of yearly perc consumption?	Yes No Yes No N/A
 Maintain rolling monthly total of yearly perc consumption?	Yes No Yes No N/A Yes No N/A Yes No N/A Yes No N/A Yes No Yes No
 Maintain rolling monthly total of yearly perc consumption?	Yes No Yes No N/A Yes No N/A Yes No N/A Yes No N/A Yes No Yes No Yes No Yes No Yes No
 Maintain rolling monthly total of yearly perc consumption?	Yes No Yes No N/A Yes No N/A

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection? X Yes No			
2. Does the facility maintain a leak log? Yes No			
a) Hose connections, fittings, couplings, and valves			
4. Which method(s) of detection (is/are) used by the responsible official?			
a) Visual examination (condensed solvent on exterior surfaces)			
**If using direct-reading instrumentation, is the equipment:			
FRANK DELGADO 1/12/2010			
Inspector's Name (Please Print) Date of Inspection			
1/2011			
Inspector's Signature Approximate Date of Next Inspection			
COMMENTS: ALL RECORDS WERE AVAILABLE AND UP-TO-DATE. NO LEAKS WERE FOUND.			