

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISC ARMS COMPLAIN	· / <u>-</u>
AIRS ID#: 0571107 DA	TE: <u>11/18/2011</u>	ARRIVE: 1210pm	DEPART: <u>1235pm</u>
FACILITY NAME: SN	OWHITE OF TAMPA BAY PL	ANT	
FACILITY LOCATION	4035 W Hillsborough Av	ve .	
	TAMPA 33614-5629		
OWNER/AUTHORIZE Email: CONTACT NAME: Email: ENTITLEMENT PERIO	D REPRESENTATIVE: GUR OD: 1/28/2007 / 1/28/2012 (effective date) (end date)	Me PH	IONE: (813)884-4854 obile: (813)453-2221 IONE: obile:
PART I: INSPECTION IN COMPLIANCE	COMPLIANCE STATUS (ch		FICANT Non-COMPLIANCE
PART II: FACILITY C	CLASSIFICATION - Rule 62- only one box in A)	213.300 FAC	
transfer only, both types, x (constructed by the stransfer only, both types, 14 (constructed by transfer only, both types, 15 (constructed by the stransfer only, both types, 16 (constructed by the stransfer only, both types, 17 (constructed by the stransfer only, both types, x (constructed by the stransfer only, both types, 14 (constructed by the stransfer only, both types, 15 (constructed by the stransfer only, b	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)	transfer only, 200	x < 140 gal/yr 200 gal/yr 40 gal/yr x = 12/9/91 x = 100 gal/yr x = 1,800 gal/yr x = 1,800 gal/yr
	volume of all perchloroethylene (was 55.00 gallons.	(perc) purchases made in	each of the previous 12 months by this dry

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			(check 🗹 ox for each	only one question)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?		Yes	☐ No	N/A
2. Are all perc. containers leak free ?		Yes	☐ No	N/A
3. Are all machine doors kept closed and secured except during loading/unloading?		Yes	☐ No	,
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes	☐ No	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	□ No	
Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	. 🗆	Yes	☐ No	N/A
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form) 1. If the f acility classification is an existing small area source, no controls are required. I 2. If the facility classification is a new small area source, the machine should be equipped condenser. Complete section A. below. 3. If the facility classification is an existing large area source, the machine should be equipped condenser or a carbon adsorber. Complete both sections A and B below.	with ipped	a refrig	gerated	
 must have been installed prior to September 22, 1993 4. If the facility classification is a <u>new large area source</u>, the machine should be equipped condenser. Complete both sections A and B below. 	with	a refri	gerated	
A. Has the responsible official of all existing large area & new sources:				only one question)
1. Equipped all machines with the appropriate vent controls?	. 🗆	Yes	☐ No	,
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes	☐ No	N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes	☐ No	N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes	☐ No	N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes	☐ No	□ N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes	☐ No	

PART IV: J	PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)					
B. For all ex	haust temperature on the outlet side of the condenser located on dry-to-dry, and dryer machines measured and recorded on a weekly basis?	Yes		No		
and recor	her exhaus t temperature at the condenser inlet and outlet measured ded weekly?	Yes		No		N/A
a) Is the	temperature differential equal to, or greater than 20° F?	Yes		No		N/A
at the end	c concentration in the exhaust stream inlet and outlet measured weekly of the final drying cycle while the machine is venting to the adsorber, es are equipped exclusively with a carbon adsorber?	Yes		No		N/A
a) Is the	perc concentration equal to, or less than 100 ppm?	Yes		No		N/A
4. Is the sam perc conc contraction	upling port on the carbon adsorber exhaust for measuring entrations at least 8 duct diameters downstream of any bend, on, or expansion; is at least 2 duct diameters upstream from any bend, on, or expansion; and downstream from no other inlet?	Yes		No		N/A
5. Are transformation	Fer machines equipped (dryers, reclaimers, and washers) with individual coils?	Yes		No		N/A
6. Is airflow	routed to the carbon adsorber (if used) at all times?	Yes		No	Ш	N/A
6. Is airflow	routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
6. Is airflow	routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
	routed to the carbon adsorber (if used) at all times? ECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	(check ox for ea	<u> </u>	only o	ne
PART V: R		(check ox for each	<u> </u>	only o	ne
PART V: R	ECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	(bo	check lox for each	☑ ach q	only o	ne
PART V: R 1. Are receip 2. Are rollin	ECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC ots maintained for all perc purchased?	(bo	check lox for each	☑ ach q	only o	ne
PART V: R 1. Are receip 2. Are rollin 3. Are leak of	ECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC ots maintained for all perc purchased? g monthly total s of yearly perc consumption maintained?	(bo	check l	☑ ach q	only o	ne
PART V: R 1. Are receip 2. Are rollin 3. Are leak of an b) Of an b) Of an	ECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC ots maintained for all perc purchased? ————————————————————————————————————	Yes Yes	check l	ach q No No	only o	ne n)
1. Are receip 2. Are rollin 3. Are leak of an Of an and particular	ECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC ots maintained for all perc purchased? ————————————————————————————————————	Yes Yes Yes	check l	ach q No No No	only o	ne n) N/A
PART V: R 1. Are receip 2. Are rollin 3. Are leak of an Of an b) Of an and pa 4. Is calibrate	ets maintained for all perc purchased?	Yes Yes Yes	check l	ach quantity No	only o uestio	ne n) N/A N/A
PART V: R 1. Are receip 2. Are rollin 3. Are leak of an of an b) Of an and pa 4. Is calibrat 5. Is exhaus	ets maintained for all perc purchased?	Yes Yes Yes Yes	check l	ach q No No No No No No	only o uestio	ne n) N/A N/A N/A
PART V: R 1. Are receip 2. Are rollin 3. Are leak of an of an of an and pa 4. Is calibrat 5. Is exhaus 6. Is a startu 7. Are devia	ets maintained for all perc purchased?	Yes Yes Yes Yes Yes Yes Yes	check l	ach q No No No No No No No	only of uestion	ne n) N/A N/A N/A
PART V: R 1. Are receip 2. Are rollin 3. Are leak of an of an of an and pa 4. Is calibrat 5. Is exhaus 6. Is a startu 7. Are devia	ets maintained for all perc purchased?	Yes Yes Yes Yes Yes Yes Yes Yes	check l	No	only of uestion	ne n) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	,	(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?		ox for each	•
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	□ N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	□ N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected $\underline{\text{weekly}}$ for $\underline{\text{perceptible leaks}}$ (sight, sm	iell or	touch) whil	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection of the properties of the properti	ection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y c) Filter gaskets and seating Yes No N/A i) Exhaust dampers Y d) Pumps Yes No N/A j) Diverter valves Y	Yes Yes Yes Yes Yes	NoNoNoNoNoNoNo	 N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraph)	raph sh	iall satisfy th	ıe
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A h) Stills Y c) Filter gaskets and seating Yes No N/A i) Exhaust dampers Y d) Pumps Yes No N/A j) Diverter valves Y	Yes Yes Yes Yes Yes	NoNoNoNoNoNoNo	 N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule	e 62-213.300 FAC (continued)	
9. What evidence suggests that leak checks are performed a	as required?	
☐ Leak log documentation ☐ RO Assurances ☐	On-site observation other	
Explain other:		
Jessica V. Lopez	11-18-2011	
Inspector's Name (Please Print)	Date of Inspection	
	5 years	
Inspector's Signature	Approximate Date of Next Inspection	
	Approximate Date of twhich meets the NESHAP requir	