

<u>CHROMIUM</u> <u>ELECTROPLATING/ANODIZING</u>



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS RE-INSPECTIC				
AIRS ID#: 0112358 DATE: <u>2/11/2011</u> FACILITY NAME: CERTIFIED META	ARRIVE: <u>13:30</u> DEPART: <u>14:30</u> L FINISHING INC			
POMPAN	28th Avenue NO BEACH 33069-4817			
OWNER/AUTHORIZED REPRESENTATIVE: DAVID SEXTON PHONE: (954)979-0707 Email: Mobile: CONTACT NAME: LAWRENCE KAUFFMAN PHONE: (954)979-0707 Email: Mobile: ENTITLEMENT PERIOD: 10/19/2006 / 10/19/2011 Mobile: (effective date) (end date)				
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☑ IN COMPLIANCE ☑ MINOR Non-COMPLIANCE ☑ SIGNIFICANT Non-COMPLIANCE				
PART II: CLASSIFICATION – Rule 62-213.300 FAC Facility type(s)/applicable standard as indicated on notification form:				
1. Hard Chromium Plating				
a. <u>Existing Large</u> (0.015 mg/dscm) c. <u>New</u> (0.015 mg/dscm)	 b. Existing Small (0.03 mg/dscm) [] d. <u>Alternative Standard</u> for existing facilities (0.03 mg/dscm) using a rolling average of rectifier capacity (less than 60 million A-hr/year) 			
2. <u>Decorative Chromium Plating/Anodizing</u>				
a. <u>Chromic Acid Bath</u>	 Emissions of ≤ 0.01/mg/dscm (4.4x10⁻⁶ gr/dscf) Surface tension of ≤ 45 dynes/cm (3.1x10⁻³ lb-f/ft) (May only be selected if a wetting agent is used.) 			
b. <u>Trivalent Chromium Bath</u>	1) With wetting agent \Box 2) Without wetting agent $\leq 0.01 \text{ mg/dscm} (4.4 \text{ x} 10^{-6} \text{ gr/dscf})$			
c. <u>Chromium</u> <u>Anodizing</u>	 Emissions of ≤ 0.01 mg/dscm (4.4x10⁻⁶ gr/dscf) Surface tension of 45 dynes/cm (3.1x10⁻³ lb-f/ft) (May only be selected if a wetting agent is used.) 			

PART III: <u>CONTROL TECHNOLOGY</u> – Rule 62-213.300 FAC

(<u>Select control</u> <u>device</u>)	DEVICE IN USE?
1. Composite Mesh Pad	Yes No
2. Fiber Bed Mist Eliminator	□Yes □No
3. Packed Bed Scrubber	□Yes □No
4. Packed Bed Scrubber/Composite Mesh Pad	□Yes □No
5. Foam Blanket Fume Suppressant	Yes No
6. Fume Suppressant w/ Wetting Agent	⊠Yes □No
Has the facility conducted an initial performance test to establish monitoring parameters? (Not required for sources using a wetting agent or 1-inch foam blanket thickness)	

PART IV: <u>RECORDKEEPING/REPORTING</u> <u>REQUIREMENTS</u> – Rule 62-213.300(3)

Has the responsible official maintained the following records?

 Quarterly inspection records for add-on air pollution control devices and monitoring equipment. (applicable only to a facility using a packed bed scrubber, mist eliminator, or composite mesh pad)	Yes	$\square No \boxtimes N/A$
monitoring equipment (equipment identified, date performed, description)	⊠Yes	No
 4. Records of date of occurrence, duration, cause, and corrective action of each malfunction of process, add-on pollution control device, and monitoring equipment. 5. Results of all performance tests	☐Yes wetting	□No ⊠N/A
	105	
<u>Composite Mesh Pad</u> Measure the pressure drop across the CMP daily Packed Bed Scrubber	Yes	No
Measure the pressure drop across the PBS and the inlet velocity daily	Yes	No
Fiber-Bed Mist Eliminator Measure the pressure drop across the FBME and the upstream device daily	Yes	No
Packed Bed Scrubber/Composite Mesh Pad Measure the pressure drop across the CMP daily	Yes	No
Foam Blanket Fume Suppressant Measure the foam blanket thickness at the appropriate interval	□Yes	No
 Fume Suppressant w/ Wetting Agent Measure the surface tension at the appropriate interval Purchase records of wetting agent components Records of the date and time that fume suppressants are added to the bath9. Records of rectifier capacity, if used to determine facility size	⊠Yes ⊠Yes □Yes ⊠Yes ⊠Yes ⊠Yes	□No □N/A □No □N/A □No ⊠N/A □No ⊠N/A

2/11/2011

Inspector's Name (Please Print)

Date of Inspection

2/11/2012

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: In a compliance inspection conducted on 2/11/2011, AQD staff observed operations at Certified Metal Finishers. The facility has a chromic acid bath that which they measure the surface tension. The facility keeps accurate records and submitted them to the department. The surface tension is below 45/dynes and is at 31/dynes per centimeters. Mr. Larry Kaufman accompanied staff on the inspection. Housekeeping is good and the record-keeping is excellent.