

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVI	ERY (CI)	
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO	O:	
AIRS ID#: 0830123 DA'	TE: <u>April 24, 2007</u>	ARRIVE: <u>09:00</u>	DEPART: <u>09:50</u>	
FACILITY NAME: S-C	CURVE CLEANERS			
FACILITY LOCATION	9 SW 10th Street			
	OCALA 34474			
RESPONSIBLE OFFIC	IAL: DAVID HOFFMAN	PHON	E: (352)629-3709	
CONTACT NAME:		PHONE:		
REMITTANCE YEAR:	2005 ENTITLE	EMENT PERIOD: 10/23/20 (effective da		
DADT L. INCRECTION	COMPLIANCE STATUS (1)	.1 [7]		
IN COMPLIANCE	CE MINOR Non-COMP	_	NT Non-COMPLIANCE	
M COMPLIANC	JE MINOR NOII-COMF	LIANCE SIGNIFICA	INT NOII-COMPLIANCE	
		2 200 74 5		
	<u>CLASSIFICATION</u> - Rule 62-21 ly one box in A)	13.300 FAC		
transfer only, both types, x	ly, x < 140 gal/yr x < 200 gal/yr	dry-to-dry only, x < 1 transfer only, x < 200 both types, x < 140 ga (constructed on or after	40 gal/yr gal/yr al/yr	
transfer only, both types, 14	e area source \Box ly, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91)$	4. New large area sourd dry-to-dry only, $140 \le 140 \le$	\leq x \leq 2,100 gal/yr \leq 1,800 gal/yr 1,800 gal/yr	
drop store/out	t of business/petroleum ds above limits			
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 165 gallons.				

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box	
Do	es the responsible official of the dry cleaning facility:	for each question)	
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A	
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A	
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No	
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A	
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	⊠Yes □ No □ N/A	
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)		
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.	
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.		
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993		
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped with a refrigerated	
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)	
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes No N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No	

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?			
3.	a) Is the temperature differential equal to, or greater than 20° F? Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A □Yes □ No □ N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	□Yes □ No □ N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	⊠Yes □ No □ N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- \(\sum Yes \) No \(\sup N/A \)		
6.	Route airflow to the carbon adsorber (if used) at all times?	⊠Yes □ No □ N/A		
D/	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC			
	oes the responsible official:	(check ☑ only one box for each question)		
1.	Maintain receipts for perc purchased?	Yes No		
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No		
3.	Maintain leak detection inspection and repair reports for the following:			
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A		
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A		
4.	Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A		
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No N/A		
6.	Maintain a startup/shutdown/malfunction plan?	⊠ Yes □ No		
7.	Maintain deviation reports?			
	a) Problem corrected?	Yes No N/A		
8.	Maintain a compliance plan, if applicable?	Yes No N/A		

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?						
2. Does the facility maintain a leak log?	Yes No					
d) Pumps						
4. Which method(s) of detection (is/are) used by the responsible official?						
a) Visual examination (condensed solvent on exterior surfaces)						
**If using direct-reading instrumentation, is the equipment: ** \(\subseteq \text{N/A} \) 1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) \(\subseteq \text{Yes} \) \(\subseteq \text{No} \)						
2) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) Yes No						
3) Inspected for leaks and obvious signs of wear on a weekly bas4) Kept in a clean and secure area when not in use?						
5) Verified for accuracy by use of duplicate samples (calorimetric						
, , , , , , , , , , , , , , , , , , , ,	by vermous for accountery by also of displaced samples (constant only).					
Michael Young	April 24, 2007					
Inspector's Name (Please Print)	Date of Inspection					
	April 24, 2008					
Inspector's Signature	Approximate Date of Next Inspection					
COMMENTS:						