

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2)	COMPLAINT/D	SISCOVERY (CI)
RE-INSPECTION (FUI)	ARMS COMPLA	AINT NO:
AIRS ID#: 1030372 DATE: <u>1/10/08</u>	ARRIVE: <u>9:30</u>	DEPART: <u>10:30</u>
FACILITY NAME: PALMS CLEANERS		
FACILITY LOCATION: 1216 S PASADENA AVE		
SOUTH PASADENA 33	707-6202	
OWNER/AUTHORIZED REPRESENTATIVE: DOYL Email:	E MCCOURT	PHONE: (727)344-8500 Mobile:
CONTACT NAME: KATHY HATHEWAY Email:		PHONE: (727)344-8500 Mobile:
ENTITLEMENT PERIOD: 3/11/2010 / 3/11/2015 (effective date) (end date)		Mobile.
PART I: <u>INSPECTION</u> <u>COMPLIANCE</u> <u>STATUS</u> (chec	ck ☑ only one box)
☐ IN COMPLIANCE ☐ MINOR Non-COMPLI	IANCE SIG	NIFICANT Non-COMPLIANCE
PART II: FACILITY CLASSIFICATION - Rule 62-27 (check ☑ only one box in A)	13.300 FAC	
 A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit drop store/out of business/petroleum / facility exceeds above limits 	transfer only, both types, x (constructed of types). 4. New large ar dry-to-dry on transfer only, both types, 14	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91)
B . The sum of the volume of all perchloroethylene (perchange) cleaning facility was 55.00 gallons.	erc) purchases made	e in each of the previous 12 months by this dry

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			(check very contract of the co		ly or	
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No [N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes		No [N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes	□ N	Vо		
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes	□ N	Jo [N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	1	Vo [N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	\boxtimes	Yes	□ N	No [N/A
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)						
1. If the f acility classification is an existing small area source , no controls are required. P	rocee	ed to F	'art V.			
2. If the facility classification is a new small area source , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
3. If the fa cility classification is an existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993						
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refri	gerated			
A. Has the responsible official of all existing large area & new sources:			(check very contract of the co		ly oi estioi	
1. Equipped all machines with the appropriate vent controls?	\boxtimes	Yes	□ N	1 0		
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes	□ N	Vo [N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes	□ N	lo [N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes		No [N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	\boxtimes	Yes		lo [N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	\boxtimes	Yes	□ N	lo		

DADT IV. DDOCESS VENT CONTROLS Dule 62 212 200 EAC (continued)						
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources: 1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,						
reclaimer, and dryer machines measured and recorded on a weekly basis?	🖂	Yes		No		
2. Is the weeken exhaust temperature at the condensar inlet and outlet measured						
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	П	Yes	П	No	\boxtimes	N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
		100	ш	1.0		1,711
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber,						
if machines are equipped exclusively with a carbon adsorber?	\square	Yes	П	No	\bowtie	N/A
			_			
a) Is the perc concentration equal to, or less than 100 ppm?	∐	Yes	Ш	No	\bowtie	N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring						
perc concentrations at least 8 duct diameters downstream of any bend,						
contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	🗆	Yes	П	No	\boxtimes	N/A
						- ,,
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual		Yes		Mo	\square	NT/A
				No	\bowtie	N/A
condenser coils?	Ш	res				
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		No	\boxtimes	N/A
	_			No		N/A
	_			No		N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes				
	_	Yes	[check	V	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	🗆	Yes		V	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?	🗆	Yes	(check ox for e	V	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC		Yes	(check ox for e	☑ each q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes Output Downward Yes	(check ox for e	each q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes Output Downward Yes	(check ox for e	each q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes bo Yes Yes	(check ox for e	each q No No	only o	one on)
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes bo Yes Yes	(check ox for e	each q No No	only o	one on)
6. Is airflow routed to the carbon adsorber (if used) at all times?	🗆	Yes Yes Yes Yes	(check ox for e	each q No No No	only o	one on)
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes	(check ox for e	No No No	only of uestic	one on) N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Is calibration data maintained for applicable direct reading instruments? 5. Is exhaust duct monitoring data on perc concentrations maintained?		Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No No No No No	only of uestic	one on) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	each q No No No No No	only of uestic	nne on) N/A N/A N/A N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No	only of uestice	nne on) N/A N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No	only of uestic	nne on) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	bo	x for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) whi	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection (of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y		□ No□ No□ No□ No□ No	 N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarb	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph sh	all satisfy th	he
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	 No No No No No No No	 N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule	e 62-213.300 FAC (continued)	
9. What evidence suggests that leak checks are performed a	as required?	
□ Leak log documentation □ RO Assurances □	On-site observation other	
Explain other:		
Jeff Morris	1/10/08	
Inspector's Name (Please Print)	Date of Inspection	
	1/10/09	
Inspector's Signature	Approximate Date of Next Inspection	
COMMENTS:		