

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY (CI)					
RE-INSPECTION (FUI)	ARMS COMPLAINT NO:					
AIRS ID#: 0710161 DATE: <u>11/09/2006</u> A	RRIVE: <u>10:25 A.M.</u> DEPART: <u>11:15 A.M.</u>					
FACILITY NAME: NU-IMAGE CLEANERS						
FACILITY LOCATION: 3722 Cleveland Street						
FT. MYERS 33901						
RESPONSIBLE OFFICIAL: STEPHEN MORAUSKI	PHONE: (941)936-0665					
CONTACT NAME:	PHONE:					
REMITTANCE YEAR: 2005 ENTITLEM	ENT PERIOD: 6/6/2002 / 6/6/2007 (effective date) (end date)					
PART I: INSPECTION COMPLIANCE STATUS (check	·					
IN COMPLIANCE MINOR Non-COMPLIA	NCE SIGNIFICANT Non-COMPLIANCE					
PART II: FACILITY CLASSIFICATION - Rule 62-213.3 (check ☑ only one box in A)	00 FAC					
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91)					
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$)	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$)					
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits						
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 98.6 gallons.						

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box						
Does the responsible official of the dry cleaning facility:			for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes	□No	⊠N/A		
2.	Examine the containers for leakage?	Yes	☐ No	⊠ N/A		
3.	Close and secure machine doors except during loading/unloading?	X Yes	☐ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	∐Yes	□ No	⊠ N/A		
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes	□ No	⊠ N/A		
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a Existing small area source , no controls are required.	red. Pr o	ceed to l	Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.					
	 If the facility classification is a Existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 If the facility classification is a New large area source, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below. 					
A.	Has the responsible official of all <u>existing large area & new sources</u> :		only each ques	one box for stion)		
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	□N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	□No	□N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	□No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	□Yes	□No	⊠N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)		
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	□Yes □ No □N/A	
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☒ N/A	
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	- □Yes □ No ⊠ N/A	
a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend,		
contraction, or expansion; and downstream from no other inlet?	- ☐Yes ☐ No ☒ N/A	
5. Equip transfer machines (dryers, reclaimers, and washers) with individual		
condenser coils?		
6. Route airflow to the carbon adsorber (if used) at all times?		
	- □Yes □ No ⊠ N/A	
6. Route airflow to the carbon adsorber (if used) at all times?		
6. Route airflow to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	- □Yes □ No ☑ N/A (check ☑ only one box for each question)	
6. Route airflow to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official:	-	
6. Route airflow to the carbon adsorber (if used) at all times?	-	
6. Route airflow to the carbon adsorber (if used) at all times?	-	
6. Route airflow to the carbon adsorber (if used) at all times?	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: 1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: 1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: 1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: 1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: 1. Maintain receipts for perc purchased? ————————————————————————————————————	-	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check \square only one box for each question)

detection and repair inspection?					
2. Does the facility maintain a leak log?					
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves	Muck cookers Yes No N/A Stills Yes No N/A exhaust dampers Yes No N/A Diverter valves Yes No N/A				
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————					
ROBERT J. STEWART	11/09/2006				
Inspector's Name (Please Print)	Date of Inspection				
	11/2007				
Inspector's Signature	Approximate Date of Next Inspection				

COMMENTS: Corrected rolling PERC total to 98.6 gallons. Also discussed the new EPA Rule and requirement to have a halogen or gas leak detector at the facility and in use by August 2008.