

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVER	RY (CI)		
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO:			
AIRS ID#: 0250805 DA	TE: <u>06/30/2009</u>	ARRIVE: <u>12:40PM</u>	DEPART: <u>01:25PM</u>		
FACILITY NAME: MIAMI LAKES					
FACILITY LOCATION: 6685 NW 169TH ST					
	MIAMI 33015-4289				
OWNER/AUTHORIZE	D REPRESENTATIVE: ANG	EL SUAREZ PHONE	: (786)235-0795		
CONTACT NAME:		PHONE	:		
ENTITLEMENT PERIOD: 12/15/2008 / 12/15/2013 (effective date) (end date)					
	(chective date) (chid date)				
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)					
☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE					
	CLASSIFICATION - Rule 62-21 ly one box in A)	3.300 FAC			
(check 🗹 on	Ty one box in A)				
A. 1. Existing smal	<u>ll area source</u> lly, x < 140 gal/yr	2. New small area source dry-to-dry only, x < 140			
	x < 200 gal/yr	transfer only, $x < 200 \text{ g}$			
both types, x		both types, $x < 140 \text{ gal/}$			
(constructed l	before 12/9/91)	(constructed on or after	12/9/91)		
3. Existing larg	ge area source	4. New large area source			
	aly, $140 \le x \le 2{,}100 \text{ gal/yr}$	dry-to-dry only, $140 \le x$			
	$0.200 \le x \le 1,800 \text{ gal/yr}$ $0.40 \le x \le 1,800 \text{ gal/yr}$	transfer only, $200 \le x \le$ both types, $140 \le x \le 1$,			
	before $12/9/91$)	(constructed on or after			
5. Ineligible for General Permit					
	at of business/petroleum				
facility excee	eds above limits				
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry					
cleaning facility	was 320 gallons.				

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box					
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	□Yes □ No □ N/A			
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below <i>must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area</u> & <u>new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	Yes No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- ⊠Yes □No □N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- ⊠Yes □No □N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ∐Yes ∐No ⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- □Yes □ No ⊠N/A
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☒ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	□Yes □ No ⊠ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend,	
contraction, or expansion; and downstream from no other inlet?	Yes No N/A
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	□Yes □ No ⊠ N/A
6. Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No ⊠ N/A
PART V: RECORDKEEPING REQUIREMENTS - Rule 62-213.300(3) FAC	(abaab 🗸 aula ana ban ƙan
Does the responsible official:	(check v only one box for each question)
1. Maintain receipts for perc purchased?	- Xes No
2. Maintain rolling monthly total of yearly perc consumption?	∑ Yes □ No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days	
and parts installed w/in 5 days of receipt?	☐ Yes ☐ No ☒ N/A
4. Maintain calibration data? (for applicable direct reading instruments)	 ☐ Yes ☐ No ☑ N/A ☐ Yes ☐ No ☑ N/A
	☐ Yes ☐ No ☒ N/A
4. Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A
4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations?	 ☐ Yes ☐ No ☐ No ☐ No ☐ No ☐ No
4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?				
	<u> </u>			
2. Does the facility maintain a leak log?				
3. Does the responsible official check the following areas for lead a) Hose connections, fittings, couplings, and valves) Muck cookers			
4. Which method(s) of detection (is/are) used by the responsible official?				
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————				
MARUFUL MALIK 06/30/2009				
Inspector's Name (Please Print)	Date of Inspection			
	07/15/2009			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: On June 30, 2009 I visited this facility to conduct an annual compliance inspection. On site I met Mrs.Delena Barrett, the manager of the facility. No leaks were detected in the dry cleaning machine. Perc purchase receipts and yearly perc consumption records were available. An FNOV was issued for no Halogen leak detector available on site and it was signed and received by Mr.Angelo Izquierdo, the Regional Manager of the facility.