

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D ARMS COMPLA	ISCOVERY (CI)						
AIRS ID#: 0112365 DATE: <u>8/31/11</u>	ARRIVE: <u>1000</u>	DEPART: <u>1135</u>						
FACILITY NAME: DRYCLEAN USA - KEYSTONE	PLAZA #71324							
FACILITY LOCATION: 10450 Wiles Road								
CORAL SPRINGS 330	076-2002							
OWNER/AUTHORIZED REPRESENTATIVE: Jose Email: CONTACT NAME: same Email: ENTITLEMENT PERIOD: 8/30/2007 / 8/30/2012 (effective date) (end date)		PHONE: (954)757-6 Mobile: PHONE: (954)757-6352 Mobile:						
PART I: INSPECTION COMPLIANCE STATUS (cl) NIFICANT Non-COMPLIANCE						
PART II: FACILITY CLASSIFICATION (check ✓ only one box in A) - Rule 62								
 A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit drop store/out of business/petroleum / facility exceeds above limits 	transfer only, both types, x - (constructed of types). 4. New large are dry-to-dry only transfer only, both types, 14	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91)						
B . The sum of the volume of all perchloroethylene cleaning facility was 80 gallons.	(perc) purchases made	e in each of the previous 12 months by this dry						

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC					only o	
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A
2.	Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No	\boxtimes	N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds						
	maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A
D/	ART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC						
	efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
	1. If the f acility classification is an existing small area source , no controls are required. P	rocee	ed to P	art V	•		
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
	3. If the fa cility classification is an existing large area source , the machine should be equipped refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Compust have been installed prior to September 22, 1993</i>				a		
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refrig	gerate	d		
A.	Has the responsible official of all existing large area & new sources:					only o	
1.	Equipped all machines with the appropriate vent controls?		Yes		No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No		N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away						NT/ 4
Ĭ.	from the condenser upon opening the door?		Yes		No	Ш	N/A
4.	from the condenser upon opening the door? Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?				No No		N/A
	Measured and recorded the temperature of the outlet exhaust stream of a	_					

PAF	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)					
B. F	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, eclaimer, and dryer machines measured and recorded on a weekly basis?	Yes		No		
a	s the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	Yes		No		N/A
ä	a) Is the temperature differential equal to, or greater than 20° F?	Yes		No		N/A
a	s the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, f machines are equipped exclusively with a carbon adsorber?	Yes		No		N/A
a) Is the perc concentration equal to, or less than 100 ppm?	Yes		No		N/A
4. Is p	s the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes		No		N/A
5. A	Are transfer machines equipped (dryers, reclaimers, and washers) with individual ondenser coils?	Yes		No		N/A
\						
6. Is	s airflow routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
6. I	s airflow routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
6. Is	s airflow routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
	s airflow routed to the carbon adsorber (if used) at all times?	((check	V	only o	one
PAR		((check ox for each	V	only o	one
PAR 1. A	RT V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	(bo	check	☑ ach q	only o	one
1. A 2. A	RT V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	(bo	check	☑ ach q No	only o	one
1. A 2. A 3. A	RT V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	(bo	(check ox for each	☑ ach q No	only o	one
1. A 2. A 3. A a	Are receipts maintained for all perc purchased?	Yes Yes	check	☑ ach q No No	only o	one on)
1. A 2. A 3. A b	Are receipts maintained for all perc purchased?	Yes Yes Yes	check	☑ ach q No No No	only o	one on)
1. A 2. A 3. A b 4. Is	Are receipts maintained for all perc purchased? ————————————————————————————————————	Yes Yes Yes	check	ach q No No No	only o questio	one m) N/A N/A
1. A 2. A 3. A a b 4. Is 5. Is	Are receipts maintained for all perc purchased?	Yes Yes Yes Yes Yes	(check ox for each	ach q No No No No	only o questio	nne nn) N/A N/A N/A
1. A 2. A 3. A a b 4. Is 5. Is 6. Is 7. A	Are receipts maintained for all perc purchased? ————————————————————————————————————	Yes Yes Yes Yes Yes	check	Mo No No No No No No	only o questio	nne nn) N/A N/A N/A
1. A 2. A 3. A a b 4. Is 5. Is 6. Is 7. A	Are receipts maintained for all perc purchased?	Yes Yes Yes Yes Yes Yes	check	No	only o questio	nne nn) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? \boxtimes	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	ection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y		NoNoNoNoNoNo	N/AN/AN/AN/AN/AN/A
8.	Are the following dry cleaning system components inspected <u>monthly</u> for <u>vapor leaks</u> using a haloge	enated	hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph sh	hall satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes N/A N/A Exhaust dampers Yes N/A N/A	Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62	2-213.300 FAC (continued)	
 9. What evidence suggests that leak checks are performed as a □ Leak log documentation □ RO Assurances □ Explain other: 	. • <u> </u>	
Art Pennetta	8/31/11	
Inspector's Name (Please Print)	Date of Inspection	
	TBD	
Inspector's Signature	Approximate Date of Next Inspection	
COMMENTS:		