

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) [RE-INSPECTION (FUI) [COMPLAINT/DISCOVER ARMS COMPLAINT NO:	· /
AIRS ID#: 0250806 DATE: 8/3/2010	ARRIVE: <u>12:25PM</u>	DEPART: <u>12:50PM</u>
FACILITY NAME: DORAL CENTER FACILITY LOCATION: 9525 NW 41ST ST		
MIAMI 33178-2373 OWNER/AUTHORIZED REPRESENTATIVE: A Email: CONTACT NAME: STELLA CID Email: ENTITLEMENT PERIOD: 12/15/2008 / 12/15 (effective date) (end date	ANGEL SUAREZ Mobile: PHONE: Mobile: %/2013	: (786)235-0795 : (305)471-0006
PART I: INSPECTION COMPLIANCE STATUS IN COMPLIANCE MINOR Non-CO	·	T Non-COMPLIANCE
(check ✓ only one box in A) A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit d rop store/out of business/petroleum / facility exceeds above limits	transfer only, $200 \le x$ both types, $140 \le x \le$ (constructed on or after	0 gal/yr al/yr yr 12/9/91)
B. The sum of the volume of all perchloroethyle cleaning facility was 231.60 gallons.	ne (perc) purchases made in each o	f the previous 12 months by this dry

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			(-11-	<u>.</u>	1	
		(check ✓ only one box for each question)				
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	_	No		N/A
2. Are all perc. containers leak free?	\boxtimes	Yes		No		N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No		N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	\boxtimes	Yes		No		N/A
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC						
(Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
1. If the f acility classification is an existing small area source , no controls are required. F	roce	ed to F	Part V.	•		
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped condenser. Complete section A. below.	with	a refrig	gerated	l		
3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equirefrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Compust have been installed prior to September 22, 1993</i>				ı		
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refri	gerated	d		
A. Has the responsible official of all existing large area & new sources:			(check ox for e		only o	
1. Equipped all machines with the appropriate vent controls?	\boxtimes	Yes		No		
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes		No		N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes		No		N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes		No		N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	\boxtimes	Yes		No		N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	\boxtimes	Yes		No		

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:						
1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,		V	П	NI.		
reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	Ш	No		
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured						
and recorded weekly?		Yes		No	\boxtimes	N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No	\boxtimes	N/A
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber,						
if machines are equipped exclusively with a carbon adsorber?	П	Yes	П	No	\boxtimes	N/A
					_	
a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No	\boxtimes	N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring						
perc concentrations at least 8 duct diameters downstream of any bend,						
contraction, or expansion; is at least 2 duct diameters upstream from any bend,	_		_			
contraction, or expansion; and downstream from no other inlet?	Ш	Yes	Ш	No	\bowtie	N/A
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual						
c. The transfer machines equipped (dr) ers, rectainers, and washers, with marviagar		Yes	П	No	\boxtimes	N/A
condenser coils?						
			_			
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times?				No	\boxtimes	N/A
				No	\boxtimes	N/A
				No		N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes				
	_	Yes	check	V (only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		V (only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	_	Yes	check x for e	V (only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?		Yes (bo	check x for e	☑ (each q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? ————————————————————————————————————		Yes (bo	check x for e	☑ deach q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?		Yes (bo Yes Yes	check x for e	each q No No	only o	one on)
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?		Yes (bo	check x for e	☑ deach q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes (bo Yes Yes	check x for e	each q No No No	only o	one on)
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes (bo Yes Yes Yes	check x for e	each q No No No	only o	one on) N/A N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes (bo Yes Yes	check x for e	each q No No No	only o	one on)
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes (bo Yes Yes Yes	check x for e	each q No No No	only o	one on) N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes (bo Yes Yes Yes Yes Yes	check x for e	each q No No No No No	only o	one on) N/A N/A N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes (bo Yes Yes Yes Yes Yes Yes Yes Yes	check x for e	No	only o	one on) N/A N/A N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes (bo Yes Yes Yes Yes Yes Yes Yes Yes Yes	check x for e	each q No	only o	nne on) N/A N/A N/A N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes (bo Yes Yes Yes Yes Yes Yes Yes Yes	check x for e	No	only o	one on) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(cl	heck 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	box	for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ? 🖂	Yes [☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes [☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes [☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes [☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes?	Yes [☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or to	uch) whil	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of	perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y		No No No No No	N/AN/AN/AN/AN/AN/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated hy	ydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraphic paragraphic) and the system is in operation?	raph shal	ll satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under $\S 63.322(k)$ or (l))			
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes Yes NO N/A N/A	Yes	No No No No No No	N/AN/AN/AN/AN/AN/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62	2-213.300 FAC (continued)			
9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☒ On-site observation ☐ other Explain other:				
MARUFUL MALIK	8/3/2010			
Inspector's Name (Please Print)	Date of Inspection			
	8/3/2011			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: On August 03, 2010 I visited this facility to conduct the annual compliance inspection. On site I met Ms.Stella Cid, the manager of the facility. No leaks were detected in the dry cleaning machine. Perc purchase receipts and yearly perc consumption records were available. Halogen leak detector was in working condition.