

Florida Department of Environmental Protection

> Northwest District Branch Office 3900 Commonwealth Boulevard, MS 55 Tallahassee, Florida 32399-3000

Rick Scott Governor

Jennifer Carroll Lt. Governor

Herschel T. Vinyard Jr. Secretary

October 7, 2011

Jeff Crane Morrow Cleaners 101 West Crawford Street Quincy, Florida 32351-3117

Dear Mr. Crane:

A Department representative inspected your facility to determine compliance with the Air Quality Operating Permit. The program identification number for this facility is **0390035**. The permit **expires on March 20, 2014**. This letter applies only to activities covered by the Air Resource Management Program.

The Tallahassee Branch Office reported a status of In Compliance for your facility. Your facility compliance status may be subject to further review by the District Program office.

The assistance you provided is appreciated. The inspection checklist and its comments section are enclosed. If you have any questions, your local contact is Tracy White at (850) 245-2960 or tracy.a.white@dep.state.fl.us.

Sincerely,

Marlane Castellano

Marlane Castellanos Branch Manager

MC/tw Enclosures cc: Rick Bradburn, Mary Beth Curle, Carol Melton: FDEP, Pensacola

| TSHIDTOL WOTECTION |
|--------------------|
| Ster Marte |
| FLORIDA |
| |

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI) | COMPLAINT/DISCOVERY (CI) |
|--|---|
| AIRS ID#: 0390035 DATE: <u>9/20/2011</u> | ARRIVE: <u>9:30 A.M.</u> DEPART: |
| FACILITY NAME: MORROW CLEANERS | |
| FACILITY LOCATION: 101 W CRAWFORD ST | |
| QUINCY 32351-3117 | |
| OWNER/AUTHORIZED REPRESENTATIVE: JEFF Email: CONTACT NAME: JEFF CRANE Email: ENTITLEMENT PERIOD: 3/20/2009 / 3/20/2014 (effective date) (end date) | CRANE PHONE: (850)875-4100 Mobile: PHONE: (850)875-4100 Mobile: |
| | |
| PART I: <u>INSPECTION</u> <u>COMPLIANCE</u> <u>STATUS</u> (che | |
| · · · · · · · · · · · · · · · · · · · | |
| PART II:FACILITY CLASSIFICATION (check \square only one box in A)- Rule 62-2A. 1.Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)-3.Existing large area source dry-to-dry only, 140 \le x \le 2,100 gal/yr transfer only, 200 \le x \le 1,800 gal/yr both types, 140 \le x \le 1,800 gal/yr both types, 140 \le x \le 1,800 gal/yr for transfer only, 200 \le x \le 1,800 gal/yr for transfer only of the veloce above limitsB.The sum of the veloce of all percellar p | 213.300 FAC 2. <u>New small area source</u> \Box dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source \Box dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91) |

B. The sum of the volume of all perchloroethylene (perc) purchases made in each of the previous 12 months by this dry cleaning facility was 161 gallons.

| PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC | | | check 🗹 | only one question) |
|--|-------------|-----|---------|-----------------------|
| 1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers? | \boxtimes | Yes | 🗌 No | N/A |
| 2. Are all perc. containers leak free ? | \boxtimes | Yes | 🗌 No | N/A |
| 3. Are all machine doors kept closed and secured except during loading/unloading? | \boxtimes | Yes | 🗌 No | |
| Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? | | Yes | 🗌 No | N/A |
| 5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions. | | Yes | □ No | N/A |
| 6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications? | _ | Yes | □ No | N/A |
| | | | | |
| PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC | | | | |

(Refer to Part II-A.1.-4. Classification: page <u>1</u> of <u>4</u>, this form)

1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.

2. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the fa cility classification is an **existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993*

4. If the facility classification is a <u>new large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

| A. | Has the responsible official of all <u>existing large area & new sources</u> : | | • | check ☑ x for each c | only one [uestion) |
|----|--|-------------|-----|-------------------------|-----------------------|
| 1. | Equipped all machines with the appropriate vent controls? | \boxtimes | Yes | 🗌 No | |
| 2. | Equipped dry-to-dry machines with a closed-loop vapor venting system? | | Yes | 🗌 No | N/A |
| 3. | Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? | | Yes | 🗌 No | N/A |
| 4. | Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? | \boxtimes | Yes | 🗌 No | N/A |
| 5. | Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? | | Yes | 🗌 No | N/A |
| 6. | Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? | \boxtimes | Yes | 🗌 No | |

| PA | PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued) | | | | | |
|-----------------|---|-------------|------------|--------------|---------|--|
| B. 1. | For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis? | \boxtimes | Yes | 🗌 No | | |
| 2. | Is the washer exhaust temperature at the condenser inlet and outlet measured and recorded weekly? | | Yes | No | N/A | |
| 3. | a) Is the temperature differential equal to, or greater than 20° F? Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, | | Yes | L No | ∐ N/A | |
| | if machines are equipped exclusively with a carbon adsorber?a) Is the perc concentration equal to, or less than 100 ppm? | | Yes Yes | □ No □ No | N/A N/A | |
| 4. | Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | | Yes | 🗌 No | N/A | |
| 5. | Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils? | | Yes | 🗌 No | N/A | |
| 6. | Is airflow routed to the carbon adsorber (if used) at all times? | | Yes | 🗌 No | N/A | |

| PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC | | · | check ☑ x for each c | only one question) |
|---|-------------|-----|-------------------------|-----------------------|
| 1. Are receipts maintained for all perc purchased? | \boxtimes | Yes | 🗌 No | |
| 2. Are rolling monthly total s of yearly perc consumption maintained ? | \boxtimes | Yes | 🗌 No | |
| 3. Are leak detection inspection and repair reports maintained for the following: | | | | |
| a) Of any leaks repaired w/in 24 hrs? or; | | Yes | 🗌 No | N/A |
| b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | | Yes | 🗌 No | N/A |
| 4. Is calibration data maintained for applicable direct reading instruments? | | Yes | 🗌 No | N/A |
| 5. Is exhaust duct monitoring data on perc concentrations maintained? | | Yes | 🗌 No | N/A |
| 6. Is a startup/shutdown/malfunction plan maintained for each machine? | \boxtimes | Yes | 🗌 No | |
| 7. Are deviation reports maintained? | | Yes | 🗌 No | N/A |
| a) Problem corrected? | | Yes | 🗌 No | N/A |
| 8. Is a compliance plan maintained, if applicable? | | Yes | 🗌 No | N/A |
| | | | | |

| PA | ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC | (check 🗹 only one |
|----|---|--|
| 1. | What type of leak detection equipment is used to detect leaks? | box for each question) |
| | Halogenated hydrocarbon detector PCE gas analyzer None used | |
| 2. | Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to | |
| | the manufacturer's instructions (manual was available and RO could demonstrate | |
| | <i>procedure)</i> ? 🖂 | Yes 🗌 No |
| 3. | For major sources is the halogenated hydrocarbon detector or PCE gas analyzer | |
| | operated according to EPA Method 21 ? | Yes No N/A |
| 4. | Is the vapor leak inspection conducted by placing the probe inlet at the surface of | |
| | each component interface where leakage could occur and moving it slowly along | |
| | the interface periphery? | Yes 🗌 No |
| 5. | Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or | |
| | infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per | |
| | million by volume (based on documented specifications) ? | Yes 🗌 No 🗌 N/A |
| 6. | Is the halogenated hydrocarbon detector capable of detecting vapor concentrations | |
| | of PCE of 25 parts per million by volume (based on documented specifications) and | |
| | indicating a concentration of 25 parts per million by volume or greater by emitting | |
| | an audible or visual signal that varies as the concentration changes? \boxtimes | Yes No N/A |
| 7. | Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sr | mell or touch) while the |
| | system is in operation (§63.322(k))? | |
| | (Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for ins | spection of perceptible leaks) |
| | b) Door gaskets and seating 🖾 Yes 🔲 No 🗍 N/A h) Stills 🖾 | Yes No N/A Yes No N/A |
| | c) Filter gaskets and seating Xestimate Yes No N/A i) Exhaust dampers d) Pumps Yes No N/A j) Diverter valves Xestimate Yes | Yes \square No \boxtimes N/AYes \square No \square N/A |
| | e) Solvent tanks and containers \square Yes \square No \square N/A k) Cartridge filter housings \square | |
| 0 | f) Water separators Yes No N/A | |
| 8. | Are the following dry cleaning system components inspected <u>monthly</u> for <u>vapor leaks</u> using a halog | |
| | or PCE gas analyzer while the system is in operation? (<i>Any inspection conducted according to this parage</i> | graph shall satisfy the |
| | requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))a) Hose connections, fittings, | |
| | couplings, and valves 🛛 Yes 🗌 No 🗌 N/A g) Muck cookers | Yes D No N/A |
| | | Yes No N/A Yes No X/A |
| | d) Pumps Ves No N/A j) Diverter valves | Yes 🗌 No 🖾 N/A |
| | e) Solvent tanks and containers X Yes No N/A k) Cartridge filter housings f) Water separators Yes No N/A | Yes No N/A |

| PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued) | | | | | | |
|---|-------------------------------------|--|--|--|--|--|
| 9. What evidence suggests that leak checks are performed as required? ☑ Leak log documentation ☑ RO Assurances ☑ On-site observation □ other Explain other : | | | | | | |
| | | | | | | |
| Tracy White | 9/20/11 | | | | | |
| Inspector's Name (Please Print) | Date of Inspection | | | | | |
| <u>Inspector's Signature</u> | | | | | | |
| Inspector's Signature | Approximate Date of Next Inspection | | | | | |

COMMENTS: I met with Doris Rittman. Ms. Rittman gave me access to the recordkeeping calendars and Perc receipts. Records for the 2010-11 calendar years were maintained. I observed the machine. No issues were noted at the facility.