

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE</b> :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVE	CRY (CI)			
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO	):			
AIDS ID#• 1270127 DA'	TF: March 28, 2007	ADDIVE: 11.25	DEDART: 12:15			
AIRS ID#: 1270137 DATE: March 28, 2007 ARRIVE: 11:25 DEPART: 12:15						
FACILITY NAME: KENNEDY'S CLEANERS						
FACILITY LOCATION: 831 N Seagrave Street						
DAYTONA BEACH 32114						
RESPONSIBLE OFFICIAL: CHARLES KENNEDY		PHONI	<b>PHONE:</b> (386)258-7343			
CONTACT NAME:		PHONE:				
REMITTANCE YEAR:	2006 <b>ENTITL</b>	LEMENT PERIOD: 12/21/200 (effective da				
DADT I. INCDECTION	COMPLIANCE STATUS (ch	haalt 🗹 anly and hay)				
IN COMPLIANCE			NT No. COMPLIANCE			
IN COMPLIANC	CE MINOR Non-COM	PLIANCE SIGNIFICAL	NT Non-COMPLIANCE			
	CLASSIFICATION - Rule 62-2 ly one box in A)	213.300 FAC				
transfer only, both types, x	ly, x < 140 gal/yr x < 200 gal/yr	2. New small area source dry-to-dry only, x < 14 transfer only, x < 200 both types, x < 140 ga (constructed on or after	40 gal/yr gal/yr l/yr			
transfer only, both types, 14	e area source $\square$ ly, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91)$	4. New large area source dry-to-dry only, $140 \le$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1$ (constructed on or after	$x \le 2.100 \text{ gal/yr}$ $\le 1,800 \text{ gal/yr}$ 1,800  gal/yr			
drop store/out	t of business/petroleum ds above limits					
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 150 gallons.						

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box				
Do	es the responsible official of the dry cleaning facility:	for each question)		
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A		
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A		
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No		
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A		
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	⊠Yes □ No □ N/A		
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)			
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	ired. Proceed to Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>			
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993			
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. <b>Complete both sections A and B below.</b>	quipped with a refrigerated		
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :	(check ☑ only one box for each question)		
1.	Equipped all machines with the appropriate vent controls?	Yes □No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- ⊠Yes □No □N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ⊠Yes □No □N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No		

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	
3.	a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☐ N/A ☐Yes ☐ No ☐ N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	□Yes □ No ⊠ N/A
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	⊠Yes □ No □ N/A
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- □Yes □ No □ N/A
6.	Route airflow to the carbon adsorber (if used) at all times?	⊠Yes □ No □ N/A
PA	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	
	bes the responsible official:	(check ☑ only one box for each question)
1.	Maintain receipts for perc purchased?	⊠ Yes □ No
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No
3.	Maintain leak detection inspection and repair reports for the following:	
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No No
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No    N/A
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A
6.	Maintain a startup/shutdown/malfunction plan?	⊠ Yes □ No
7.	Maintain deviation reports?	
	a) Problem corrected?	Yes No N/A
8.	Maintain a compliance plan, if applicable?	☐ Yes ☐ No     N/A

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?					
2. Does the facility maintain a leak log?					
d) Pumps \overline{\overline{\text{N}}} Yes \overline{\overline{\text{N}}} No \overline{\overline{\text{N}}} A j) Diverted					
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces)					
1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) Yes No 2) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) Yes No					
3) Inspected for leaks and obvious signs of wear on a weekly basis?	3) Yes No				
4) Kept in a clean and secure area when not in use?					
5) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) Yes No					
Michael Young	March 28, 2007				
Inspector's Name (Please Print)	Date of Inspection				
Ma	arch 28, 2008				
Inspector's Signature	Approximate Date of Next Inspection				
COMMENTS:					