CONNECTION PROTECTION	
Same Mana	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)
AIRS ID#: 0990503 DATE: <u>1/25/2011</u>	ARRIVE: <u>12:55 PM</u> DEPART: <u>1:30 PM</u>
FACILITY NAME: RIO CLEANERS	
FACILITY LOCATION: 8128 Glades Road	
BOCA RATON 33434	
OWNER/AUTHORIZED REPRESENTATIVE: SCOT Email: CONTACT NAME: Same Email: ENTITLEMENT PERIOD: 4/15/2005 / 4/15/2010 (effective date) (end date)	TT LUONG PHONE: (561)477-7567 Mobile: PHONE: (Mobile: Facility may be operating without Entitlement!
PART I: INSPECTION COMPLIANCE STATUS (che	
PART II: FACILITY CLASSIFICATION (check I only one box in A) - Rule 62-2	213.300 FAC
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)3. Existing large area source \Box dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)5. Ineligible for General Permit \Box d rop store/out of business/petroleum / facility exceeds above limits	2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91) 4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)
B . The sum of the volume of all perchloroethylene ()	perc) purchases made in each of the previous 12 months by this dry

cleaning facility was 110.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			check ☑ x for each o	only one question)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	🗌 No	N/A
2. Are all perc. containers leak free ?	\square	Yes	🗌 No	N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes	🗌 No	
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 	\boxtimes	Yes	🗌 No	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	□ No	N/A
 6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications? 		Yes	□ No	N/A

	ART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)							
	1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.							
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.							
	3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>							
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refrig	gerated	_			
A.	Has the responsible official of all existing large area & new sources:			check x for ea		only c uestio		
1.	Equipped all machines with the appropriate vent controls?	\square	Yes		No		ļ	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No		N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes		No		N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes		No		N/A	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	\boxtimes	Yes		No		N/A	

Conducted all temperature monitoring after an appropriate cool-down period and				
after verifying that the coolant had been completely charged?	\boxtimes	Yes	No No	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	 Yes Yes	□ No	N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC			check 🗹	only one question)
1.	Are receipts maintained for all perc purchased?	\boxtimes	Yes	No No	
2.	Are rolling monthly total s of yearly perc consumption maintained ?	\boxtimes	Yes	🗌 No	
3.	Are leak detection inspection and repair reports maintained for the following:				
	a) Of any leaks repaired w/in 24 hrs? or;	\boxtimes	Yes	🗌 No	N/A
	b) Of any parts ordered to repair leak and leak repaired w/in 2 days				
	and parts installed w/in 5 days of receipt?	\bowtie	Yes	∐ No	□ N/A
4.	Is calibration data maintained for applicable direct reading instruments?		Yes	🗌 No	N/A
5.	Is exhaust duct monitoring data on perc concentrations maintained?		Yes	🗌 No	N/A
6.	Is a startup/shutdown/malfunction plan maintained for each machine?	\boxtimes	Yes	🗌 No	
7.	Are deviation reports maintained?	\boxtimes	Yes	🗌 No	N/A
	a) Problem corrected?	\boxtimes	Yes	🗌 No	N/A
8.	Is a compliance plan maintained, if applicable?		Yes	🗌 No	N/A

PA	ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC	(c)	heck 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?			question)
	Halogenated hydrocarbon detector PCE gas analyzer None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ? 🖂	Yes	No No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	🗌 No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? 🖾	Yes	🗌 No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	No No	N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? \square	Yes	🗌 No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sr	mell or to	uch) while	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of	`perceptib	le leaks)
	b) Door gaskets and seating 🛛 Yes 🗌 No 🗍 N/A h) Stills 🖾		No No No No No	 N/A N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated h	ydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	graph shal	ll satisfy th	ie
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or (l)			
	b) Door gaskets and seating Xes No N/A N) Stills c) Filter gaskets and seating Xes No N/A i) Exhaust dampers	Yes [Yes [Yes [Yes [Yes [No No No No No	 N/A N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62	-213.300 FAC (continued)	
 9. What evidence suggests that leak checks are performed as re Leak log documentation RO Assurances Explain other : 	·	
Jeffrey Dizek	1/25/2011	
Inspector's Name (Please Print)	Date of Inspection	
	1/2012	
Inspector's Signature	Approximate Date of Next Inspection	
COMMENTS: Entitlement submitted.		