INCOMPANY PROTECTION	
and the	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)
AIRS ID#: 0990505 DATE: <u>8/12/2010</u>	ARRIVE: <u>11:30 AM</u> DEPART: <u>12:30 PM</u>
FACILITY NAME: ROYAL CLEANERS	
FACILITY LOCATION: 2621 N Federal Hwy	
BOCA RATON 33431	
OWNER/AUTHORIZED REPRESENTATIVE: DAVI Email: CONTACT NAME: Same Email: ENTITLEMENT PERIOD: 8/5/2006 / 8/5/2011 (effective date) (end date)	ID IZA PHONE: (561)391-8722 Mobile: PHONE: (Mobile:
PART I: INSPECTION COMPLIANCE STATUS (che	
(check \blacksquare only one box in A)A. 1. Existing small area sourcedry-to-dry only, x < 140 gal/yrtransfer only, x < 200 gal/yrboth types, x < 140 gal/yr(constructed before 12/9/91)3. Existing large area sourcedry-to-dry only, 140 \le x \le 2,100 gal/yrtransfer only, 200 \le x \le 1,800 gal/yrboth types, 140 \le x \le 1,800 gal/yrboth types, 140 \le x \le 1,800 gal/yr(constructed before 12/9/91)5. Ineligible for General Permitd rop store/out of business/petroleum /facility exceeds above limits	213.300 FAC 2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91) 4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91) perc) purchases made in each of the previous 12 months by this dry

cleaning facility was 100.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-2	213.300 FAC	(chec box for	k ☑ o r each q	only or uestior	
1. Is all perc, and wastes containing perc, in tightly sealed & impervio	us containers? 🖂	Yes] No		N/A
2. Are all perc. containers leak free ?	🖾	Yes] No		N/A
3. Are all machine doors kept closed and secured except during loadin	g/unloading? 🛛	Yes] No		
 Are cartridge filters d rained in their housing or in sealed containers 24 hours prior to disposal? 		Yes 🗌] No		N/A
5. Has each dry cleaning system installed after December 21, 2005 at a routed the air-PCE gas-vapor stream contained within each dry clea through a refrigerated condenser and passed the air-PCE gas-vapor inside the dry cleaning machine drum through a non-vented carbon equivalent control device immediately before the door of the dry cl machine is opened? The carbon adsorber must be desorbed in accommanufacturer's instructions.	ning machine stream from adsorber or eaning dance with	Yes 🗌] No		N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber b maintain according to the manufacturer's specifications?		Yes 🗌] No		N/A

PART IV:	PROCESS V	ENT CONTRO	<u>)LS</u> – Rule 62	-213.300 FAC
(Refer to P	Part II-A 1 -4	Classification	\cdot nage 1 of 4	this form)

(Reter to Part II-A.1.-4. Classification: page $\underline{1}$ of $\underline{4}$, this form)

1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.

2. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the fa cility classification is an **existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993*

4. If the facility classification is a <u>new large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

A.	Has the responsible official of all existing large area & new sources:			check ☑ k for each c	only one question)
1.	Equipped all machines with the appropriate vent controls?	\boxtimes	Yes	🗌 No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\square	Yes	🗌 No	N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes	🗌 No	N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes	🗌 No	N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	\boxtimes	Yes	🗌 No	N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	\boxtimes	Yes	🗌 No	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	Yes Yes	□ No □ No	N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		```	check ☑ x for each c	only one [uestion)
1.	Are receipts maintained for all perc purchased?	\boxtimes	Yes	🗌 No	
2.	Are rolling monthly total s of yearly perc consumption maintained ?	\boxtimes	Yes	🗌 No	
3.	Are leak detection inspection and repair reports maintained for the following:				
	a) Of any leaks repaired w/in 24 hrs? or;	\boxtimes	Yes	🗌 No	N/A
	b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	\boxtimes	Yes	🗌 No	□ N/A
4.	Is calibration data maintained for applicable direct reading instruments?		Yes	🗌 No	N/A
5.	Is exhaust duct monitoring data on perc concentrations maintained?		Yes	🗌 No	N/A
6.	Is a startup/shutdown/malfunction plan maintained for each machine?	\boxtimes	Yes	🗌 No	
7.	Are deviation reports maintained?	\boxtimes	Yes	🗌 No	N/A
	a) Problem corrected?	\boxtimes	Yes	🗌 No	N/A
8.	Is a compliance plan maintained , if applicable?		Yes	🗌 No	N/A

P	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	box for each o	question)
	Halogenated hydrocarbon detector PCE gas analyzer None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ? 🖂	Yes 🗌 No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes 🗌 No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery?	Yes 🗌 No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes 🗌 No	N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes? \square	Yes 🗌 No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or touch) while	e the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perceptible	e leaks)
	b) Door gaskets and seating Xes Ves No N/A h) Stills Xes Ves	Yes No Yes No Yes No	 N/A N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	genated hydrocarbo	n detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph shall satisfy the	2
	requirements to conduct an inspection for perceptible leaks under $(3.322(k) \text{ or } (l))$		
	b) Door gaskets and seating Xes No N/A N) Stills Xes c) Filter gaskets and seating Xes No N/A i) Exhaust dampers Xes	Yes No Yes No Yes No	N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)					
 9. What evidence suggests that leak checks are performed as required? 					
Jeffrey Dizek	8/12/2010				
Inspector's Name (Please Print)	Date of Inspection				
	8/2011				
Inspector's Signature Approximate Date of Next Inspection					
COMMENTS:					