

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY	(CI)		
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO:			
AIRS ID#: 0210079 DA	TE: <u>10/29/2008</u>	ARRIVE: <u>10:00 A.M.</u>	DEPART: <u>10:50 A.M.</u>		
FACILITY NAME: CLEANER IMAGE					
FACILITY LOCATION	3883 Davis Blvd				
	NAPLES 34104-5007				
OWNER/AUTHORIZE	D REPRESENTATIVE: GEO	RGE GREENFIELD PHONE :	(239)643-8088		
CONTACT NAME:		PHONE:			
ENTITLEMENT PERIOD: 6/19/2000 / 6/19/2005 Facility may be operating without Entitlement! (end date)					
_	COMPLIANCE STATUS (ch				
☐ IN COMPLIAN	CE MINOR Non-COMP	LIANCE SIGNIFICANT	Non-COMPLIANCE		
	CLASSIFICATION - Rule 62-21 ly one box in A)	3.300 FAC			
transfer only, both types, x (constructed l 3. Existing larg dry-to-dry on	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr before 12/9/91)	 2. New small area source dry-to-dry only, x < 140 g transfer only, x < 200 gal/both types, x < 140 gal/yr (constructed on or after 12 4. New large area source dry-to-dry only, 140 ≤ x ≤ transfer only, 200 ≤ x ≤ 1, 	yr 2/9/91) <u> </u>		
•	$40 \le x \le 1,800 \text{ gal/yr}$	both types, $140 \le x \le 1,80$ (constructed on or after 12	00 gal/yr		
5. Ineligible for drop store/ou	General Permit tof business/petroleum ds above limits	(constructed on or area 12	19191)		

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box			
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No ⊠N/A			
2.	Examine the containers for leakage?	□Yes □ No ⊠ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated			
Α.	Has the responsible official of all <u>existing large</u> <u>area</u> & <u>new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	□Yes □No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	□Yes □ No ⊠N/A
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☒ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend,	
contraction, or expansion; and downstream from no other inlet?	Yes No N/A
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	□Yes □ No ⊠ N/A
6. Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A
PART V: RECORDKEEPING REQUIREMENTS - Rule 62-213.300(3) FAC	(ab a ab 📈 a color a con b a co fa co
	(check ☑ only one box for
Does the responsible official:	each question)
Does the responsible official: 1. Maintain receipts for perc purchased?	
-	- 🛚 Yes 🗌 No
1. Maintain receipts for perc purchased?	- 🛚 Yes 🗌 No
Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption?	- ⊠ Yes □ No ⊠ Yes □ No
Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption? Maintain leak detection inspection and repair reports for the following:	- ⊠ Yes □ No ⊠ Yes □ No
1. Maintain receipts for perc purchased? 2. Maintain rolling monthly total of yearly perc consumption? 3. Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days	- ⊠ Yes □ No ⊠ Yes □ No - □ Yes □ No ⊠ N/A
1. Maintain receipts for perc purchased? 2. Maintain rolling monthly total of yearly perc consumption? 3. Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	-
 Maintain receipts for perc purchased?	-
1. Maintain receipts for perc purchased?	-
1. Maintain receipts for perc purchased?	-

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?				
2. Does the facility maintain a leak log?				
	Muck cookers			
4. Which method(s) of detection (is/are) used by the responsible of	fficial?			
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————				
ROBERT J. STEWART	10/29/2008			
Inspector's Name (Please Print)	Date of Inspection			
•	11/12/2008			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: Facility operator stated that he has submitted (mailed) an renewal General Permit application on Monday, October 27, 200, but a check with DEP main office in Tallahassee shows they have not received it as of this date (See DEP Warning letter dated June 16, 2008) of Corrected the 12 month rolling PERC total from 60 gallons to 192.9 gallons. Temperature readings annotated on DEP compliance calendar was 36-38 degrees F for both dry cleaning machines. When the owner and facility operator were asked where the temperature of the condensor was read, they both indicated a thermometer gauges on the back of both of the machines refrigerated piping. These gauges only indicates a temperature down to to 40 degrees F at the bottom of the scale, so to read the 36-38 F as annotated in the calendars would be just an estimate. The inspection revealed another set (2) LCD indicators mounted at the front and between the two dry cleaning machines. These are probably the temperature indicators for the refrigerated condensors for both machines, although the owner says they work intermittantly. The machine on the right hand side is not in use at this time, but it is it still operable, just not being used at this time. Both facility operator and owner seem unsure as to where and who reads the temperature for the refrigerated condensor. A reinspection will be rescheduled at a later date as soon as both machines refrigerated condensor temperature indicator is either repaired or replaced in order to give a correct reading when both machines are in operation. Owner will call to reschedule a time and date for a reinspection once this is done.