CHARDER MOTECTION	
Some Martin	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



## **COMPLIANCE INSPECTION CHECKLIST**

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D	ISCOVERY (CI)
AIRS ID#: 0230038 DATE: <u>1-19-11</u>	ARRIVE: <u>1200</u>	DEPART: <u>1215</u>
FACILITY NAME: ADVANCE DRY CLEANERS		
FACILITY LOCATION: 2367 W US 90 WEST #1	20	
LAKE CITY 32055		
OWNER/AUTHORIZED REPRESENTATIVE: PRAF Email: CONTACT NAME: Email: ENTITLEMENT PERIOD: 4/7/2008 / 4/7/2013 (effective date) (end date)	∢ASH PATEL	PHONE: (386)755-5571 Mobile: PHONE: Mobile:
PART I: INSPECTION COMPLIANCE STATUS (che         IN COMPLIANCE         IN COMPLIANCE		) NIFICANT Non-COMPLIANCE
PART II:FACILITY CLASSIFICATION (check $\square$ only one box in A)- Rule 62-2A. 1.Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)-3.Existing large area source dry-to-dry only, 140 $\le$ x $\le$ 2,100 gal/yr transfer only, 200 $\le$ x $\le$ 1,800 gal/yr tooth types, 140 $\le$ x $\le$ 1,800 gal/yr (constructed before 12/9/91)5.Ineligible for General Permit d rop store/out of business/petroleum / facility exceeds above limitsB.The sum of the volume of all perchloroethylene (page 100 gal/general sector)	<ol> <li><u>New small ar</u> dry-to-dry onl transfer only, both types, x &lt; (constructed of <b>4.</b> New large are dry-to-dry onl transfer only, both types, 14 (constructed of</li> </ol>	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91) ea source y, 140 $\leq x \leq 2,100$ gal/yr 200 $\leq x \leq 1,800$ gal/yr $0 \leq x \leq 1,800$ gal/yr on or after 12/9/91)

cleaning facility was 65tt.00 gallons.

PA	ART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			(check ox for e		only o questio	
	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	$\boxtimes$	Yes		No		N/A
2.	Are all perc. containers leak free ?	$\boxtimes$	Yes		No		N/A
3.	Are all machine doors kept closed and secured except during loading/unloading?	$\boxtimes$	Yes		No		ľ
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	$\boxtimes$	Yes		No		N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with						
	manufacturer's instructions		Yes		No	$\bowtie$	N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	$\boxtimes$	Yes		No		N/A
	ART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						ļ
	1. If the f acility classification is an <b>existing small area source</b> , no controls are required. <b>P</b>	roce	ed to P	art V	•		
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped we condenser. <b>Complete section A. below.</b>	with :	a refrig	erated	i		
	3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equip refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Co must have been installed prior to September 22, 1993		with e n adsor		L		
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refrig	gerated	1		
А.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		```	check ox for e		only o questio	
1.	Equipped all machines with the appropriate vent controls?	$\boxtimes$	Yes		No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	$\boxtimes$	Yes		No		N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	$\boxtimes$	Yes		No		N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes		No		N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded $45^{\circ}$ F?		Yes		No	$\boxtimes$	N/A
-	Conducted all temperature monitoring after an appropriate cool down period and						ļ

6.	Conducted all temperature monitoring after an appropriate cool-down period and			
	after verifying that the coolant had been completely charged?	$\square$	Yes	No

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
<b>B.</b> 1.	<b>For all existing large or new large area sources:</b> Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	Yes Yes	D No	□ N/A □ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(check box for		only one question)
1. Are receipts maintained for all perc purchased?	] Y	es 🗌	No	
2. Are rolling monthly total s of yearly perc consumption maintained ?	Y	es 🗌	No	
3. Are leak detection inspection and repair reports maintained for the following:				
a) Of any leaks repaired w/in 24 hrs? or;	] Y	es 🗌	No	N/A
<ul> <li>b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?</li> </ul>	] Y	es 🗌	No	N/A
4. Is calibration data maintained for applicable direct reading instruments?	] Y	es 🗌	No	N/A
5. Is exhaust duct monitoring data on perc concentrations maintained?	] Y	es 🗌	No	N/A
6. Is a startup/shutdown/malfunction plan maintained for each machine?	Y	es 🗌	No	
7. Are deviation reports maintained?	] Y	es 🗌	No	N/A
a) Problem corrected?	] Y	es 🗌	No	N/A
8. Is a compliance plan maintained, if applicable?	] Y	es 🗌	No	N/A

PA	ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC	(ch	neck 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?			question)
	Halogenated hydrocarbon detector PCE gas analyzer None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	<i>procedure)</i> ? 🖂	Yes	No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	] No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	] No	N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? $\square$	Yes [	No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or tou	uch) whil	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of	perceptib	le leaks)
	b) Door gaskets and seating 🖾 Yes 🔲 No 🗍 N/A h) Stills 🖾		] No ] No ] No ] No ] No	<ul> <li>□ N/A</li> <li>□ N/A</li> <li>□ N/A</li> <li>□ N/A</li> <li>□ N/A</li> </ul>
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated hy	drocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	graph shall	l satisfy th	ıe
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or $(l)$			
	b) Door gaskets and seating       Xes       No       N/A       h) Stills         c) Filter gaskets and seating       Xes       No       N/A       i) Exhaust dampers	Yes Yes Yes Yes Yes	] No ] No ] No ] No ] No	<ul> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> </ul>

PART VI: LEAK DETECTION AND REPAIRS – Rule	62-213.300 FAC (continued)	
<ul> <li>9. What evidence suggests that leak checks are performed as</li> <li>☑ Leak log documentation ☑ RO Assurances ☑ Explain other :</li> </ul>	·	
Marc Lovallo	1-19-11	
Inspector's Name (Please Print)	Date of Inspection	
	Jan 2012	
Inspector's Signature	Approximate Date of Next Inspection	
<b>COMMENTS:</b> needs secondary containment for waste drug	ums.	