

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D	DISCOVERY (CI) AINT NO:
AIRS ID#: 0190054 DA	ГЕ: 3-31-11	ARRIVE: 130	DEPART: <u>145</u>
FACILITY NAME: SIL	VER HANGAR CLEANERS		
FACILITY LOCATION	: 305-E Blanding Blvd		
	ORANGE PARK 320°	73-4364	
OWNER/AUTHORIZED Email: CONTACT NAME: PE Email: ENTITLEMENT PERIC			PHONE: (904)272-0054 Mobile: PHONE: (904)273-0054 Mobile: perating without Entitlement!
PART I: INSPECTION IN COMPLIANCE	COMPLIANCE STATUS (c		SNIFICANT Non-COMPLIANCE
PART II: FACILITY C	LASSIFICATION - Rule 62 only one box in A)	2-213.300 FAC	
transfer only, both types, x - (constructed by a constructed by a construc	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)	transfer only, both types, x (constructed of the constructed of the co	aly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91)
B . The sum of the vecleaning facility vec	•	(perc) purchases mad	e in each of the previous 12 months by this dry

	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC					only o	
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A
2.	Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		No		N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.	\boxtimes	Yes		No		N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A
	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC Refer to Part II-A.14. Classification: page 1 of 4, this form)						
	1. If the f acility classification is an existing small area source , no controls are required. P	rocee	ed to P	art V	•		
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped condenser. Complete section A. below.	with a	a refrig	erated	l		
	2. If the fe cility electrication is an existing large even gavens the machine should be equi-						
	3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equirefrigerated condenser or a carbon adsorber. Complete both sections A and B below. Comust have been installed prior to September 22, 1993				a		
	refrigerated condenser or a carbon adsorber. Complete both sections A and B below. C	arboi	ı adsoı	rber			
A.	refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Comust have been installed prior to September 22, 1993</i> 4. If the facility classification is a new large area source , the machine should be equipped	arboi	a dsor	rber gerated	d — • 🗹	only o	
	refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Comust have been installed prior to September 22, 1993 4. If the facility classification is a new large area source, the machine should be equipped condenser. Complete both sections A and B below.	arboi	a refrig	rber gerated	d — • 🗹	-	
1.	refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Comust have been installed prior to September 22, 1993 4. If the facility classification is a new large area source, the machine should be equipped condenser. Complete both sections A and B below. Has the responsible official of all existing large area & new sources:	with	a refrig	rber gerated	d — Ø each	-	
1. 2.	refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Comust have been installed prior to September 22, 1993 4. If the facility classification is a new large area source, the machine should be equipped condenser. Complete both sections A and B below. Has the responsible official of all existing large area & new sources: Equipped all machines with the appropriate vent controls?	with	a refrig	rber gerated	d — Each	-	on)
 1. 2. 3. 	refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Must have been installed prior to September 22, 1993 4. If the facility classification is a new large area source, the machine should be equipped condenser. Complete both sections A and B below. Has the responsible official of all existing large area & new sources: Equipped all machines with the appropriate vent controls? Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away	with	a refrig (bo Yes Yes	rber gerated	d — each No No	-	on) N/A
 1. 2. 3. 4. 	refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Must have been installed prior to September 22, 1993 4. If the facility classification is a new large area source, the machine should be equipped condenser. Complete both sections A and B below. Has the responsible official of all existing large area & new sources: Equipped all machines with the appropriate vent controls? Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	with	a refrig (bo Yes Yes	rber gerated	d V each No No	-	n) N/A N/A

PART	Γ IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
	or all existing large or new large area sources:						
	the exhaust temperature on the outlet side of the condenser located on dry-to-dry,		Vac		No		
rec	claimer, and dryer machines measured and recorded on a weekly basis?	Ш	Yes	Ш	No		
2. Is	the washer exhaus t temperature at the condenser inlet and outlet measured						
	d recorded weekly?		Yes		No		N/A
a)	Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
	the perc concentration in the exhaust stream inlet and outlet measured weekly the end of the final drying cycle while the machine is venting to the adsorber,						
	machines are equipped exclusively with a carbon adsorber?	П	Yes	П	No	П	N/A
a)	Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A
4 Is	the sampling port on the carbon adsorber exhaust for measuring						
	rc concentrations at least 8 duct diameters downstream of any bend,						
co	ntraction, or expansion; is at least 2 duct diameters upstream from any bend,	_		_		_	
co	ntraction, or expansion; and downstream from no other inlet?	Ш	Yes	Ш	No		N/A
5 Ar	re transfer machines equipped (dryers, reclaimers, and washers) with individual						
J. 111	ndenser coils?		Yes		No		N/A
co							
	airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
			Yes		No		N/A
			Yes		No		N/A
6. Is	airflow routed to the carbon adsorber (if used) at all times?						
6. Is			(check	V	only o	one
6. Is	airflow routed to the carbon adsorber (if used) at all times?		(check x for e	V	-	one
6. Is	airflow routed to the carbon adsorber (if used) at all times?		(V	-	one
6. Is PAR 1. An	airflow routed to the carbon adsorber (if used) at all times?		(bo		each q	-	one
6. Is PART 1. Ar 2. Ar	airflow routed to the carbon adsorber (if used) at all times?		(bo		☑ each q	-	one
6. Is PART 1. Ar 2. Ar 3. Ar	airflow routed to the carbon adsorber (if used) at all times?	\boxtimes	(bo Yes Yes		each q No No	-	one on)
6. Is PART 1. Ar 2. Ar 3. Ar a)	airflow routed to the carbon adsorber (if used) at all times?	\boxtimes	(bo		each q	-	one
6. Is PART 1. Ar 2. Ar 3. Ar a)	airflow routed to the carbon adsorber (if used) at all times?		Yes Yes Yes		each q No No No	uestio	one on)
6. Is PART 1. Ar 2. Ar 3. Ar a) b)	airflow routed to the carbon adsorber (if used) at all times?	\boxtimes	(bo Yes Yes		each q No No	westion	one on) N/A N/A
6. Is PART 1. Ar 2. Ar 3. Ar a) b)	airflow routed to the carbon adsorber (if used) at all times?		Yes Yes Yes	x for e	each q No No No	westion	one on)
1. Ar 2. Ar a) b) 4. Is	airflow routed to the carbon adsorber (if used) at all times?		Yes Yes Yes	x for e	No No No	westion	one on) N/A N/A
1. Ar 2. Ar 3. Ar a) b) 4. Is 5. Is	r V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC re receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes	x for e	No No No No No	westion	one on) N/A N/A N/A
1. Ar 2. Ar 3. Ar a) b) 4. Is 5. Is 6. Is	re receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes	x for e	each q No No No No No	westion	nne nn) N/A N/A N/A
1. Ar 2. Ar a) b) 4. Is 5. Is 6. Is 7. Ar	re receipts maintained for all perc purchased? ————————————————————————————————————		Yes	x for e	No	westion	nne on) N/A N/A N/A N/A
1. Ar 2. Ar 3. Ar a) b) 4. Is 5. Is 6. Is 7. Ar a)	re receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	x for e	No	westion	nne on) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	ection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y		□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	raph sh	hall satisfy th	ie
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes Yes No N/A N/A N/A N/A N/A N/A Yes Yes	Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A

TAKT VI. LEAK DETECTION AND RELAIRS - I	Rule 62-213.300 FAC (continued)	
9. What evidence suggests that leak checks are perform	ned as required?	
□ Leak log documentation □ RO Assurance	es 🖂 On-site observation 🗌 other	
Explain other:		
Marc Lovallo	3-31-11	
Marc Lovallo Inspector's Name (Please Print)	Date of Inspection	
	Date of Inspection	