

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE</b> :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY	Y (CI)			
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO:				
<b>AIRS ID#:</b> 0250856 <b>DA</b> ′	ΓΕ: <u>7/17/06</u>	ARRIVE: <u>12:20</u>	DEPART: <u>1:05 PM</u>			
FACILITY NAME: PICASSO CLEANERS						
FACILITY LOCATION: 18514 W DIXIE HWY						
	MIAMI 33180					
RESPONSIBLE OFFIC	IAL: JOSE DIAZ	PHONE:	(305)936-0558			
CONTACT NAME:		PHONE:	PHONE:			
REMITTANCE YEAR: 2005 ENTITLE		ITLEMENT PERIOD: 2/14/2003 (effective date)	/ 2/14/2008 (end date)			
PART I: <u>INSPECTION</u> <u>COMPLIANCE</u> <u>STATUS</u> (check ✓ only one box)						
☑ IN COMPLIANO	CE MINOR Non-CO	OMPLIANCE SIGNIFICANT	Non-COMPLIANCE			
	LASSIFICATION - Rule ( ly one box in A)	62-213.300 FAC				
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)		2. New small area source dry-to-dry only, x < 140 transfer only, x < 200 gal both types, x < 140 gal/y (constructed on or after 1	/yr r			
transfer only, both types, 14	e area source $\[ \]$ ly, $140 \le x \le 2,100 \text{ gal/yr} \]$ $200 \le x \le 1,800 \text{ gal/yr} \]$ $40 \le x \le 1,800 \text{ gal/yr} \]$ before $12/9/91)$	4. New large area source dry-to-dry only, $140 \le x$ transfer only, $200 \le x \le 1$ both types, $140 \le x \le 1,8$ (constructed on or after 1)	1,800 gal/yr 00 gal/yr			
drop store/out	General Permit to f business/petroleum ds above limits					
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 225 gallons.						

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check <b>☑</b> only one box		
Do	es the responsible official of the dry cleaning facility:	for each question)		
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A		
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A		
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No		
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A		
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A		
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)			
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	ired. Proceed to Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>			
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below</b> <i>must have been installed prior to September 22, 1993</i>			
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped with a refrigerated		
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area</u> & <u>new sources</u> :	(check ☑ only one box for each question)		
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No		

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)		
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	□Yes □ No □N/A	
a) Is the temperature differential equal to, or greater than $20^{\circ}$ F?	☐Yes ☐ No ☒ N/A	
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	- □Yes □ No ⊠ N/A	
a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend,		
contraction, or expansion; and downstream from no other inlet?	- ☐Yes ☐ No ☒ N/A	
5. Equip transfer machines (dryers, reclaimers, and washers) with individual	Yes  No  N/A	
condenser coils?		
6. Route airflow to the carbon adsorber (if used) at all times?		
	- □Yes □ No ⊠ N/A	
6. Route airflow to the carbon adsorber (if used) at all times?		
6. Route airflow to the carbon adsorber (if used) at all times?  PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	- □Yes □ No ☑ N/A  (check ☑ only one box for each question)	
6. Route airflow to the carbon adsorber (if used) at all times?  PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Does the responsible official:	-	
6. Route airflow to the carbon adsorber (if used) at all times?	-	
6. Route airflow to the carbon adsorber (if used) at all times?	-	
6. Route airflow to the carbon adsorber (if used) at all times?	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Does the responsible official:  1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Does the responsible official:  1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Does the responsible official:  1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Does the responsible official:  1. Maintain receipts for perc purchased? ————————————————————————————————————	-	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Does the responsible official:  1. Maintain receipts for perc purchased? ————————————————————————————————————	-	

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check  $\square$  only one box for each question)

detection and repair inspection?	— — —				
2. Does the facility maintain a leak log?					
c) Filter gaskets and seating	bookers         Yes         No         N/A            Yes         No         N/A           dampers         Yes         No         N/A           valves         Yes         No         N/A           ge filter housings         Yes         No         N/A				
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————					
TERRENCE ANDERSON	7/17/ 06				
Inspector's Name (Please Print)	Date of Inspection				
7/07	1				
Inspector's Signature A	Approximate Date of Next Inspection				
COMMENTS: NO LEAKS, RECORDS AVAILABLE 225 GALLONS OF PERC USED DURING THE PERION					