

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) [RE-INSPECTION (FUI) [COMPLAINT/D ARMS COMPLA		7 (CI)			
AIRS ID#: 0250867 DA	ΓΕ: <u>8/3/2010</u>	ARRIVE: 1:05PM	<u>1</u>	DEPART: <u>1:30PM</u>			
FACILITY NAME: FOUNTAINBLEAU CLEANERS							
FACILITY LOCATION	10686 NW 7 STREE	ET					
	MIAMI 33150-1008	8					
OWNER/AUTHORIZED Email: CONTACT NAME: Email: ENTITLEMENT PERIC	DREPRESENTATIVE: C DD: 10/10/2005 / 10/10 (effective date) (end date	0/2010	PHONE: Mobile: PHONE: Mobile:	(305)519-3780			
DADEL INCRECTION	COMPLIANCE CEATING	(1.1.17)	`				
PART I: <u>INSPECTION COMPLIANCE STATUS</u> (check ✓ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
A. 1. Existing smal dry-to-dry only transfer only, both types, x (constructed by the constructed by transfer only, both types, 14 (constructed by the constructed by	l area source ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)	transfer only, both types, 14 (constructed of	y, x < 140 g x < 200 gal. < 140 gal/yr on or after 1: ea source y, 140 \le y $200 \le x \le$ to or after 1:	/yr 2/9/91)	this dry		
	was 30.00 gallons.	the (pere) purchases made	om each of	me previous 12 monuis by	uns ury		

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			(abaals	اكا ا	omlr. 6		
		(check ☑ only one box for each question)					
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A	
2. Are all perc. containers leak free?	\boxtimes	Yes		No		N/A	
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No			
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		No		N/A	
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A	
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A	
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC							
(Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)							
1. If the f acility classification is an existing small area source , no controls are required. F	roce	ed to F	Part V.				
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.							
3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993							
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.							
A. Has the responsible official of all existing large area & new sources:			(check ox for e		only o		
1. Equipped all machines with the appropriate vent controls?	\boxtimes	Yes		No			
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No		N/A	
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes		No		N/A	
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes		No		N/A	
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes		No	\boxtimes	N/A	
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	\boxtimes	Yes		No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)							
	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes		No		N/A
	a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes		No		N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes		No		N/A
							1
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
			Yes		No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?		(check	V	only o	one
PA			(V	only o	one
P A	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(bo		☑ each q	only o	one
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo		each q	only o	one
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo		each q	only o	one
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo Yes Yes		each q No No	only o uestio	one on)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes		No No No	only of uestion	one on)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes		No No No	only of uestion	nne nn) N/A N/A
1. 2. 3. 4. 5.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes		No No No No No	only of uestion	nne nn) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes		No No No No No No No	only of uestion	nne nn) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes		No	only of uestion	nne nn) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check	x ☑ only one
1.	What type of leak detection equipment is used to detect leaks?	box for	each question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ? 🖂	Yes	No
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes	No N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery?	Yes	No
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes	No N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes?	Yes	No 🛛 N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or touch) while the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perc	ceptible leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y	Yes	No
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated hydro	ocarbon detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraphic paragraphic) or PCE gas analyzer while the system is in operation?	raph shall sai	tisfy the
	requirements to conduct an inspection for perceptible leaks under $\S63.322(k)$ or (l))		
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes Yes NO N/A N/A	Yes	No

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)					
9. What evidence suggests that leak checks are performed as re ☐ Leak log documentation ☐ RO Assurances ☒ Explain other:	equired? On-site observation				
MARUFUL MALIK	8/3/2010				
Inspector's Name (Please Print)	Date of Inspection				
	8/3/2011				
Inspector's Signature	Approximate Date of Next Inspection				

COMMENTS: On August 03, 2010 I visited this facility to conduct the annual compliance inspection. On site I met Mr.Carlos Gonzalez, the owner of the facility. No leaks were detected in the dry cleaning machine. Perc purchase receipts and yearly perc consumption records were available. Halogen leak detector was in working condition. I advised Mr. Gonzalez to renew his entitlement which expires on October 10, 2010.