

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE:</b> ANNUAL (INS1, INS2) $\boxtimes$ COMPI	LAINT/DISCOVERY (CI)					
RE-INSPECTION (FUI) ARMS	COMPLAINT NO:					
AIRS ID#: 0250894 DATE: <u>04/21/2009</u> ARRIVE	: <u>12:45PM</u>					
FACILITY NAME: JENNY'S DRY CLEANERS						
FACILITY LOCATION: 8243 SW 40TH ST						
MIAMI 33155						
OWNER/AUTHORIZED REPRESENTATIVE: JORGE FERRET	PHONE: (305)223-6110					
CONTACT NAME:	PHONE:					
ENTITLEMENT PERIOD: 10/18/2007 / 10/18/2012 (effective date) (end date)						
PART I: INSPECTION COMPLIANCE STATUS (check ✓ only						
☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE	SIGNIFICANT Non-COMPLIANCE					
PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC (check only one box in A)						
$\frac{140 \text{ gal/yr}}{\text{dry-to-dry only, x}} < \frac{140 \text{ gal/yr}}{\text{dry-to-dry only}}$	small area source \times to-dry only, x < 140 gal/yr					
	fer only, $x < 200 \text{ gal/yr}$ types, $x < 140 \text{ gal/yr}$					
	structed on or after 12/9/91)					
3. Existing large area source 4. New	large area source					
dry-to-dry only, $140 \le x \le 2{,}100 \text{ gal/yr}$ dry-	to-dry only, $140 \le x \le 2,100 \text{ gal/yr}$					
	fer only, $200 \le x \le 1,800 \text{ gal/yr}$ types, $140 \le x \le 1,800 \text{ gal/yr}$					
(constructed before 12/9/91) (con	structed on or after 12/9/91)					
5. Ineligible for General Permit						
drop store/out of business/petroleum facility exceeds above limits						
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 0 gallons.						

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			(check <b>☑</b> only one box					
Does the responsible official of the dry cleaning facility:			h questi	on)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes [	□No	□N/A				
2.	Examine the containers for leakage?	⊠Yes [	☐ No	□ N/A				
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes [	☐ No					
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes [	□ No	□ N/A				
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes [	□ No	⊠ N/A				
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)							
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	ired. Proce	eed to I	Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>							
	3. If the facility classification is a <b>Existing large</b> area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993							
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped wi	th a refr	rigerated				
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :	(check ☑ only one box for each question)						
1.	Equipped all machines with the appropriate vent controls?	⊠Yes [	□No					
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes [	□No	□N/A				
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes [	□No	□N/A				
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes [	□No					
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ∐Yes [	□No	⊠N/A				
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes [	□No					

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)						
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)					
1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No					
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	-  Yes  No  N/A					
a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A					
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A					
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A					
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No No					
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes  No  N/A					
6. Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No □ N/A					
PART V: RECORDKEEPING REQUIREMENTS - Rule 62-213.300(3) FAC	(1 1 <del>[</del> ] 1					
Does the responsible official:	(check ✓ only one box for each question)					
1. Maintain receipts for perc purchased?	- Xes No					
2. Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No					
3. Maintain leak detection inspection and repair reports for the following:						
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A					
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No     N/A					
4. Maintain calibration data? (for applicable direct reading instruments)						
	Yes No No N/A					
5. Maintain exhaust duct monitoring data on perc concentrations?						
<ul><li>5. Maintain exhaust duct monitoring data on perc concentrations?</li><li>6. Maintain a startup/shutdown/malfunction plan?</li></ul>	Yes No N/A					
	Yes No No					
6. Maintain a startup/shutdown/malfunction plan?	Yes					
6. Maintain a startup/shutdown/malfunction plan?	Yes					

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?				
2. Does the facility maintain a leak log?	\(\) Yes \(\) No			
3. Does the responsible official check the following areas for leaks?  a) Hose connections, fittings,     couplings, and valves	s			
4. Which method(s) of detection (is/are) used by the responsible official?				
a) Visual examination (condensed solvent on exterior surfaces)				
MARUFUL MALIK 04/21/2009				
Inspector's Name (Please Print)	Date of Inspection			
	04/2010			
Inspector's Signature	Approximate Date of Next Inspection			

**COMMENTS:** On April 21, 2009 I visited this facility to conduct an annual compliance inspection. On site I met Mr.Jorge Ferret, the owner of the facility. No leaks were detected in the dry cleaning machine. He owner mentioned that he hardly uses the dry cleaning machine, perhaps once a week. He has not purchased any perc since July, 2008. However, the facility keeps a Halogen leak detector.