

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE</b> :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY	(CI)		
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO:			
AIRS ID#: 0250900 DA'	TF. 11/15/06	ARRIVE: <u>11:10 AM</u>	DEDART, 11.20 AM		
	DEPART: <u>11:30 AM</u>				
FACILITY NAME: BEST QUALITY CLEANERS					
FACILITY LOCATION	14720 NE 6TH AVE				
	MIAMI 33161				
RESPONSIBLE OFFIC	IAL: AMIN LALJI	<b>PHONE:</b> (305)949-7766			
CONTACT NAME:		PHONE:			
REMITTANCE YEAR: 2005 ENTIT		<b>LEMENT PERIOD:</b> 4/8/2002 / 4/8/2007 (effective date) (end date)			
PART I: INSPECTION	COMPLIANCE STATUS (che	ck 🗹 only one box)			
☐ IN COMPLIANO	CE MINOR Non-COMPI	LIANCE SIGNIFICANT	Non-COMPLIANCE		
	LASSIFICATION - Rule 62-21 y one box in A)	3.300 FAC			
transfer only, both types, x	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)	<ul> <li>2. New small area source dry-to-dry only, x &lt; 140 g transfer only, x &lt; 200 gal/both types, x &lt; 140 gal/yr (constructed on or after 12</li> <li>4. New large area source</li> </ul>	yr 2/9/91)		
transfer only, both types, 14	ly, $140 \le x \le 2,100$ gal/yr $200 \le x \le 1,800$ gal/yr $10 \le x \le 1,800$ gal/yr perfore $12/9/91$ )	dry-to-dry only, $140 \le x \le$ transfer only, $200 \le x \le 1$ , both types, $140 \le x \le 1,80$ (constructed on or after 12)	800 gal/yr 0 gal/yr		
drop store/out	General Permit  tof business/petroleum ds above limits				
B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was gallons.					

	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check only one box				
Do	es the responsible official of the dry cleaning facility:	for each question)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No □N/A				
2.	Examine the containers for leakage?	□Yes □ No □ N/A				
3.	Close and secure machine doors except during loading/unloading?	☐ Yes ☐ No				
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	□Yes □ No □ N/A				
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No □ N/A				
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requ	nired. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>					
	<ol> <li>If the facility classification is a Existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993</li> <li>If the facility classification is a New large area source, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.</li> </ol>					
	•					
A.	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :	(check ☑ only one box for each question)				
1.	Equipped all machines with the appropriate vent controls?	-  Yes  No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes  No  N/A				
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?					
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\Begin{aligned} Yes  \Box No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes  No  N/A				
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	- □Yes □No				

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No No		
	a) Is the temperature differential equal to, or greater than $20^{\rm o}{\rm F?}$	☐Yes ☐ No ☐ N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	-  Yes  No  N/A		
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A		
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check <b>☑</b> only one box for		
Do	pes the responsible official:	each question)		
1.	Maintain receipts for perc purchased?	Yes No		
2.	Maintain rolling monthly total of yearly perc consumption?	☐ Yes ☐ No		
3.	Maintain leak detection inspection and repair reports for the following:			
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A		
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A		
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☐ N/A		
5.	Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A		
6.	Maintain a startup/shutdown/malfunction plan?	Yes No		
7.	Maintain deviation reports?	Yes No N/A		
	a) Problem corrected?	- Yes No N/A		
8.	Maintain a compliance plan, if applicable?	Yes No N/A		

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Yes No
Does the facility maintain a leak log?	
3. Does the responsible official check the following areas for leaks?  a) Hose connections, fittings,     couplings, and valves	ck cookers
4. Which method(s) of detection (is/are) used by the responsible official a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tube e) Halogen leak detector  **If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 0-50 2) Calibrated against a standard gas prior to and after each use (PID/3) Inspected for leaks and obvious signs of wear on a weekly basis? 4) Kept in a clean and secure area when not in use?	a)
5) Verified for accuracy by use of duplicate samples (calorimetric or	
TERRENCE ANDERSON	11/15/06
Inspector's Name (Please Print)	Date of Inspection
	11/07
Inspector's Signature	Approximate Date of Next Inspection
COMMENTS: NO PERC IN MACHINE FACILITY USED ONLY AS DROP STORE NOTIFICATION TO SURRENDER PERMIT LEFT TO BE COMPLE NO DRY CLEANING DONE ON SITE. RO HAS ANOTHER STORE WHERE DRY CLEANING IS DONE.	ETED