CHARTERIN WOTECTION	
Some Man	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)			
AIRS ID#: 0250920 DATE: <u>3/13/2013</u>	ARRIVE: <u>12:37 AM</u> DEPART: <u>1:06 PM</u>			
FACILITY NAME: SOCIETY CLEANERS				
FACILITY LOCATION: 3912 SW 8TH STREET				
CORAL GABLES 3313	j4-2902			
OWNER/AUTHORIZED REPRESENTATIVE: LOUF Email: CONTACT NAME: Email: ENTITLEMENT PERIOD: 6/21/2007 / 6/21/2012 (effective date) (end date)	RDES SANCHEZ PHONE: (305)444-6611 Mobile: PHONE: Mobile: Facility may be operating without Entitlement!			
PART I: INSPECTION COMPLIANCE STATUS (che IN COMPLIANCE IN COMPLIANCE				
PART II: FACILITY CLASSIFICATION (check \square only one box in A) - Rule 62-213.300 FAC A.1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr \square 3. Existing large area source dry-to-dry only, 140 \le x \le 2,100 gal/yr transfer only, 200 \le x \le 1,800 gal/yr both types, 140 \le x \le 1,800 gal/yr (constructed before 12/9/91) 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, 200 \le x \le 1,800 gal/yr transfer only, 200 \le x \le 1,800 gal/yr transfer only, 200 \le x \le 1,800 gal/yr both types, 140 \le x \le 1,800 gal/yr (constructed before 12/9/91) 4. New large area source dry-to-dry only, 140 \le x \le 2,100 gal/yr transfer only, 200 \le x \le 1,800 gal/yr transfer only, 200 \le x \le 1,800 gal/yr both types, 140 \le x \le 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit d rop store/out of business/petroleum / facility exceeds above limits 9. B. The sum of the volume of all perchloroethylene (perc) purchases made in each of the previous 12 months by this dry				

cleaning facility was 77.20 gallons.

			;		
PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			check 🗹 x for each		
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	🗌 No	→ □	N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes		→ □	N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes	□ No)	
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 	\square	Yes	🗌 No	→ □	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with				_	
manufacturer's instructions.		Yes	□ No	\rightarrow	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes	🗌 No		N/A
 If the f acility classification is an <u>existing small area source</u>, no controls are required. Proceed to Part V. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below. If the fa cility classification is an <u>existing large area source</u>, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i> 					
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped we condenser. Complete both sections A and B below.	with	1 refrig	;erated		
A. Has the responsible official of all <u>existing large area & new sources</u> :		`	check 🗹 x for each	2	
1. Equipped all machines with the appropriate vent controls?	\boxtimes	Yes	□ No)	
1	\boxtimes	Yes		→ □	
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		105			N/A
 Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? 		Yes		,	N/A N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away				_	

6	Conducted all temperature monitoring after an appropriate cool-down period and				
			X 7		
	after verifying that the coolant had been completely charged?	M	Yes	L No	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)				
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	\bowtie	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? a) Is the temperature differential equal to, or greater than 20° F?		Yes Yes	D No	⊠ N/A ⊠ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	🗌 No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	🗌 No	N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	🗌 No	N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	`	eck 🗹 For each q	only one uestion)
1. Are receipts maintained for all perc purchased?	Yes [No	
2. Are rolling monthly total s of yearly perc consumption maintained ?	Yes [No	
3. Are leak detection inspection and repair reports maintained for the following:			
a) Of any leaks repaired w/in 24 hrs? or;	Yes [No	N/A
b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes [] No	N/A
4. Is calibration data maintained for applicable direct reading instruments?	Yes [No	N/A
5. Is exhaust duct monitoring data on perc concentrations maintained?	Yes [No	N/A
6. Is a startup/shutdown/malfunction plan maintained for each machine?	Yes [No	
7. Are deviation reports maintained?	Yes [No	N/A
a) Problem corrected?	Yes [No	N/A
8. Is a compliance plan maintained, if applicable?	Yes [No	N/A

P	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	box for each q	uestion)
	Halogenated hydrocarbon detector PCE gas analyzer None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ? 🖂	Yes 🗌 No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes 🗌 No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery?	Yes 🗌 No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes 🗌 No	N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes? $\hfill \hfill $	Yes 🗌 No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	mell or touch) while	e the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perceptible	e leaks)
	b) Door gaskets and seating Yes No N/A h) Stills X c) Filter gaskets and seating Yes No N/A i) Exhaust dampers X d) Pumps Yes No N/A j) Diverter valves Y	Yes No [Yes No [Yes No [Yes No [Yes No [N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated hydrocarbo	n detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph shall satisfy the	2
	requirements to conduct an inspection for perceptible leaks under $(3.322(k) \text{ or } (l))$		
	b) Door gaskets and seating Xes No N/A N) Stills c) Filter gaskets and seating Xes No N/A i) Exhaust dampers	Yes No Yes No Yes No Yes No Yes No	N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)				
 9. What evidence suggests that leak checks are performed as required? 				
	2/10/2010			
FRANK DELGADO	3/13/2013			
Inspector's Name (Please Print)	Date of Inspection			
	3/2014			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS: RAY GORDON AND I INSPECTED THE FACILITY. WE DID NOT FIND ANY LEAKS AROUND THE DRY CLEANING MACHINE. THE MACHINE WAS IN USE AT THE TIME OF THE INSPECTION. THE CONDENSER TEMPERATURE WAS 40 DEGREES FAHRENHEIT. ALL RECORDS WERE AVAILABLE AND FOUND UP-TO-DATE. THE ENTITLEMENT PERIOD HAS EXPIRED. THE OWNER SUBMITTED AN ELECTRONIC RENEWAL TO THE FDEP THE NEXT DAY.				

REVIEWED By Ray Gordon at 12:00 pm, Apr 05, 2013