

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: AN	NNUAL (INS1, INS2)	COMP	LAINT/DISCOVERY	Y(CI)				
RE	E-INSPECTION (FUI)	ARMS	COMPLAINT NO:					
<b>AIRS ID#:</b> 0250923 <b>DATE:</b>	<u>12/7/06</u>	ARRIVE	: <u>12:25 PM</u>	DEPART: <u>1:00 PM</u>				
FACILITY NAME: MR. TONY'S DRY CLEANING & LAUNDRY								
FACILITY LOCATION: 4315 NW 7TH STREET #9								
	MIAMI 33126							
RESPONSIBLE OFFICIAL	: JULIO RAMOS		PHONE:	(305)448-3808				
CONTACT NAME:		PHONE:						
REMITTANCE YEAR: 200	05 ENTIT	TLEMENT PE	ERIOD: 11/20/2005 (effective date)	/ 11/20/2010 (end date)				
PART I: <u>INSPECTION</u> CO	MPLIANCE STATUS	(check <b>v</b> only	one box)					
IN COMPLIANCE	MINOR Non-CO	MPLIANCE	SIGNIFICANT	Non-COMPLIANCE				
PART II: FACILITY CLAST (check only or		2-213.300 FAC						
A. 1. Existing small ardry-to-dry only, x transfer only, x < both types, x < 14 (constructed before a dry-to-dry only, 1	x < 140 gal/yr 200 gal/yr 40 gal/yr re 12/9/91)	dry- tran both (cor	to-dry only, $x < 140$ ; sfer only, $x < 200$ gal a types, $x < 140$ gal/yr astructed on or after 1 $x$ large area source to-dry only, $x < x$	/yr r 2/9/91)				
transfer only, 200 both types, $140 \le$ (constructed before	$0 \le x \le 1,800 \text{ gal/yr}$ $x \le 1,800 \text{ gal/yr}$ $x \le 12/9/91)$	tran both	sfer only, $200 \le x \le 1$ 1 types, $140 \le x \le 1,8$ 1 structed on or after 1	,800 gal/yr 00 gal/yr				
5. Ineligible for General drop store/out of facility exceeds all	business/petroleum							
B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 15 gallons.								

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check <b>☑</b> only one box				
Do	es the responsible official of the dry cleaning facility:	for ea	ich questi	on)		
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A		
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A		
3.	3. Close and secure machine doors except during loading/unloading?		☐ No			
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes	□ No	□ N/A		
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes	□No	⊠ N/A		
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	red. Pro	ceed to I	Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>					
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993					
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated		
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area</u> & <u>new sources</u> :		(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	□N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	□No	□N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	□No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	□No	⊠N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No			

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)					
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No			
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	-  Yes  No  N/A			
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	□Yes □ No □ N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A			
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A			
6.	Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No □ N/A			
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(-bl- 🗸l b f			
Does the responsible official:		(check ✓ only one box for each question)			
1.	Maintain receipts for perc purchased?	Yes No			
	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No			
3.	Maintain leak detection inspection and repair reports for the following:				
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A			
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No   ⊠ N/A			
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A			
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☒ N/A			
6.	Maintain a startup/shutdown/malfunction plan?	Yes □ No			
7.	Maintain deviation reports?	Yes No N/A			
	a) Problem corrected?	Yes No N/A			
8.	Maintain a compliance plan, if applicable?	Yes No N/A			
1					

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check  $\square$  only one box for each question)

detection and repair inspection?			
2. Does the facility maintain a leak log?	⊠ Yes □ No		
d) Pumps \textcolor Yes \textcal No \textcal N/A j) Diverte	cookers  Yes No N/A  Yes No N/A  th dampers  Yes No N/A  Yes No N/A		
4. Which method(s) of detection (is/are) used by the responsible official?			
a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) e) Halogen leak detector **If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 0-500 2) Calibrated against a standard gas prior to and after each use (PID/FI 3) Inspected for leaks and obvious signs of wear on a weekly basis? 4) Kept in a clean and secure area when not in use?	b)		
TERRENCE ANDERSON	12/7/06		
Inspector's Name (Please Print)	Date of Inspection		
•	2/07		
Inspector's Signature	Approximate Date of Next Inspection		
COMMENTS: NEW RO: NOTIFICATION COMPLETED NO LEAKS RECORDS UPDATED DURING INSPECTION (WRONG CALENDAR	R MAILED TO FACILITY)		