

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE: | ANNUAL (INS1, INS2) RE-INSPECTION (FUI) | COMPLAINT/DISCOVER ARMS COMPLAINT NO: | · / — |
|---|--|---|------------------------------------|
| AIRS ID#: 0250926 DA | TE: <u>3/28/2011</u> | ARRIVE: 1:25PM | DEPART: <u>2:00PM</u> |
| FACILITY NAME: PAI | RIS DRY CLEANERS | | |
| FACILITY LOCATION | V: 12212 SW 8TH ST | | |
| | MIAMI 33184-1552 | | |
| OWNER/AUTHORIZEI Email: CONTACT NAME: M Email: ENTITLEMENT PERIC | IUHAMMAD QUADRI | Mobile: | : (305)551-9515 : (305)551-9515 |
| PART I: <u>INSPECTION</u> | COMPLIANCE STATUS (c | check 🗹 only one box) | |
| IN COMPLIANC | CE MINOR Non-COM | PLIANCE SIGNIFICAN | IT Non-COMPLIANCE |
| A. 1. Existing small dry-to-dry onl transfer only, both types, x (constructed by 3. Existing larged dry-to-dry onl transfer only, | only one box in A) Il area source ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr perfore 12/9/91) | 2-213.300 FAC 2. New small area source dry-to-dry only, x < 140 transfer only, x < 200 gas both types, x < 140 gal/y (constructed on or after 4. New large area source dry-to-dry only, 140 ≤ transfer only, 200 ≤ x both types, 140 ≤ x ≤ | 0 gal/yr al/yr ('yr 12/9/91) |
| 5. Ineligible for d rop store/ou facility exceed | | (constructed on or after | |

| PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC | | | check 🗹 x for each | only one question) | | |
|--|-------|----------|-----------------------|--------------------|--|--|
| 1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers? | | Yes | ☐ No | N/A | | |
| 2. Are all perc. containers leak free? | | Yes | ☐ No | □ N/A | | |
| 3. Are all machine doors kept closed and secured except during loading/unloading? | | Yes | ☐ No | | | |
| 4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? | | Yes | ☐ No | □ N/A | | |
| 5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions. | | Yes | ☐ No | □ N/A | | |
| 6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications? | | Yes | ☐ No | □ N/A | | |
| | | | | | | |
| PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form) | | | | | | |
| 1. If the f acility classification is an <u>existing small area source</u> , no controls are required. P | rocee | ed to P | art V. | | | |
| 2. If the facility classification is a new small area source , the machine should be equipped with a refrigerated condenser. Complete section A. below. | | | | | | |
| 3. If the fa cility classification is an existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 | | | | | | |
| 4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below. | with | a refrig | gerated | | | |
| A. Has the responsible official of all existing large area & new sources: | | | check ☑ x for each | only one question) | | |
| 1. Equipped all machines with the appropriate vent controls? | | Yes | ☐ No | | | |
| 2. Equipped dry-to-dry machines with a closed-loop vapor venting system? | | Yes | ☐ No | □ N/A | | |
| 3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? | | Yes | ☐ No | □ N/A | | |
| 4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? | | Yes | ☐ No | □ N/A | | |
| 5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? | | Yes | ☐ No | □ N/A | | |
| | Ш | | | | | |

| PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued) | | | | | |
|---|-------------|---------------------------------|---------------------------------------|----------|-------------------|
| B. For all existing large or new large area sources: 1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis? | | Yes | □ No | O | |
| 2. Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? | | Yes | □ No | o 🗌 | N/A |
| a) Is the temperature differential equal to, or greater than 20° F? | | Yes | ☐ No | о 🗌 | N/A |
| 3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? | | Yes | □ Ne | о 🗆 | N/A |
| a) Is the perc concentration equal to, or less than 100 ppm? | | Yes | □ No | о 🗌 | N/A |
| 4. Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | | Yes | □ No | о 🗆 | N/A |
| 5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils? | | Yes | □ No | о 🗆 | N/A |
| 6. Is airflow routed to the carbon adsorber (if used) at all times? | | Yes | □ No | o 🗌 | N/A |
| | | | | | |
| | | | | | |
| PARTY PECONDECEDING REQUIREMENTS Puls (2.212.2007) EAC | | | | | |
| PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC | | , | check ✓ x for eac | | |
| PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ———————————————————————————————————— | <u></u> | , | | h quest | |
| | | bo | x for eac | h quest | |
| 1. Are receipts maintained for all perc purchased? | | bo | x for eac | h quest | |
| Are receipts maintained for all perc purchased? Are rolling monthly total s of yearly perc consumption maintained? | | bo | x for eac | h quest | |
| Are receipts maintained for all perc purchased? | | Yes Yes | x for eac | h quest | ion) |
| 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days | | bo Yes Yes Yes | x for eac | h questi | N/A |
| 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | | bo Yes Yes Yes | x for eac | h questi | N/A N/A |
| Are receipts maintained for all perc purchased? | | Yes Yes Yes Yes Yes | X for eac | h questi | N/A N/A N/A |
| Are receipts maintained for all perc purchased? | | Yes Yes Yes Yes Yes Yes | No | h questi | N/A N/A N/A |
| Are receipts maintained for all perc purchased? | | Yes Yes Yes Yes Yes Yes Yes Yes | No No No No No No No No | h questi | N/A N/A N/A N/A |

| PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC | | | only one |
|--|--|---|-------------------------------------|
| 1. W | hat type of leak detection equipment is used to detect leaks? | box for each | question) |
| | Halogenated hydrocarbon detector PCE gas analyzer None used | | |
| 2. Is | the halogenated hydrocarbon detector or PCE gas analyzer operated according to | | |
| th | e manufacturer's instructions (manual was available and RO could demonstrate | | |
| pr | ocedure) ? | Yes No | |
| 3. Fo | or major sources is the halogenated hydrocarbon detector or PCE gas analyzer | | |
| Oj | perated according to EPA Method 21 ? | Yes No | N/A |
| 4. Is | the vapor leak inspection conducted by placing the probe inlet at the surface of | | |
| ea | ch component interface where leakage could occur and moving it slowly along | | |
| the | e interface periphery? | Yes No | |
| 5. Is | the PCE gas analyzer a flame ionization detector, photo ionization detector, or | | |
| in | frared analyzer capable of detecting vapor concentrations of PCE of 25 parts per | | |
| mi | illion by volume (based on documented specifications) ? | Yes No | N/A |
| 6. Is | the halogenated hydrocarbon detector capable of detecting vapor concentrations | | |
| of | PCE of 25 parts per million by volume (based on documented specifications) and | | |
| ine | dicating a concentration of 25 parts per million by volume or greater by emitting | | |
| an | audible or visual signal that varies as the concentration changes? | Yes No | N/A |
| 7. Aı | re the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm | nell or touch) while | e the |
| sy | stem is in operation (§63.322(k))? | | |
| (In | spection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp | pection of perceptibl | le leaks) |
| b) c) d) e) | Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Y | Yes No Yes No Yes No Yes No Yes No | □ N/A □ N/A □ N/A □ N/A □ N/A □ N/A |
| 8. Aı | re the following dry cleaning system components inspected monthly for vapor leaks using a halogo | genated hydrocarbo | on detector |
| or | PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag | graph shall satisfy th | e |
| rec | quirements to conduct an inspection for perceptible leaks under $\S 63.322(k)$ or (l)) | | |
| b) c) | Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Yes No N/A j | Yes No Yes No Yes No Yes No Yes No Yes No | □ N/A □ N/A □ N/A □ N/A □ N/A □ N/A |

| PART VI: LEAK DETECTION AND REPAIRS – Rule 62 | 2-213.300 FAC (continued) | | | | | |
|---|-------------------------------------|--|--|--|--|--|
| 9. What evidence suggests that leak checks are performed as required? Leak log documentation RO Assurances On-site observation other Explain other: | | | | | | |
| MARUFUL MALIK | 3/28/2011 | | | | | |
| Inspector's Name (Please Print) | Date of Inspection | | | | | |
| | 3/28/2012 | | | | | |
| Inspector's Signature | Approximate Date of Next Inspection | | | | | |

COMMENTS: This facility is operating as a drop store since May, 2009. The Aerotech USA, Dry Cleaning Machine, is still on site but it does not have any Perc. However, Muhammad Quadri, the owner wants to keep the permit active.