

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVER	Y (CI)			
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO:				
AIRS ID#: 0250935 DA ′	TE: <u>11/19/08</u>	ARRIVE: <u>2:35P.M.</u>	DEPART: <u>3:05P.M.</u>			
FACILITY NAME: CALUSA CLEANERS INC						
FACILITY LOCATION: 7914 SW 104TH STREET						
	MIAMI 33156-3632					
OWNER/AUTHORIZED REPRESENTATIVE: ENRIQUE ALVAREZ PHONE: (305)270-1188						
CONTACT NAME:		PHONE:				
ENTITLEMENT PERIO		2				
	(effective date) (end date)					
PART I: INSPECTION	COMPLIANCE STATUS (che	eck 🗹 only one box)				
☐ IN COMPLIANO	CE MINOR Non-COMPI	LIANCE SIGNIFICAN	Γ Non-COMPLIANCE			
	LASSIFICATION - Rule 62-21	3.300 FAC				
(check 🗹 onl	y one box in A)					
A. 1. Existing smal	l <u>l area source</u> ly, x < 140 gal/yr	2. New small area source dry-to-dry only, x < 140	cal/vr			
transfer only,	x < 200 gal/yr	transfer only, $x < 200$ ga	l/yr			
both types, x	< 140 gal/yr pefore 12/9/91)	both types, $x < 140$ gal/y (constructed on or after				
(constructed t	Clore 12/7/71)	(constructed on or arter				
3. Existing large	e area source	4. New large area source dry-to-dry only, $140 \le x$	< 2.100 gal/yr			
	$200 \le x \le 1,800 \text{ gal/yr}$	transfer only, $200 \le x \le$				
both types, 14	$40 \le x \le 1,800 \text{ gal/yr}$	both types, $140 \le x \le 1.8$				
(constructed t	pefore 12/9/91)	(constructed on or after	12/9/91)			
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits						
B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 126 gallons.						

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	•	only or			
Does the responsible official of the dry cleaning facility:			for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A		
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A		
3.	Close and secure machine doors except during loading/unloading?	X Yes	☐ No			
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes	□ No	□ N/A		
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes	□ No	⊠ N/A		
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a Existing small area source, no controls are requi	red. Pro	ceed to l	Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.					
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993					
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated		
Α.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :		only each ques	one box for stion)		
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	□N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	□No	□N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	□No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes	□No	⊠N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)					
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)				
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No				
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- □Yes □ No ⊠N/A				
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☒ N/A				
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A				
a) Is the perc concentration equal to, or less than 100 ppm?	□Yes □ No ⊠ N/A				
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend,					
contraction, or expansion; and downstream from no other inlet?	Yes No N/A				
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	□Yes □ No ⊠ N/A				
6. Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No ⊠ N/A				
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC					
Does the responsible official:	(check v only one box for each question)				
1. Maintain receipts for perc purchased?	- 🛚 Yes 🔲 No				
2. Maintain rolling monthly total of yearly perc consumption?	∑ Yes □ No				
3. Maintain leak detection inspection and repair reports for the following:					
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A				
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days					
and parts installed w/in 5 days of receipt?	☐ Yes ☐ No ☒ N/A				
4. Maintain calibration data? (for applicable direct reading instruments)	 ☐ Yes ☐ No ☑ N/A ☐ Yes ☐ No ☑ N/A 				
	☐ Yes ☐ No ☒ N/A				
4. Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A				
4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations?	 ☐ Yes ☐ No ☐ No ☐ No ☐ No ☐ No 				
4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A				

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	X Yes No			
2. Does the facility maintain a leak log?				
3. Does the responsible official check the following areas for leaks a) Hose connections, fittings, couplings, and valves	Muck cookers \(\) Yes \(\) No \(\) N/A Stills \(\) Yes \(\) No \(\) N/A Exhaust dampers \(\) Yes \(\) No \(\) N/A Diverter valves \(\) Yes \(\) No \(\) N/A			
4. Which method(s) of detection (is/are) used by the responsible official?				
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————				
MARUFUL MALIK 11/19/08				
Inspector's Name (Please Print)	Date of Inspection			
	11/30/2008			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: I visited this facility to conduct an annual inspection. On site I met Katerin Ballesteros, an atendant at the facility. A leak was detected in the dry cleaning machine, therefore, an FNOV was issued. Reinspection will be on at 11/30/2008.