

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2)	COMPLAINT/DIS	COVERY (CI)		
	RE-INSPECTION (FUI)	ARMS COMPLAIN	NT NO:		
AIRS ID#: 0310436 DA7	ГЕ: <u>2/27/06</u>	ARRIVE:	DEPART:		
FACILITY NAME: CHIMNEY LAKES CLEANERS					
FACILITY LOCATION: 8540-12 ARGYLE FOREST BLVD					
	JACKSONVILLE 322	244			
RESPONSIBLE OFFICE	IAL: ADIL KOREL	<b>PHONE:</b> (904)779-0904			
CONTACT NAME: same		PHONE: (			
REMITTANCE YEAR:	2005 ENTITI	<b>LEMENT PERIOD:</b> 12/30/1997 / 12/30/2002 (effective date) (end date)			
	COMPLIANCE STATUS (cl				
	CE MINOR Non-COM	PLIANCE   SIGNI	FICANT Non-COMPLIANCE		
	<b>LASSIFICATION</b> - <b>Rule 62-</b> 2 y one box in A)	213.300 FAC			
transfer only, both types, x <	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)	<ul> <li>2. New small area dry-to-dry only, transfer only, x doth types, x &lt; 1 (constructed on the state of t</li></ul>	x < 140 gal/yr < 200 gal/yr   40 gal/yr   or after 12/9/91)		
dry-to-dry onl transfer only, both types, 14	y, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $0 \le x \le 1,800 \text{ gal/yr}$ refore $12/9/91$	dry-to-dry only, transfer only, 20	$140 \le x \le 2,100 \text{ gal/yr}$ $10 \le x \le 1,800 \text{ gal/yr}$ $10 \le x \le 1,800 \text{ gal/yr}$		
	General Permit of business/petroleum ds above limits				
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 115 gallons.					

	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check only one box			
Do	es the responsible official of the dry cleaning facility:	for each question)			
	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	Yes No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	⊠Yes □ No □ N/A			
	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)				
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	nired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>				
	3. If the facility classification is a <b>Existing large</b> area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	equipped with a refrigerated			
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	- ⊠Yes □No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes □No □N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes □No □N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	⊠Yes □No □N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	- ⊠Yes □No			

PA	PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No			
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No No			
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	☐Yes ☐ No ☐ N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A			
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes  No  N/A			
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A			
PA	PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC (check ☑ only one box for				
Does the responsible official:		each question)			
1.	Maintain receipts for perc purchased?	Yes No			
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No			
3.	Maintain leak detection inspection and repair reports for the following:				
	a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A			
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No     N/A			
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A			
5.					
_	Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A			
6.	Maintain exhaust duct monitoring data on perc concentrations?  Maintain a startup/shutdown/malfunction plan?				
		Yes No			
	Maintain a startup/shutdown/malfunction plan?	Yes □ No □ N/A			
7.	Maintain a startup/shutdown/malfunction plan? Maintain deviation reports?	Yes □ No  Yes □ No □ N/A  Yes □ No □ N/A			

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check  $\square$  only one box for each question)

detection and repair inspection?	<del></del>			
2. Does the facility maintain a leak log?				
b) Door gaskets and seating	fluck cookers			
<ul> <li>4. Which method(s) of detection (is/are) used by the responsible official?</li> <li>a) Visual examination (condensed solvent on exterior surfaces)</li></ul>				
b) Physical detection (airflow felt through gaskets)	b) 🔀			
c) Odor (noticeable perc odor)				
d) Use of direct-reading instrumentation (FID/PID/calorimetric to				
e) Halogen leak detector	e)			
**If using direct-reading instrumentation, is the equipment: — ** N/A  1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? — 1) Yes No  2) Calibrated against a standard gas prior to and after each use (PID/FID only)? — 2) Yes No  3) Inspected for leaks and obvious signs of wear on a weekly basis? — 3) Yes No  4) Kept in a clean and secure area when not in use? — 4) Yes No  5) Verified for accuracy by use of duplicate samples (calorimetric only)? — 5) Yes No				
Levante Davis	2/27/06			
Inspector's Name (Please Print)	Date of Inspection			
	2/1/07			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS: Owner given application for renewal of AGP				