

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOV	VERY (CI)		
	RE-INSPECTION (FUI)	ARMS COMPLAINT	NO:		
AIRS ID#: 0890425 DA	TE: <u>3-3-08</u>	ARRIVE: <u>130</u>	DEPART: <u>145</u>		
FACILITY NAME: FERNANDINA CLEANERS					
FACILITY LOCATION	N: 832 S 8th Street				
	FERNANDINA BEACH	32034-3705			
OWNER/AUTHORIZED REPRESENTATIVE: JOAN LYLO PHONE: (904)261-3542					
CONTACT NAME:		РНО	NE:		
ENTITLEMENT PERIOD: 1/27/2002 / 1/27/2007 Facility may be operating without Entitlement! (end date)					
		. 🗖			
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)					
⊠ IN COMPLIAN	CE MINOR Non-COMPI	LIANCE SIGNIFIC	ANT Non-COMPLIANCE		
	<u>CLASSIFICATION</u> - Rule 62-21 ly one box in A)	3.300 FAC			
transfer only, both types, x	aly, x < 140 gal/yr , x < 200 gal/yr	2. New small area sou dry-to-dry only, x < transfer only, x < 20 both types, x < 140 (constructed on or a	140 gal/yr 0 gal/yr gal/yr		
transfer only, both types, 14	ge area source lly, $140 \le x \le 2,100 \text{ gal/yr}$, $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91)$	4. New large area sou dry-to-dry only, 140 transfer only, $200 \le$ both types, $140 \le x$ (constructed on or a	$x \le 2,100 \text{ gal/yr}$ $x \le 1,800 \text{ gal/yr}$ $x \le 1,800 \text{ gal/yr}$		
drop store/ou	r General Permit to f business/petroleum eds above limits				
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 95 gallons.					

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box			
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	⊠Yes □ No □ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source, no controls are requi	nired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	equipped with a refrigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	- ⊠Yes □No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes □No □N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes □No □N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes No N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	- ⊠Yes □No			

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No			
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- □Yes □ No □N/A			
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☐ N/A			
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A			
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A			
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A			
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?				
6. Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A			
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ✓ only one box for				
Does the responsible official:	each question)			
1. Maintain receipts for perc purchased?	- 🛚 Yes 🔲 No			
2. Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No			
3. Maintain leak detection inspection and repair reports for the following:				
3. Manual reak detection inspection and repair reports for the following.				
a) documentation of leaks repaired w/in 24 hrs? or;				
a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days	- Yes No N/A			
a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	-			
 a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 	-			
 a) documentation of leaks repaired w/in 24 hrs? or;	-			
 a) documentation of leaks repaired w/in 24 hrs? or;	-			
 a) documentation of leaks repaired w/in 24 hrs? or;	-			

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	X Yes No				
2. Does the facility maintain a leak log?					
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves					
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) e) Halogen leak detector	b) \overline{\overline{\sigma}} b) \overline{\sigma} c) \overline{\sigma} d) \overline{\sigma}**(see below) e) \overline{\sigma}				
2) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) Yes No					
3) Inspected for leaks and obvious signs of wear on a weekly basis? 3) Yes No 4) Kept in a clean and secure area when not in use? 4) Yes No					
5) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) Yes No					
Marc Lovallo	3-3-08				
Inspector's Name (Please Print) D	rate of Inspection				
MAr	ch 2009				
Inspector's Signature A	pproximate Date of Next Inspection				
COMMENTS:					