

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVE	· · ·				
AIRS ID#: 0571192 DAT	E: <u>10/10/2012</u>	ARRIVE: <u>10:45am</u>	DEPART: <u>11:10am</u>				
FACILITY NAME: FLE	ETWOOD CLEANERS						
FACILITY LOCATION:	4343 HENDERSON BL	VD, STE #110					
	TAMPA 33629-5657						
OWNER/AUTHORIZED Email: CONTACT NAME: Email: ENTITLEMENT PERIO	D: 8/1/2008 / 8/1/2013 (effective date) (end date)	TURNER PHONI Mobile PHONI Mobile	E:				
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☐ IN COMPLIANCE ☑ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
PART II: FACILITY CL (check or	ASSIFICATION - Rule 62- nly one box in A)	-213.300 FAC					
transfer only, x both types, x < (constructed be 3. Existing large dry-to-dry only transfer only, 2 both types, 140 (constructed be 5. Ineligible for	y, $x < 140 gal/yrx < 200 gal/yrx < 140 gal/yrx = 140 gal/$	 2. New small area source dry-to-dry only, x < 14 transfer only, x < 200 both types, x < 140 ga (constructed on or after dry-to-dry only, 140 ≤ transfer only, 200 ≤ both types, 140 ≤ x ≤ (constructed on or after dry-to-dry only area. 	40 gal/yr gal/yr l/yr er 12/9/91) e				
	olume of all perchloroethylene (vas 49.00 gallons.	(perc) purchases made in each	of the previous 12 months by this dry				

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC					only o	
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A
2.	Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No		N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	\boxtimes	N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A
	ART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC tefer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
	1. If the f acility classification is an existing small area source , no controls are required. P	rocee	ed to P	art V	•		
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.							
3. If the fa cility classification is an existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993							
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.						
Α.	Has the responsible official of all <u>existing large area & new sources</u> :					only o	
1.							
	Equipped all machines with the appropriate vent controls?	\boxtimes	Yes		No		
2.	Equipped all machines with the appropriate vent controls? Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes			No No		
							on)
3.	Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away		Yes		No		on) N/A
3.4.	Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? Measured and recorded the temperature of the outlet exhaust stream of a		Yes Yes		No No		n) N/A N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:						
1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,						
reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured						
and recorded weekly?		Yes		No		N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber,						
if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A
a) Is the same concentration coupl to on loss than 100 ppm?		Vac		Ma		NT/A
a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No	Ш	N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring						
perc concentrations at least 8 duct diameters downstream of any bend,						
contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	П	Yes		No		N/A
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual		3 7		NT.		NT/A
ሀ 1 <u>ነ</u> 1.ስ			1 1	No	1 1	N/A
condenser coils?		Yes			_	
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes	_	No		N/A
	_		_			N/A
	_		_			N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		No		
	_	Yes	(check	No	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		No	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes	(check ox for e	No	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\textbf{\text{\tint{\text{\tint{\text{\tint{\text{\text{\text{\tin}\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\tex{\tex	Yes	(check ox for e	No Z ach q	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\textbf{\text{\tint{\text{\tint{\text{\tint{\text{\text{\text{\tin}\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\tex{\tex	Yes bo Yes	(check ox for e	No Z ach q	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times\)	Yes bo Yes	(check	No Z ach q	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times\)	yes bo Yes Yes	(check	No ach q No	only o	ne n)
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times \)	yes bo Yes Yes	(check	No ach q No	only o uestio	ne n)
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	\Bigs	yes Yes Yes Yes	(check ox for e	No ach q No No	only o uestio	ne n) N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	\(\times \)	Yes Yes Yes Yes Yes	(check	No ach q No No No	only o uestio	ne n) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Is calibration data maintained for applicable direct reading instruments? 5. Is exhaust duct monitoring data on perc concentrations maintained?	\(\times \)	yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No ach q No No No No No	only o uestio	ne n) N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	\Bar \Ba	Yes Yes Yes Yes Yes Yes Yes Yes	(check bx for e	No Ach q No No No No No No No No	only o	ne n) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		yes Yes Yes Yes Yes Yes Yes Yes	(check box for each of the control o	No Ach q No	only o uestio	ne n) N/A N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	(check box for each of the control o	No Ach q No No No No No No No No	only o uestio	ne n) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one		
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)		
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used					
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to					
	the manufacturer's instructions (manual was available and RO could demonstrate					
	procedure) ?	Yes	☐ No			
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer					
	operated according to EPA Method 21 ?	Yes	☐ No	N/A		
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of					
	each component interface where leakage could occur and moving it slowly along					
	the interface periphery? \boxtimes	Yes	☐ No			
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or					
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per					
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A		
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations					
	of PCE of 25 parts per million by volume (based on documented specifications) and					
	indicating a concentration of 25 parts per million by volume or greater by emitting					
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A		
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	le the		
	system is in operation (§63.322(k))?					
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	ection	of perceptib	le leaks)		
	b) Door gaskets and seating Yes No N/A h) Stills X		 No No No No No No	N/AN/AN/AN/AN/AN/A		
8.	Are the following dry cleaning system components inspected $\underline{monthly}$ for $\underline{vapor\ leaks}$ using a halogen $\underline{monthly}$ for $\underline{monthly}$ f	enated	hydrocarbo	on detector		
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraph of the system)	raph sl	hall satisfy th	ie		
	requirements to conduct an inspection for perceptible leaks under $\S63.322(k)$ or (l))					
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes NO N/A N/A N/A Yes Yes Yes NO N/A Yes	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A		

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)						
9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other Explain other:						
Jessica Lopez	10-10-2012					
Inspector's Name (Please Print)	Date of Inspection					
Inspector's Signature	Approximate Date of Next Inspection					

COMMENTS: EPC STAFF SPOKE WITH THE OWNER, JON TURNER. BOTH MACHINES WERE TESTED FOR LEAKS TODAY. HE WAS ADVISED THAT THE UNION PERC (MACHINE #2 LOCATED NEXT TO THE WALL TO THE FAR END STILL HAD SOME LEAKS AROUND THE FILTER COMPARTMENTS ON THE FAR LEFT. PERC MACHINE (MACHINE #1),UNION,HAD THE LEAKS FIXED.