MONIGERAL PROTECTION	
Same Mana	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



## **COMPLIANCE INSPECTION CHECKLIST**

INSPECTION TYPE: ANNUAL (INS1, RE-INSPECTION				
AIRS ID#: 1210025 DATE: <u>9-4-08</u>	ARRIVE: <u>1115</u>	DEPART: <u>1130</u>		
FACILITY NAME: M M CLEANER				
FACILITY LOCATION: 3540 US 17	7 South Suite 109			
GREEN C	OVE SPRINGS 32043			
OWNER/AUTHORIZED REPRESENTA	TIVE: MONTY LAKADAWALA	<b>PHONE:</b> (904)284-3600		
CONTACT NAME:	РНО	DNE:		
ENTITLEMENT PERIOD: 12/20/2003 (effective date)	/ 12/20/2008 (end date)			
PART I: INSPECTION COMPLIANCE	STATUS (sheet 🖉 only one hor)			
		CANT Non-COMPLIANCE		
PART II: FACILITY CLASSIFICATION (check ☑ only one box in A)	<u>N</u> - Rule 62-213.300 FAC			
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)	2. New small area son dry-to-dry only, x < transfer only, x < 20 both types, x < 140 (constructed on or a	< 140 gal/yr 00 gal/yr gal/yr		
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ transfer only, $200 \le x \le 1,800$ ga both types, $140 \le x \le 1,800$ gal/y (constructed before 12/9/91)	al/yr transfer only, $200 \leq$	$0 \le x \le 2,100 \text{ gal/yr}$ $\le x \le 1,800 \text{ gal/yr}$ $\le 1,800 \text{ gal/yr}$		
5. Ineligible for General Permit drop store/out of business/petrol facility exceeds above limits	eum			
B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 75 gallons.				

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	🛛 Yes 🗌 No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV:PROCESS VENT CONTROLS – Rule 62-213.300 FAC(Refer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a Existing small area source, no controls are required. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>				
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	juipped v	vith a ref	rigerated	
А.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		☑ only each que	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	No	□N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	No	□N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	No		

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)			
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A	
	a) Is the temperature differential equal to, or greater than $20^{\circ}$ F?	Yes No N/A	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A	

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC Does the responsible official:	(check ☑ only one box for each question)
1. Maintain receipts for perc purchased?	- Xes No
2. Maintain rolling monthly total of yearly perc consumption?	Yes No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A
5. Maintain exhaust duct monitoring data on perc concentrations?	- Yes No N/A
6. Maintain a startup/shutdown/malfunction plan?	- 🛛 Yes 🗌 No
7. Maintain deviation reports?	- Yes No N/A
a) Problem corrected?	Yes No N/A
8. Maintain a compliance plan, if applicable?	- Yes No N/A

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No		
2. Does the facility maintain a leak log?	Xes No		
<ul> <li>3. Does the responsible official check the following areas for leaks?</li> <li>a) Hose connections, fittings, couplings, and valves</li> <li>b) Door gaskets and seating</li> <li>c) Filter gaskets and seating</li> <li>d) Pumps</li> <li>e) Solvent tanks and containers</li> <li>f) Water separators</li> <li>Yes No N/A</li> </ul>	s Xes No N/A ust dampers Yes No N/A ter valves Yes No N/A		
4. Which method(s) of detection (is/are) used by the responsible official?			
a) Visual examination (condensed solvent on exterior surfaces)			
MArc Lovallo	9-4-8		
Inspector's Name (Please Print)	Date of Inspection		
	September 2009		
Inspector's Signature	Approximate Date of Next Inspection		

**COMMENTS:**