

## HALOGENATED SOLVENT DEGREASERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)		(CI)
AIRS ID#: 0990540 DATE: <u>9/25/2006</u>	ARRIVE: <u>10:00 AM</u>	DEPART: <u>11:05 AM</u>
FACILITY NAME: SOLITRON DEVICES		
<b>FACILITY LOCATION:</b> 3301 Electronics	Way	
WEST PALM BE	EACH 33407	
RESPONSIBLE OFFICIAL: SHEVACH SARA	F PHONE:	(561)848-4311
CONTACT NAME: Same	PHONE:	(
REMITTANCE YEAR: 2004 EN	TITLEMENT PERIOD: 5/22/2003 (effective date)	/ 5/22/2008 (end date)
PART I: INSPECTION COMPLIANCE STATE  IN COMPLIANCE		Non-COMPLIANCE
PART II: NOTIFICATION – Rule 62-210.300 II (check ☑ appropriate box(es))	FAC	
1. Halogenated solvent used at facility:  perchloroethylene  methylene chloride  trichloroethylene  1,1,1-trichloroethane  carbon tetrachloride  chloroform	New In-line Existing In-line	m that facility has the  21 m²
PART III: <u>CLASSIFICATION</u> – Rule 62-213.30 Indicate the machine type(s) observed at the fa		
Batch Vapor, $x \le 1.21 \text{ m}^2$	<u> </u>	atch Cold (immersion)
Batch Vapor, $x > 1.21 \text{ m}^2$	Existing In-line Ba	atch Cold (remote reservoir)

	T IV: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC . <u>Batch Vapor and In-Line Machines</u>			
	1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
	2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
	2. Does the facility maintain a necodard ratio of 0.75 of greater.	Z 1 C3		
	3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	□No	
	4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	□Yes	□No	
	5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?		□No	
	6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	r □Yes	□No	⊠N/A
	7. Does the facility have each machine equipped with:  a. a device to shut off sump heat if the solvent level drops to the heater coils?  b. a device to shut off sump heat if the vapor level rises above the height of the	⊠Yes	□No	
	vapor condenser? c. a primary condenser?	⊠Yes ⊠Yse	□N □N	
	8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	⊠Yes	□No	
B. <u>B</u>	<ol> <li>atch Cold Cleaning Machines</li> <li>Does the facility collect and store all waste solvent in closed containers?</li> <li>Does the facility use a flexible hose or flushing device only within the</li> </ol>	Yes	□No	
	freeboard area?	Yes	□No	
	3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping ceases, whichever is longer?	Yes	□No	
	4. Does the facility maintain the solvent level inside the machine at or below the fill line?	Yes	□No	
	5. Does the facility immediately clean up spills during solvent transfer?	103		
	Store wipe rags in a covered container?	Yes	□No	
	<ul><li>6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used).</li><li>7. Does the facility ensure that the machine is not exposed to drafts greater than</li></ul>	Yes	□No	□N/A
	40 m/min (132 ft/min) when the cover is open?  8. Does the facility ensure that sponges, fabrics, wood and paper products are not	Yes	□No	
	placed in the machine?	Yes	□No	
<u> </u>	9. Does the facility employ a tightly fitting cover over the solvent sump?  The cover must be closed at all times except during parts cleaning	□Yes	□No	□N/A
<u> 1</u>	10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal.	□Yes	□No	□N/A

	PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines)  Facility chose to meet requirements using:  control device combination / work practice standards ————————————————————————————————————					
		Machines, $x \le 1.21 \text{ m}^2$				
	(Select control combination)		<u>DEVICE IN USE</u>			
	1.	working mode cover  reduced room draft freeboard refrig. device	1.0 freeboard ratio -	superheated vapor superheated vapor dwell		
	9.	freeboard refrig. device carbon adsorber	carbon adsorber 1.0 freeboard ratio -	superheated vapor		
В.	_	$\underline{\text{Machines}}, x > 1.21 \text{ m}^2$				
	( Select contro					
	combination	)	<u>DEVICE IN USE</u>			
	<ol> <li>□g</li> </ol>	freeboard refrig. device 1.0 freeboard ratio	superheated vapor Superheated vapor Superheated vapor Superheated vapor Superheated vapor Feduced room draft - Feduced r	1.0 freeboard ratio  working mode cover  reduced room draft  carbon adsorber  dwell   1.0 freeboard ratio  superheated vapor		
C.	Existing In-I	Line Machines				
	(Select contro	='	<u>DEVICE IN USE</u>			
	<ol> <li>□g</li> <li>□g</li> <li>□g</li> <li>□g</li> <li>□g</li> </ol>	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -			
D.	New In-Line	Machines				
	(Select contro		<u>DEVICE IN USE</u>			
		freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber			

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC							
Has the responsible official maintained the following:							
Owner's manuals, design specifications, and other instructional							
machine and control equipment?		⊠Yes	□No				
<ol> <li>Date of installation for cleaning machine and all control device unknown, they must have a letter stating installation occurred bef</li> <li>Halogenated solvent content for each solvent used? (exempt if</li> <li>Estimates of annual solvent consumption for each machine?</li> <li>Dates of solvent additions and amounts added to each machine</li> </ol>	ore or after 11/29/93 <5% by weight)	⊠Yes ⊠Yes ⊠Yes	□No □No □No				
those using an alternative emission limit)		Yes	□No	⊠N/A			
6. Idling emissions limit tests, including values obtained during the initial performance test? (applicable only to those using an idling emissions limit) 7. All control device and parameter monitoring? (applicable only to batch vapor and			□No	⊠N/A			
in-line machines)		⊠Yes	□No	□N/A			
8. Information on remedial actions in the event of exceedances or other repairs and subsequent monitoring of affected parameters?  9. Monthly emissions calculations (applicable only to those using an alternative or idling emission limit)			□No	□N/A			
			□No	⊠N/A			
			_ □No	_ ⊠N/A			
11. Cleaning capacity calculations? (applicable only to those usin limit without a solvent-air interface)		Yes	□No	⊠N/A			
Jeffrey Dizek 9/25/2006							
Inspector's Name (Please Print)	Date of Inspection						
9/20							
Inspector's Signature Approximate Date of Next In		Inspection	1				
COMMENTS:							