

HALOGENATED SOLVENT DEGREASERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (RE-INSPEC		LAINT/DISCOVER	Y (CI)		
AIRS ID#: 0990540 DATE: <u>9/26/20</u>	<u>07</u> ARRIVI	E: <u>12:40 PM</u>	DEPART: <u>1:35 PM</u>		
FACILITY NAME: SOLITRON DE	VICES				
FACILITY LOCATION: 3301	Electronics Way				
WES	T PALM BEACH 33407				
RESPONSIBLE OFFICIAL: SHEV	ACH SARAF	PHONE:	(561)848-4311		
CONTACT NAME: Same		PHONE: (
REMITTANCE YEAR: 2006	ENTITLEMENT P	ERIOD: 5/22/2003 (effective date)	/ 5/22/2008 (end date)		
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE					
PART II: NOTIFICATION – Rule (check ☑ appropriate box(es))	62-210.300 FAC				
1. Halogenated solvent used perchloroethylene		Ing machine type(s). Batch Vapor, $x \le 1$ Batch Vapor, $x > 1$ New In-line	.21 m ²		
PART III: CLASSIFICATION – Ru	de 62-213.300 FAC				
Indicate the machine type(s) observed at the facility:					
Batch Vapor, $x \le 1.21 \text{ m}^2$ \triangleright Batch Vapor, $x > 1.21 \text{ m}^2$			Batch Cold (immersion)		

	T IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC . Batch Vapor and In-Line Machines			
	1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
	2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
	2. Does the facility maintain a needoard fatho of 0.73 of greater?	<u> </u>		
	3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	Yes	□No	
	4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	□Yes	□No	
	5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?		□No	
	6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorbe should not be by-passed, the lip exhaust shall be located above the closed machine cover	r □Yes	□No	⊠N/A
	7. Does the facility have each machine equipped with: a. a device to shut off sump heat if the solvent level drops to the heater coils? b. a device to shut off sump heat if the vapor level rises above the height of the	⊠Yes	□No	
	vapor condenser? c. a primary condenser?	⊠Yes ⊠Yse	□N □N	
	8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	⊠Yes	□No	
В. <u>В</u>	1. Does the facility collect and store all waste solvent in closed containers?	□Yes	□No	
	 Does the facility use a flexible hose or flushing device only within the freeboard area? Does the facility drain cleaned parts for 15 seconds or longer or until dripping ceases, whichever is longer? Does the facility maintain the solvent level inside the machine at or below the fill line? Does the facility immediately clean up spills during solvent transfer? 		□No	
			□No	
			□No	
	Store wipe rags in a covered container? 6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used)	∐Yes	□No	□NI/A
	7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	☐Yes	□No	□N/A
	8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?	□Yes	□No	
į	<u>Remote Reservoir Type Only</u>			
,	9. Does the facility employ a tightly fitting cover over the solvent sump? The cover must be closed at all times except during parts cleaning	Yes	□No	□N/A
<u> </u>	10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal	□Yes	□No	□N/A

	PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines) Facility chose to meet requirements using: control device combination / work practice standards ————————————————————————————————————					
		Machines, $x \le 1.21 \text{ m}^2$				
	(Select contro combination)		<u>DEVICE IN USE</u>			
	1.	working mode cover reduced room draft freeboard refrig. device	1.0 freeboard ratio -	superheated vapor superheated vapor dwell		
	9.	freeboard refrig. device carbon adsorber	carbon adsorber 1.0 freeboard ratio -	superheated vapor		
В.		$\underline{\underline{\underline{Machines}}}, x > 1.21 \text{ m}^2$	_	—		
	(Select contro					
	combination)	<u>DEVICE IN USE</u>			
	 □g 	freeboard refrig. device 1.0 freeboard ratio	superheated vapor Superheated vapor Superheated vapor Superheated vapor Superheated vapor Feduced room draft - Feduced r	1.0 freeboard ratio working mode cover reduced room draft carbon adsorber dwell 1.0 freeboard ratio superheated vapor		
C.	Existing In-l	Line Machines				
	(Select contro combination)	='	<u>DEVICE IN USE</u>			
	 □g □g □g □g □g 	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -			
D.	New In-Line	Machines				
	(Select contro combination)		<u>DEVICE IN USE</u>			
		freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber			

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC			
Has the responsible official maintained the following:				
Owner's manuals, design specifications, and other instructional machine and control equipment? Date of installation for cleaning machine and all control devices	? If the exact date is	⊠Yes ⊠Yes	□No	
unknown, they must have a letter stating installation occurred before or after 11/29/93 3. Halogenated solvent content for each solvent used? (exempt if <5% by weight) 4. Estimates of annual solvent consumption for each machine? 5. Dates of solvent additions and amounts added to each machine? (applicable only to			□No □No □No	
those using an alternative emission limit)		Yes	□No	⊠N/A
6. Idling emissions limit tests, including values obtained during the initial performance test? (applicable only to those using an idling emissions limit)			□No	⊠N/A
in-line machines)	in-line machines)			N/A
 8. Information on remedial actions in the event of exceedances or other repairs and subsequent monitoring of affected parameters? 9. Monthly emissions calculations (applicable only to those using an alternative or idling emission limit)			□No	□N/A
			□No	⊠N/A
10. 3-month rolling average emissions calculations? (applicable only to those using an alternative emission limit)		Yes	□No	⊠N/A
		□Yes	□No	⊠N/A
Jeffrey Dizek	9/26/2007			
Inspector's Name (Please Print)	Date of Inspection			
	9/2008			
Inspector's Signature Approximate Date of Next		Inspection	1	
COMMENTS:				