

## HALOGENATED SOLVENT DEGREASERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D  ARMS COMPLA	ISCOVERY (CI)	
AIRS ID#: 0990540 DA	ГЕ: <u>9/28/2010</u>	ARRIVE: 1:55 P	M DEPART: 2:30 P	<u>'M</u>
FACILITY NAME: SOI	LITRON DEVICES			
FACILITY LOCATION	: 3301 ELECTRON	ICS WAY		
	WEST PALM BEA	ACH 33407		
OWNER/AUTHORIZED Email: CONTACT NAME: AD Email: ENTITLEMENT PERIC	RTHUR LAPLANTE	/2013	PHONE: (561)848-4311 Mobile: PHONE: (561)848-4311 Mobile:	
PART I: INSPECTION  IN COMPLIANCE	<u></u>	S (check only one box	) NIFICANT Non-COMPLIANCE	3
perchloroet methylene o trichloroeth 1,1,1-trichlo carbon tetra		2. Indication on not following maching Batch V Batch V New In-Existing	ification form that facility has the ne type(s). apor, $x \le 1.21 \text{ m}^2$	
PART III: <u>CLASSIFIC</u>	ATION – Rule 62-213.300 e type(s) observed at the fac	FAC		
Batch Vapor, $x \le$ Batch Vapor, $x >$		New In-line	Batch Cold (immersion Batch Cold (remote rese	_

	TTIV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC  Batch Vapor and In-Line Machines			
	Tupor unu m Eme Muemmes			
	1. Does the facility maintain an idling and downtime mode cover that is readily opened and			
	closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
	with reduced draft according to Part II, Section (3)(c)0.0 of the permit notification?	∐ i es	Пио	
	2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
	3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	□No	
	4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	□Yes	□No	
	5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	□Yes	□No	
	6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	Yes	□No	⊠N/A
	onound not be by pussed, and up summust summ be received above and stored maximis eaver.			
	7. Does the facility have each machine equipped with: a. a device to shut off sump heat if the solvent level drops to the heater coils?	⊠Yes	□No	
	b. a device to shut off sump heat if the vapor level rises above the height of the vapor condenser?	⊠Yes	□N	
	c. a primary condenser?	ĭ Y se	□N	
	8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	⊠Yes	□No	
B. F	Batch Cold Cleaning Machines			
	1. Does the facility collect and store all waste solvent in closed containers?	Yes	□No	
<i>D</i> . <u>D</u>	2. Does the facility use a flexible hose or flushing device only within the freeboard area?	□Yes	□N <sub>2</sub>	
	3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping		□No	
	ceases, whichever is longer?	Yes	□No	
	4. Does the facility maintain the solvent level inside the machine at or below the fill line?		— □N1.	
	5. Does the facility immediately clean up spills during solvent transfer?	∐Yes	□No	
	Store wipe rags in a covered container?	Yes	□No	
	6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used)	□Yes	□No	□N/A
	7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	□Yes	□No	
	8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u>			
	placed in the machine?	Yes	□No	
;	Remote Reservoir Type Only  9. Does the facility employ a tightly fitting cover over the solvent sump?			
	The cover must be closed at all times except during parts cleaning.	Yes	□No	□N/A
	<u>Immersion Type Only</u>			
	10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry			
	and removal	□Yes	□No	□N/A

	PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines)  Facility chose to meet requirements using:  control device combination / work practice standards				
A.	Batch Vapor	$\frac{1}{2}$ Machines, $x \le 1.21 \text{ m}^2$			
	(Select contro combination)		<u>DEVICE IN USE</u>		
	1.	working mode cover  reduced room draft freeboard refrig. device	1.0 freeboard ratio - \[ \] 1.0 freeboard ratio - \[ \] 1.0 freeboard ratio - \[ \] superheated vapor \[ \] working mode cover \[ \] reduced room draft \[ \] 1.0 freeboard ratio - \[ \] dwell \[ \]	superheated vapor superheated vapor dwell	
	9.	freeboard refrig. device carbon adsorber	carbon adsorber 1.0 freeboard ratio -	superheated vapor	
В.		$\frac{1}{2} \frac{\text{Machines}}{\text{Machines}}, x > 1.21 \text{ m}^2$			
٠.	( Select control	<del>-</del>			
	combination	<del></del> '	<u>DEVICE IN USE</u>		
	1. ☐g 2. ☐g 3. ☐g 4. ☐g 5. ☐g 6. ☐g 7. ☐g	freeboard refrig. device freeboard ratio	superheated vapor Superheated vapor Superheated vapor Superheated vapor Superheated vapor Feduced room draft - Feduced room draft - Feduced room draft - Superheated vapor Feduced room draft Feduced r	1.0 freeboard ratio   working mode cover   reduced room draft   carbon adsorber   dwell    1.0 freeboard ratio   superheated vapor	
C.	Existing In-l	Line Machines			
	(Select contro combination)		<u>DEVICE IN USE</u>		
	<ol> <li>□g</li> <li>□g</li> <li>□g</li> <li>□g</li> <li>□g</li> </ol>	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -		
D.	New In-Line	Machines			
	(Select contro combination)		<u>DEVICE IN USE</u>		
		freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber		

PART VI: <u>RECORDKEEPING</u> <u>REQUIREMENTS</u> – Rule 62-213.300(3) FAC						
Has the responsible official maintained the following:						
Owner's manuals, design specifications, and other instructional materia machine and control equipment?		⊠Yes	□No			
<ol> <li>Date of installation for cleaning machine and all control devices? If the exact date is unknown, they must have a letter stating installation occurred before or after 11/29/93</li> <li>Halogenated solvent content for each solvent used? (exempt if &lt;5% by weight)</li> <li>Estimates of annual solvent consumption for each machine?</li></ol>			□No □No □No			
5. Dates of solvent additions and amounts added to each machine? (applied those using an alternative emission limit)		Yes	□No	⊠N/A		
<ul> <li>6. Idling emissions limit tests, including values obtained during the initial performance test? (applicable only to those using an idling emissions limit)</li></ul>			□No	⊠N/A		
			□No	□N/A		
			□No	□N/A		
			□No	⊠N/A		
10. 3-month rolling average emissions calculations? (applicable only to those using an alternative emission limit)		□Yes	□No	⊠N/A		
11. Cleaning capacity calculations? (applicable only to those using an altelement without a solvent-air interface)		□Yes	□No	⊠N/A		
Jeffrey Dizek 9/28/2010						
Inspector's Name (Please Print)  Date of I	Inspection					
	9/2	011				
Inspector's Signature Approximate Date of Next Inspection						
COMMENTS:						