

HALOGENATED SOLVENT DEGREASERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D ARMS COMPLA	ISCOVERY (CI)		
AIRS ID#: 0990540 DATI	E: <u>9/27/12</u>	ARRIVE: 2:00 P	M DEPART: 2:5	50 PM	
FACILITY NAME: SOLI	TRON DEVICES				
FACILITY LOCATION:	3301 ELECTRONIC	CS WAY			
	WEST PALM BEA	CH 33407			
OWNER/AUTHORIZED Email: CONTACT NAME: AR' Email: ENTITLEMENT PERIOI	THUR LAPLANTE	2013	PHONE: (561)848-4311 Mobile: PHONE: (561)848-4311 Mobile:		
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE					
PART II: NOTIFICATION – Rule 62-210.300 FAC (check ☑ appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene□ trichloroethylene□ 1,1,1-trichloroethane□ carbon tetrachloride□ chloroform□ Batch Cold□					
PART III: CLASSIFICAT Indicate the machine to Batch Vapor, $x \le 1$ Batch Vapor, $x > 1$	ype(s) observed at the faci .21 m ² \boxtimes		Batch Cold (immers	•	

PART IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC A. Batch Vapor and In-Line Machines			
1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	□No	
4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	□Yes	□No	
5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?		□No	
6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	Yes	□No	⊠N/A
7. Does the facility have each machine equipped with: a. a device to shut off sump heat if the solvent level drops to the heater coils? b. a device to shut off sump heat if the vapor level rises above the height of the	⊠Yes	□No	
vapor condenser? c. a primary condenser?	⊠Yes ⊠Yse	□N □N	
8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	⊠Yes	□No	
Batch Cold Cleaning Machines Does the facility collect and store all waste solvent in closed containers? Does the facility use a flexible hose or flushing device only within the	□Yes	□No	
freeboard area?	Yes	□No	
3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping ceases, whichever is longer?	Yes	□No	
4. Does the facility maintain the solvent level inside the machine at or below the fill line?	□Yes	□No	
5. Does the facility immediately clean up spills during solvent transfer? Store wipe rags in a covered container?	□Yes	□No	
6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used)	□Yes	□No	□N/A
7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	□Yes	□No	
8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?	□Yes	□No	
 Remote Reservoir Type Only 9. Does the facility employ a tightly fitting cover over the solvent sump? The cover must be closed at all times except during parts cleaning	□Yes	□No	□N/A
10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal.	□Yes	□No	□N/A

PA	Facility chose control d	e to meet requirements using device combination / work pra	g: actice standards	applicable to batch cold cleaning machines)	\boxtimes	
	alternative solvent emission limit (proceed to Part VI)idling emission limit / work practice standards (proceed to Part VI)					
Α.	Batch Vapor	Machines, $x \le 1.21 \text{ m}^2$				
	(Select control combination)		DEVICE IN USE			
	3. ⊠g 4. □g 5. ⊠g 6. □g 7. □g 8. □g 9. □g	working mode cover	1.0 freeboard ratio -	superheated vapor superheated vapor dwell		
	10. □g	carbon adsorber	1.0 freeboard ratio -	superheated vapor		
В.	Batch Vapor	Machines, $x > 1.21 \text{ m}^2$				
	(Select contro combination)		<u>DEVICE IN USE</u>			
	2.	freeboard refrig. device 1.0 freeboard ratio	superheated vapor superheated vapor superheated vapor superheated vapor reduced room draft - reduced room draft - reduced room draft -	1.0 freeboard ratio working mode cover reduced room draft dwell 1.0 freeboard ratio superheated vapor		
C.	Existing In-L	Line Machines				
	(Select control combination)	Ĺ	<u>DEVICE</u> <u>IN</u> <u>USE</u>			
	2.	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -			
D.	New In-Line	<u>Machines</u>				
	(Select control combination)		<u>DEVICE IN USE</u>			
		freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber			

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213	3.300(3) FAC			
Has the responsible official maintained the following:				
the responsible different manifestation and rollowing.				
Owner's manuals, design specifications, and other instruct machine and control equipment?	⊠Yes	□No		
 2. Date of installation for cleaning machine and all control devices? If the exact date is unknown, they must have a letter stating installation occurred before or after 11/29/93 3. Halogenated solvent content for each solvent used? (exempt if <5% by weight) 4. Estimates of annual solvent consumption for each machine?			□No □No □No	
	5. Dates of solvent additions and amounts added to each machine? (applicable only to those using an alternative emission limit)			⊠N/A
 Idling emissions limit tests, including values obtained during the initial performance test? (applicable only to those using an idling emissions limit)			□No	⊠N/A
			□No	□N/A
			□No	□N/A
			□No	⊠N/A
			□No	⊠N/A
11. Cleaning capacity calculations? (applicable only to those using an alternative emission limit without a solvent-air interface)			□No	⊠N/A
Jeffrey Dizek	9/2	7/2012		
Inspector's Name (Please Print)	Date of Inspection			
9/2				
Inspector's Signature Approximate Date of Next Inspection				
COMMENTS:				