

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

<u> </u>	NNUAL (INS1, INS2)	COMPLAINT/D	DISCOVERY (CI)
AIRS ID#: 0310449 DATE	: <u>4/6/11</u>	ARRIVE:	DEPART:
FACILITY NAME: SAGE	DRY CLEANERS		
FACILITY LOCATION:	400 W US 90		
	BALDWIN 32234		
OWNER/AUTHORIZED R Email: CONTACT NAME: Email: ENTITLEMENT PERIOD:	REPRESENTATIVE: MAR : 8/10/2006 / 8/10/2011 (effective date) (end date)	RY SAGE	PHONE: (904)266-4822 Mobile: PHONE: Mobile:
PART I: INSPECTION CO IN COMPLIANCE	OMPLIANCE STATUS (ch	. —	GNIFICANT Non-COMPLIANCE
PART II: FACILITY CLA (check ☑ only	ASSIFICATION - Rule 62- y one box in A)	213.300 FAC	
transfer only, 200 both types, 140 < (constructed befo 5. Ineligible for (x < 140 gal/yr $(200 gal/yr)$ $(40 gal/yr)$ $(40$	transfer only, both types, x (constructed of types). 4. New large ar dry-to-dry on transfer only, both types, 14	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91)
B. The sum of the volucleaning facility was	-	(perc) purchases made	e in each of the previous 12 months by this dry

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	-	,	check 🗹 x for each o	only one question)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	☐ No	N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes	☐ No	□ N/A
3. Are all machine doors kept closed and secured except during loading/unloading?		Yes	☐ No	
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes	☐ No	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	☐ No	⊠ N/A
Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	. 🗆	Yes	☐ No	N/A
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form) 1. If the f acility classification is an existing small area source, no controls are required. If	Proce	ed to P	art V.	
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped condenser. Complete section A. below.	with	a refrig	gerated	
3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equiverefrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Compust have been installed prior to September 22, 1993</i>				
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriş	gerated	
A. Has the responsible official of all existing large area & new sources:			check 🗹 x for each o	-
1. Equipped all machines with the appropriate vent controls?	. 🗆	Yes	☐ No	
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes	☐ No	N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes	☐ No	N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes	☐ No	N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes	□ No	N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes	☐ No	

РΔ	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,						
	reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured						
	and recorded weekly?		Yes		No		N/A
	a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly						
	at the end of the final drying cycle while the machine is venting to the adsorber,		X 7 .		N.T		37/4
	if machines are equipped exclusively with a carbon adsorber?	Ш	Yes	Ш	No	Ш	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No	\boxtimes	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring						
H	perc concentrations at least 8 duct diameters downstream of any bend,						
	contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	П	Yes		No	П	N/A
							- "
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes		No		N/A
	condenser cons:	Ш	168	Ш	INO	Ш	IN/ /1
							1
	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
6.							
6.	Is airflow routed to the carbon adsorber (if used) at all times?		(1	check x for e	V (only o	one
6. PA	RT V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(o bo	check x for e	☑ ceach qu	-	one
6. PA	Are receipts maintained for all perc purchased?		(u bo	check x for e	☑ ceach qu	-	one
6. PA 1. 2.	Are receipts maintained for all perc purchased? Are rolling monthly total s of yearly perc consumption maintained?		(o bo	check x for e	☑ ceach qu	-	one
1. 2. 3.	Are receipts maintained for all perc purchased?		(u bo	check x for e	☑ ceach qu	-	one
1. 2. 3.	Are receipts maintained for all perc purchased? Are rolling monthly total s of yearly perc consumption maintained?		(u bo	check x for e	☑ ceach qu	-	one
1. 2. 3.	Are receipts maintained for all perc purchased?		yes Yes	check x for e	oach qu No No	uestio	one on)
1. 2. 3.	Are receipts maintained for all perc purchased? ————————————————————————————————————		yes Yes Yes	check x for e	orach que No No No	westio	one on) N/A
1. 2. 3. 4.	Are receipts maintained for all perc purchased?		Yes Yes Yes	check x for e	each qu No No No	westio	one nn) N/A N/A N/A
1. 2. 3. 4. 5.	Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes	check x for e	No No No No No No No No No	westio	one on) N/A N/A
1. 2. 3. 4. 5. 6.	Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	check x for e	No	westion with the state of the s	nne nn) N/A N/A N/A
1. 2. 3. 4. 5. 6. 7.	Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes	check x for e	No	westion with the control of the cont	nne nn) N/A N/A N/A N/A
6. 1. 2. 3. 4. 5. 6. 7.	Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	check x for e	No	westion	nne nn) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?		ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) whi	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	ection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Yes N/A j	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarb	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph sh	hall satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Yes N/A j	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A

e 62-213.300 FAC (continued)	
as required?	
On-site observation other	
4/6/2011	
Date of Inspection	
Date of Inspection 2012	
а	as required? On-site observation other

repaired. Will check periodicaly.