

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<u>INSPECTION</u> <u>TYPE</u> : AN	NUAL (INS1, INS2)	COMPLAINT/DIS	COVERY (CI)		
RE	-INSPECTION (FUI)	ARMS COMPLAIN	NT NO:		
AIRS ID#: 0951192 DATE: <u>02/16/07</u> ARRIVE: <u>11:55</u> DEPART: <u>12:30</u>					
FACILITY NAME: TOWN 'N' COUNTRY CLEANERS					
FACILITY LOCATION: 6470 Raleigh Street					
	ORLANDO 32835				
RESPONSIBLE OFFICIAL	: CLEVELAND CHARRA	AN P	<b>HONE:</b> (407)578-5282		
CONTACT NAME:		P	PHONE:		
REMITTANCE YEAR: 200	)5 ENTITL	LEMENT PERIOD: 1/4 (effe	/2007 / 1/4/2012 ctive date) (end date)		
PART I: INSPECTION CO	<u></u>				
☑ IN COMPLIANCE	MINOR Non-COM	PLIANCE  SIGNI	FICANT Non-COMPLIANC	E	
PART II: FACILITY CLAST (check only on		213.300 FAC			
A. 1. Existing small are dry-to-dry only, x transfer only, x < both types, x < 14 (constructed before	< 140 gal/yr 200 gal/yr 0 gal/yr re 12/9/91)	2. New small area dry-to-dry only, transfer only, x - both types, x < 1 (constructed on	x < 140 gal/yr < 200 gal/yr   40 gal/yr   or after 12/9/91)		
	$40 \le x \le 2,100 \text{ gal/yr}$ $\le x \le 1,800 \text{ gal/yr}$ $x \le 1,800 \text{ gal/yr}$	transfer only, 20 both types, 140	source		
5. Ineligible for Ger drop store/out of b facility exceeds ab	ousiness/petroleum				
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 120 gallons.					

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box						
Do	es the responsible official of the dry cleaning facility:	for each question)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A				
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A				
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No				
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	□Yes □ No ☑ N/A				
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No ☑ N/A				
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	ired. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>					
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993					
	4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.					
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :	(check ☑ only one box for each question)				
1.	Equipped all machines with the appropriate vent controls?	Yes No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- Yes No N/A				
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- Yes No N/A				
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- Yes No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes No N/A				
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	□Yes □No				

PA	PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)					
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)				
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No				
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- ∐Yes □ No ⊠N/A				
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	☐Yes ☐ No ☒ N/A				
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	∐Yes □ No ⊠ N/A				
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A				
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A				
5	Equip transfer machines (dryers, reclaimers, and washers) with individual					
٥.	condenser coils?	- ∐Yes ☐ No ☒ N/A				
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A				
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for						
Do	es the responsible official:	each question)				
1.	Maintain receipts for perc purchased?	Yes No				
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No				
3.	Maintain leak detection inspection and repair reports for the following:					
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No No N/A				
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No     N/A				
4.		☐ Yes ☐ No ☒ N/A				
5.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☐ N/A				
	Maintain calibration data? (for applicable direct reading instruments)  Maintain exhaust duct monitoring data on perc concentrations?					
6.		☐ Yes ☐ No    N/A				
	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No				
	Maintain exhaust duct monitoring data on perc concentrations?  Maintain a startup/shutdown/malfunction plan?	<ul> <li>Yes □ No □ N/A</li> <li>Yes □ No □ N/A</li> <li>Yes □ No □ N/A</li> </ul>				

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?					
2. Does the facility maintain a leak log?					
3. Does the responsible official check the following areas for leaks?  a) Hose connections, fittings,     couplings, and valves	ers				
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————					
Darrell Lobin	02/16/2007				
Inspector's Name (Please Print) Date	e of Inspection				
02/16/20	008				
Inspector's Signature Appr	roximate Date of Next Inspection				
COMMENTS: ASOC submitted on 02/21/2007. Facility in compliance at time of inspection.					