WHERE PROTECTION	
State Deserve	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:       ANNUAL (INS1, INS2)       COMPLAINT/DISCOVERY (CI)         RE-INSPECTION (FUI)       ARMS COMPLAINT NO:
AIRS ID#: 0951192 DATE: 2/9/2011 ARRIVE: 11:00AM DEPART: 13:35AM
FACILITY NAME: TOWN 'N' COUNTRY CLEANERS
FACILITY LOCATION: 6470 Raleigh Street
ORLANDO 32835
OWNER/AUTHORIZED REPRESENTATIVE:       CLEVELAND CHARRAN       PHONE:       (407)578-5282         Email:       Mobile:         CONTACT NAME:       PHONE:         Email:       Mobile:         ENTITLEMENT PERIOD:       1/4/2007 / 1/4/2012         (effective date)       (end date)
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)         ☑ IN COMPLIANCE       ☐ MINOR Non-COMPLIANCE         ☑ SIGNIFICANT Non-COMPLIANCE
PART II:       FACILITY CLASSIFICATION (check ☑ only one box in A)       - Rule 62-213.300 FAC         A. 1.       Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)       2.       New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)       2.       New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)       2.       New small area source dry-to-dry only, x < 140 gal/yr (constructed on or after 12/9/91)         3.       Existing large area source dry-to-dry only, 140 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91)       2.       New small area source dry-to-dry only, x < 140 gal/yr (constructed before 12/9/91)         5.       Ineligible for General Permit d rop store/out of business/petroleum / facility exceeds above limits       New large area on or after 12/9/91)         B. The sum of the volume of all perchloroethylene (perc) purchases made in each of the previous 12 months by this dry

cleaning facility was 65.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC		`	check x for e		only c questio	
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	$\boxtimes$	Yes		No		N/A
2. Are all perc. containers leak free ?	$\boxtimes$	Yes		No		N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	$\boxtimes$	Yes		No		
<ol> <li>Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?</li> </ol>		Yes		No	$\square$	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	$\boxtimes$	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No		N/A
PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC						

(Refer to Part II-A.1.-4. Classification: page <u>1</u> of <u>4</u>, this form)

1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.

2. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the fa cility classification is an **existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber . **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993* 

4. If the facility classification is a <u>new large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

A.	Has the responsible official of all <u>existing large area &amp; new sources</u> :	`	check 🗹 x for each c	only one [uestion)
1.	Equipped all machines with the appropriate vent controls?	Yes	🗌 No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	🗌 No	N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	🗌 No	N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	🗌 No	N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded $45^{\circ}$ F?	Yes	🗌 No	N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	🗌 No	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
<b>B.</b> 1.	<b>For all existing large or new large area sources:</b> Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	Yes	D No	□ N/A
	a) Is the temperature differential equal to, or greater than $20^{\circ}$ F?	Yes	🗌 No	N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	□ N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend,			
	contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	□ N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		`	check ☑ x for each c	only one [uestion)
1.	Are receipts maintained for all perc purchased?	$\boxtimes$	Yes	D No	
2.	Are rolling monthly total s of yearly perc consumption maintained ?	$\boxtimes$	Yes	🗌 No	
3.	Are leak detection inspection and repair reports maintained for the following:				
	a) Of any leaks repaired w/in 24 hrs? or;		Yes	🗌 No	N/A
	b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?		Yes	🗌 No	N/A
4.	Is calibration data maintained for applicable direct reading instruments?		Yes	🗌 No	N/A
5.	Is exhaust duct monitoring data on perc concentrations maintained?		Yes	🗌 No	N/A
6.	Is a startup/shutdown/malfunction plan maintained for each machine?	$\boxtimes$	Yes	🗌 No	
7.	Are deviation reports maintained?		Yes	🗌 No	N/A
	a) Problem corrected?		Yes	🗌 No	N/A
8.	Is a compliance plan maintained , if applicable?		Yes	🗌 No	N/A

P	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check 🗹 🛛	only one
1.	What type of leak detection equipment is used to detect leaks?	box for each qu	estion)
	Halogenated hydrocarbon detector PCE gas analyzer None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ? 🖂	Yes 🗌 No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes 🗌 No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery?	Yes 🗌 No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes 🗌 No	N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes?	Yes 🗌 No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or touch) while	the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perceptible	leaks)
	b) Door gaskets and seating Xes No N/A h) Stills Xes No		] N/A ] N/A ] N/A ] N/A ] N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated hydrocarbon	detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph shall satisfy the	
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))		
	b) Door gaskets and seating       Xes       No       N/A       N)       Stills         c) Filter gaskets and seating       Xes       No       N/A       i)       Exhaust dampers	Yes   No   Yes   No   Yes   No   Yes   No   Yes   No	] N/A ] N/A ] N/A ] N/A ] N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)							
<ul> <li>9. What evidence suggests that leak checks are performed as required?</li> <li></li></ul>							
Assefa Hailemariam	2/9/2011						
·····							
Inspector's Name (Please Print)	Date of Inspection						
	~2/2012						
Inspector's Signature	Approximate Date of Next Inspection						
date. The dry cleaning machine was not operating at the time	with their air permit for the inspection that was conducte of the inspection. A halogen leak detector is being used	by the facility					

to comply with the EPA requirement. The perchloroethylene hazardous waste container was labeled, but no start date was documented on the label. The owner told me that have not replace any new equipment this past year. The container for the lint did not have a lid. During the inspection, no perc odor was detected. The inspector checked the machine for leaks using EPD's halogen leak detector. No perchloroethylene vapors were found.