

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI) ARMS COMPLAINT NO:						
AIRS ID#: 1010368 DATE: 10/04/2010 FACILITY NAME: LIBERTY CLEANERS	ARRIVE: <u>1145</u> DEPART: <u>1230</u>						
FACILITY LOCATION: 2412 Land O'Lakes Blvd LAND O'LAKES 34639 OWNER/AUTHORIZED REPRESENTATIVE: DILIP Email: dpatel58@hotmail.com CONTACT NAME: DILIP PATEL Email: patel58@hotmail.com ENTITLEMENT PERIOD: 11/6/2008 / 11/6/2013 (effective date) (end date)							
PART I: INSPECTION COMPLIANCE STATUS (check ✓ only one box) ☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
(check ✓ only one box in A) A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit d rop store/out of business/petroleum / facility exceeds above limits	13.300 FAC 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed on or after 12/9/91)						
B. The sum of the volume of all perchloroethylene (p cleaning facility was 60.00 gallons.	perc) purchases made in each of the previous 12 months by this dry						

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			check 🗹	only one n question)		
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?		Yes	□ No	N/A		
2. Are all perc. containers leak free ?		Yes		N/A		
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes	☐ No)		
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		o N/A		
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	□ No	o 🛭 N/A		
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes	□ No	N/A		
PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
1. If the f acility classification is an existing small area source , no controls are required. P	roce	ed to P	Part V.			
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
3. If the fa cility classification is an existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993						
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriș	gerated			
A. Has the responsible official of all existing large area & new sources:			check 🗹	only one n question)		
1. Equipped all machines with the appropriate vent controls?		Yes)		
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes	□ No	N/A		
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes		N/A		
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes		N/A		
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes		N/A		
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes)		

DADT IV. DDOCESS VENT CONTDOLS Dule 62 212 200 EAC (continued)						
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,						
reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2. Is the weeken exhaus t temperature at the condenses inlet and outlet messaged						
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes	П	No	\boxtimes	N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
	Ш	105	Ш	1,0		1,711
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber,						
if machines are equipped exclusively with a carbon adsorber?	- 🖂	Yes	П	No	\bowtie	N/A
			_			
a) Is the perc concentration equal to, or less than 100 ppm?	. Ц	Yes	Ш	No	\bowtie	N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring						
perc concentrations at least 8 duct diameters downstream of any bend,						
contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	П	No	\boxtimes	N/A
	Ш	105	Ш	1,0		1,711
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual	_	X 7		No	\square	NT/A
				No	\times	N/A
condenser coils?	- Ц	Yes	Ш		_	
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes	_	No		N/A
	_		_			N/A
	_		_		\boxtimes	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		No		
	_	Yes	Ccheck	No V	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	- 🗆	Yes		No V	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?	- 🗆	Yes	(check ox for e	No V	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	- -	Yes	(check ox for e	No Z each q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?	- -	Yes (bo	(check ox for e	No each q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?	_ -	Yes (bo	(check ox for e	No each q	only o	one
6. Is airflow routed to the carbon adsorber (if used) at all times?	_ -	Yes Output Output Yes Yes Yes	(check ox for e	No each q No	only o	one on)
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes Output Output Yes Yes Yes	(check ox for e	No each q No	only o	one on)
6. Is airflow routed to the carbon adsorber (if used) at all times?	-	Yes (bo Yes Yes	(check ox for e	No Pach q No No No	only o	one on)
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	-	Yes Yes Yes Yes Yes	(check ox for e	No each q No No No	only of uestion	one on) N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	-	Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No Peach q No No No No No	only of uestion	one on) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	-	Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No Peach q No No No No No No No No	only of uestion	one on) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Is calibration data maintained for applicable direct reading instruments? 5. Is exhaust duct monitoring data on perc concentrations maintained? 6. Is a startup/shutdown/malfunction plan maintained for each machine? 7. Are deviation reports maintained?		Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No	only of uestion	nne on) N/A N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No Peach q No No No No No No No No	only of uestion	one on) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check ☑ only one
1.	What type of leak detection equipment is used to detect leaks?	box for each question)
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to	
	the manufacturer's instructions (manual was available and RO could demonstrate	
	procedure) ?	Yes No
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer	
	operated according to EPA Method 21 ?	Yes No No N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of	
	each component interface where leakage could occur and moving it slowly along	
	the interface periphery?	Yes No
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or	
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per	
	million by volume (based on documented specifications) ?	Yes No No N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations	
	of PCE of 25 parts per million by volume (based on documented specifications) and	
	indicating a concentration of 25 parts per million by volume or greater by emitting	
	an audible or visual signal that varies as the concentration changes? 🖂	Yes No N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or touch) while the
	system is in operation (§63.322(k))?	
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perceptible leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y	
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated hydrocarbon detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph shall satisfy the
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))	
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes Yes No N/A N/A N/A N/A N/A N/A Yes Yes	Yes

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)						
9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other Explain other:						
Joseph V. Panetta	10/4/2010					
Inspector's Name (Please Print)	Date of Inspection					
Inspector's Signature	Approximate Date of Next Inspection					
COMMENTS: Visited facility and spoke with R/O listed in the Gave R/O copy of GPCI lite facility screen highlighting the expirit copy of blank (just w/ heading that print's out) inspection report, acknowledgement letter from Tallahassee. Completed inspection with checklist.						