

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE</b> :	ANNUAL (INS1, INS2)	COMPLAINT/DISCO	VERY (CI)				
	RE-INSPECTION (FUI)	ARMS COMPLAINT	NO:				
<b>AIRS ID#:</b> 0112429 <b>DA</b>	TE: <u>5/27/10</u>	ARRIVE: <u>1440</u>	<b>DEPART:</b> <u>1600</u>				
FACILITY NAME: BARTON & MILLER CLEANERS							
FACILITY LOCATION: 2600 N DIXIE HWY							
WILTON MANOR 33334-3725							
OWNER/AUTHORIZE	D REPRESENTATIVE: RIC	HARD MILLER PHO	<b>ONE:</b> (954)566-4314				
CONTACT NAME:		РНС	ONE:				
ENTITLEMENT PERIOD: 9/27/2009 / 9/27/2014 (effective date) (end date)							
PART I: <u>INSPECTION</u>	COMPLIANCE STATUS (ch	heck 🗹 only one box)					
☐ IN COMPLIAN	CE MINOR Non-COME	PLIANCE SIGNIFIC	CANT Non-COMPLIANCE				
	CLASSIFICATION - Rule 62-2 ly one box in A)	13.300 FAC					
transfer only, both types, x	ly, x < 140 gal/yr x < 200 gal/yr	2. New small area so dry-to-dry only, x < transfer only, x < 2 both types, x < 140 (constructed on or a	< 140 gal/yr 00 gal/yr gal/yr				
transfer only, both types, 14	e area source $\Box$ ly, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91)$	4. New large area so dry-to-dry only, 14 transfer only, 200 \( \) both types, 140 \( \) x (constructed on or a	$0 \le x \le 2,100 \text{ gal/yr}$ $\le x \le 1,800 \text{ gal/yr}$ $\le 1,800 \text{ gal/yr}$				
drop store/ou	t of business/petroleum ds above limits						
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 220 gallons.							

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check <b>☑</b> only one box					
Do	es the responsible official of the dry cleaning facility:	for ea	ch questi	on)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A			
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A			
3.	Close and secure machine doors except during loading/unloading?	X Yes	☐ No				
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes	☐ No	□ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes	□No	⊠ N/A			
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)						
	1. If the facility classification is a <b>Existing small</b> area source, no controls are requi	ired. <b>Pro</b>	ceed to l	Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>						
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993						
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated			
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :		only each ques	one box for			
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	□No	□N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	□No	□N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	□No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- \( \sum Yes	□No	□N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No				

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)						
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)				
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No				
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?					
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	☐Yes ☐ No ☒ N/A				
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A				
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A				
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No ☑ N/A				
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- □Yes □ No □ N/A				
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A				
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC						
Do	pes the responsible official:	(check ☑ only one box for each question)				
1.	Maintain receipts for perc purchased?	Yes No				
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No				
3.	Maintain leak detection inspection and repair reports for the following:					
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A				
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No   ☑ N/A				
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☐ N/A				
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☒ N/A				
	Maintain a startup/shutdown/malfunction plan?					
7.	Maintain deviation reports?					
	a) Problem corrected?					
8.	Maintain a compliance plan, if applicable?	☐ Yes ☐ No     N/A				

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?					
2. Does the facility maintain a leak log? 🖂 Yes 🗌 No					
d) Pumps \overline{\					
4. Which method(s) of detection (is/are) used by the responsible official	1?				
a) Visual examination (condensed solvent on exterior surfaces)					
Art Pennetta	5/27/10				
Inspector's Name (Please Print)	Date of Inspection				
	5/11				
Inspector's Signature	Approximate Date of Next Inspection				
COMMENTS:					