THERE NOTECTION	
Ser Verte	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)
AIRS ID#: 1170374 DATE: <u>5/8/08</u>	ARRIVE: <u>12:44</u> DEPART: <u>12:50</u>
FACILITY NAME: THE CLOTHES DOCTOR	
FACILITY LOCATION: 3895 Lake Emma Drive	#167
LAKE MARY 32746	
OWNER/AUTHORIZED REPRESENTATIVE: CHE	PHONE: (407)333-9347
CONTACT NAME:	PHONE:
ENTITLEMENT PERIOD: 4/25/2005 / 4/25/2010 (effective date) (end date))
PART I: <u>INSPECTION COMPLIANCE STATUS</u> (cl	
IN COMPLIANCE MINOR Non-COMI	PLIANCE SIGNIFICANT Non-COMPLIANCE
L	
PART II: FACILITY CLASSIFICATION (check ☑ only one box in A)	213.300 FAC
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)	2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)
 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit drop store/out of business/petroleum 	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)
B. The total quantity of perchloroethylene (perc) pu cleaning facility was gallons.	rchased within the preceding 12 months by this dry

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC

(Refer to Part II-A.1.-4. Classification: page <u>1</u> of <u>4</u>, this form)

1. If the facility classification is a **Existing small area source**, no controls are required. **Proceed to Part V.**

2. If the facility classification is a <u>New small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the facility classification is a **Existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993*

4. If the facility classification is a <u>New large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

A.	Has the responsible official of all <u>existing large area & new sources</u> :		☑ only each ques	one box for ation)
1.	Equipped all machines with the appropriate vent controls?	Yes	No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	No	N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	No	□N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	□Yes	No	

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)	
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A Yes No N/A
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for		
Does the responsible official:	each question)	
1. Maintain receipts for perc purchased?		
2. Maintain rolling monthly total of yearly perc consumption?	- Yes No	
3. Maintain leak detection inspection and repair reports for the following:		
a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A	
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 	Yes No N/A	
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A	
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A	
6. Maintain a startup/shutdown/malfunction plan?	Yes No	
7. Maintain deviation reports?	[] Yes [] No [] N/A	
a) Problem corrected?	Yes No N/A	
8. Maintain a compliance plan, if applicable?	[] Yes [] No [] N/A	

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC	
	(check \blacksquare only one box for
1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak	each question)
detection and repair inspection?	🗌 Yes 🗌 No

2.	Does the facility maintain a leak log? Yes No
3.	Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves Yes No N/A b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A c) Filter gaskets and seating Yes No N/A h) Stills Yes No N/A d) Pumps Yes No N/A j) Diverter valves Yes No N/A e) Solvent tanks and containers Yes No N/A k) Cartridge filter housings Yes No N/A f) Water separators Yes No N/A N/A No N/A
4.	Which method(s) of detection (is/are) used by the responsible official? a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) c) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) e) Halogen leak detector e)
**	If using direct-reading instrumentation, is the equipment:

Wanda Parker-Garvin

Inspector's Name (Please Print)

Wanda Parker Lawin

Inspector's Signature

Approximate Date of Next Inspection

5/8/08

Date of Inspection

COMMENTS: Drop off store - no perc machine or waste material on site.