

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D		(CI)			
AIRS ID#: 0710180 DAT	ΓΕ: <u>12/18/2013</u>	ARRIVE: <u>1:10 p.</u>	<u>m.</u>	DEPART: <u>1:30 p.m.</u>			
FACILITY NAME: EAGLE CLEANERS							
FACILITY LOCATION	: 13251 MCGREGOR B	LVD					
	FT MYERS 33919-59	941					
OWNER/AUTHORIZEI Email: bansariudani2(CONTACT NAME: Email: ENTITLEMENT PERIC			PHONE: Mobile: PHONE: Mobile:	(239)247-9574			
PART I: <u>INSPECTION COMPLIANCE STATUS</u> (check ☑ only one box) ☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
PART II: FACILITY CLASSIFICATION (check ☑ only one box in A) - Rule 62-213.300 FAC							
transfer only, both types, x < (constructed b 3. Existing large dry-to-dry onl transfer only, both types, 14 (constructed b 5. Ineligible for d rop store/out	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)		$\frac{1}{2}$, $\frac{1}{2}$ < $\frac{1}{$	/yr 2/9/91) = x \le 2,100 gal/yr 1,800 gal/yr 1,800 gal/yr			
	volume of all perchloroethylene was 15.00 gallons.	e (perc) purchases made	e in each of t	he previous 12 months by thi	s dry		

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC		,	check x for e		only o			
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A		
2.	Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A		
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No				
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		No		N/A		
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A		
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A		
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)								
 If the facility classification is an <u>existing small area source</u>, no controls are required. Proceed to Part V. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below. If the fa cility classification is an <u>existing large area source</u>, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 									
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.								
Α.	Has the responsible official of all <u>existing large area & new sources</u> :					only o			
1.	Equipped all machines with the appropriate vent controls?		Yes		No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes		No		N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes		No		N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes		No		N/A		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes		No		N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes		No				

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)								
B. For all existing large or new large area sources:								
Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No				
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes		No	_	N/A		
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A		
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A		
a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A		
4. Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes		No		N/A		
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual	П	Yes		No		N/A		
condenser coils?	_							
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A		
		Yes		No		N/A		
		Yes		No		N/A		
		((check	V (only o	ne		
6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC		(bo	check ox for each	☑ o	only o	ne		
6. Is airflow routed to the carbon adsorber (if used) at all times?		(bo	check	☑ (ach q	only o	ne		
6. Is airflow routed to the carbon adsorber (if used) at all times?		(bo	check	☑ o	only o	ne		
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes Yes	check	ach q No No	only o	ne n)		
6. Is airflow routed to the carbon adsorber (if used) at all times?		(bo	(check ox for each	☑ (ach q	only o	ne		
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check	nach q No No No No	only of uestion	ne n) N/A N/A		
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check lox for each	izach q ach q No No No	only ouestion	ne n) N/A		
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes	check	oach quach q	only ouestion	ne n) N/A N/A N/A		
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes	check	No	only of uestion	ne n) N/A N/A N/A		
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes	check lox for each	No No No No No No No	only ouestion	ne n) N/A N/A N/A		

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	b	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Y	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraph of the system)	raph si	hall satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Y	Yes Yes Yes Yes Yes	No No No No No No No	N/AN/AN/AN/AN/AN/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)					
9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other Explain other:					
ROBERT J. STEWART	12/18/2013				
Inspector's Name (Please Print)	Date of Inspection				
	12/2015				
Robert J. Stewart					
Inspector's Signature	Approximate Date of Next Inspection				

COMMENTS: Facility has not purchased PERC for use in the dry cleaning machine since January 2013. The dry cleaning machine has not been used for almost all of 2013. Owner stated that he has bought the cleaning facility located at 4600 Summerlin Road and is using that facility's green (non-PERC) cleaning machine to clean his clothes from this facility which he is now operating as a drop store. Owner was advised that even though he is not using the dry cleaning machine at this facility, monthly leak checks for PERC still need to be done and annotated the dry cleaning calendar or other log to document that they are being conducted.