ALE ALCO
1 Jone
FLORIDA
the first of the second second second

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY (CI)	
AIRS ID#: 0990569 DATE: <u>12/18/2007</u>	ARRIVE: <u>11:25 AM</u> DEPART: <u>11:55 AM</u>	
FACILITY NAME: LA SAND CLEANERS		
FACILITY LOCATION: 4789 N Congress Ave	enue	
BOYNTON BEACH	33426	
OWNER/AUTHORIZED REPRESENTATIVE: C	CARLOS MONTECHIARI PHONE: (561)968-7303	
CONTACT NAME: Same	PHONE: (
ENTITLEMENT PERIOD: 11/5/2006 / 11/5/20 (effective date) (end date)	-	
PART I: INSPECTION COMPLIANCE STATUS	$(\text{check } \overline{\mathbf{M}} \text{ only one hox})$	
IN COMPLIANCE MINOR Non-CO		
PART II: FACILITY CLASSIFICATION - Rule 62 (check 🗹 only one box in A)	2-213.300 FAC	
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)	2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)	
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)	
 5. Ineligible for General Permit		
cleaning facility was 75 gallons.		

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes □ No ⊠ N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)			
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.		
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>		
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	uipped with a refrigerated	
А.	Has the responsible official of all <u>existing large area & new sources</u> :	(check ☑ only one box for each question)	
1.	Equipped all machines with the appropriate vent controls?	Yes No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes No N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes No	

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)		
B.	Does the responsible official of an existing large or new large area source also:	(check 🗹 only one box for each question)	Dr
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	Yes No N Yes No N	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No No	N/A
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	- 🗌 Yes 🗌 No 🖾 M	√A
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	🗌 Yes 🗌 No 🖾 N	N/A
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No X	N/A

PART V: <u>RECORDKEEPING</u> <u>REQUIREMENTS</u> – Rule 62-213.300(3) FAC		
Does the responsible official:	(check 🗹 only one box for each question)	
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No	
2. Maintain rolling monthly total of yearly perc consumption?	🛛 Yes 🗌 No	
3. Maintain leak detection inspection and repair reports for the following:		
a) documentation of leaks repaired w/in 24 hrs? or;	- 🛛 Yes 🗌 No 🗌 N/A	
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A	
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A	
5. Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ⊠ N/A	
6. Maintain a startup/shutdown/malfunction plan?	Yes 🗌 No	
7. Maintain deviation reports?	\sim Yes \square No \square N/A	
a) Problem corrected?	- \boxtimes Yes \square No \square N/A	
8. Maintain a compliance plan, if applicable?	Yes No N/A	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

2. Does the facility maintain a leak log?	detection and repair inspection?	Xes No	
a) Hose connections, fittings, couplings, and valves Yes No NA g) Muck cookers Yes No NA b) Door gakets and seating Yes No NA h) Stills Yes No NA c) Filter gaskets and seating Yes No NA i) Exhaust dampers Yes No NA d) Pumps Yes No NA i) Diverter valves Yes No NA e) Solvent tanks and containers Yes No NA k) Cartridge filter housings Yes No NA f) Water separators Yes No NA k) Cartridge filter housings Yes No NA f) Water separators Yes No NA k) Cartridge filter housings Yes No NA f) Water separators (condensed solvent on exterior surfaces) a) b) Physical detection (is/are) used by the responsible official? a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) C) d) Use of direct-reading instrumentation, is the equipment: exit N/A f) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) Yes No f) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) Yes No f) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) Yes No f) Verified for accuracy by use of duplicate samples (calorimetric only)? 3) Yes No f) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) Yes No f) Jeffrey Dizek	2. Does the facility maintain a leak log?	Xes 🗌 No	
a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) c) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) =**(see below) e) Halogen leak detector e) **#If using direct-reading instrumentation, is the equipment: ** n) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) = Yes n) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) = Yes n) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 2) = Yes n) Sinspected for leaks and obvious signs of wear on a weekly basis? 3) = Yes n) Kept in a clean and secure area when not in use? 3) = Yes n) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) = Yes No 5) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) = Yes No 12/18/2007 Inspector's Name (Please Print) Date of Inspection	 a) Hose connections, fittings, couplings, and valves b) Door gaskets and seating c) Filter gaskets and seating d) Pumps e) Solvent tanks and containers E) Solvent tanks and containers	tills XYes No N/A chaust dampers Yes No X/A iverter valves XYes No N/A	
Inspector's Name (Please Print) Date of Inspection 12/2008	a) Visual examination (condensed solvent on exterior surfaces) a) □ b) Physical detection (airflow felt through gaskets) b) □ c) Odor (noticeable perc odor) c) □ d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) □ **(see below) e) Halogen leak detector e) □ **If using direct-reading instrumentation, is the equipment: e) □ **If using direct-reading perc vapor concentrations in a range of 0-500 ppm? 1) □ Yes □ No 2) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) □ Yes □ No 3) Inspected for leaks and obvious signs of wear on a weekly basis? 3) □ Yes □ No 4) Kept in a clean and secure area when not in use? 4) □ Yes □ No		
12/2008	Jeffrey Dizek	12/18/2007	
	Inspector's Name (Please Print)	Date of Inspection	
Inspector's Signature Approximate Date of Next Inspection		12/2008	
	Inspector's Signature	Approximate Date of Next Inspection	

COMMENTS: