

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: AN	NUAL (INS1, INS2)	COMPLAINT/DISCOV	ERY (CI)	
RE	-INSPECTION (FUI)	ARMS COMPLAINT N	0:	
AIRS ID#: 0990574 DATE:	4/7/2009	ARRIVE: <u>1:10 PM</u>	DEPART: 2:00 PM	
FACILITY NAME: SUNSH	IINE CLEANERS			
FACILITY LOCATION:	6177 JOG RD			
	LAKE WORTH 33467			
OWNER/AUTHORIZED RI	EPRESENTATIVE: ENRI	IQUE CHERRES PHON	E: (561)379-6222	
CONTACT NAME: Same		PHON	E: (
ENTITLEMENT PERIOD:	5/1/2008 / 5/1/2013 (effective date) (end date)			
				1
PART I: <u>INSPECTION</u> <u>CO</u>		. —		
☑ IN COMPLIANCE	MINOR Non-COMP	LIANCE SIGNIFICA	ANT Non-COMPLIANCE	
PART II: <u>FACILITY CLAS</u> (check ☑ only on		3.300 FAC		
A. 1. Existing small are dry-to-dry only, x transfer only, x < both types, x < 14 (constructed before	< 140 gal/yr 200 gal/yr 0 gal/yr	2. New small area sour dry-to-dry only, x < 1 transfer only, x < 200 both types, x < 140 gr (constructed on or aft	40 gal/yr gal/yr al/yr	
	$40 \le x \le 2,100 \text{ gal/yr}$ $\le x \le 1,800 \text{ gal/yr}$ $x \le 1,800 \text{ gal/yr}$	4. New large area sour dry-to-dry only, $140 ext{ } ext{c}$ transfer only, $200 ext{ } ext{c}$ both types, $140 ext{ } ext{c} ext{c}$ (constructed on or aft	\leq x \leq 2,100 gal/yr \leq 1,800 gal/yr 1,800 gal/yr	
Ineligible for Ger drop store/out of be facility exceeds ab	ousiness/petroleum			

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	*	(check ☑ only one box				
Do	es the responsible official of the dry cleaning facility:	for each	on)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes [No	□N/A			
2.	Examine the containers for leakage?	⊠Yes [No	□ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes [No				
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes [No	□ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes [☐ No	⊠ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)						
	1. If the facility classification is a Existing small area source, no controls are requi	red. Proce	ed to F	Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993						
	4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.						
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)					
1.	Equipped all machines with the appropriate vent controls?	⊠Yes [No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes [□No	□N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes [No	□N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes [□No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes [□No	□N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes [□No				

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)						
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)				
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No				
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	∐Yes □ No ⊠N/A				
	a) Is the temperature differential equal to, or greater than $20^{\rm o}{\rm F?}$	☐Yes ☐ No ☒ N/A				
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A				
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A				
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes □ No ⊠ N/A				
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A				
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A				
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for				
Does the responsible official:		each question)				
1.	Maintain receipts for perc purchased?	- 🛚 Yes 🔲 No				
2.	Maintain rolling monthly total of yearly perc consumption?	∑ Yes ☐ No				
3.	Maintain leak detection inspection and repair reports for the following:					
	a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No No				
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A				
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A				
5.	Maintain exhaust duct monitoring data on perc concentrations?	Yes No No N/A				
6.	Maintain a startup/shutdown/malfunction plan?	Yes No				
7.	Maintain deviation reports?	Yes No N/A				
	a) Problem corrected?	- Xes No No N/A				
8.	Maintain a compliance plan, if applicable?	Yes No No N/A				

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

	M		
detection and repair inspection?	⊠ Yes □ No — —		
2. Does the facility maintain a leak log?	∑ Yes ☐ No		
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves	-		
4. Which method(s) of detection (is/are) used by the responsible official?			
a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) e) Halogen leak detector	b)		
**If using direct-reading instrumentation, is the equipment:	**		
1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm?	1) Yes No		
2) Calibrated against a standard gas prior to and after each use (PID/FID only)?	2) Yes No		
3) Inspected for leaks and obvious signs of wear on a weekly basis?			
4) Kept in a clean and secure area when not in use?			
5) Verified for accuracy by use of duplicate samples (calorimetric only)?	- 5) Yes No		
Jeffrey Dizek	4/7/2009		
Inspector's Name (Please Print) Date of Inspect	Date of Inspection		
	4/2010		
Inspector's Signature Approximate D	Date of Next Inspection		
COMMENTS:			